



SiLK Acceptance Tests

(SiLK-3.24.0)

CERT Software Automation Product Development

July 17, 2025

1 Introduction

SiLK, the System for Internet-Level Knowledge, is a collection of traffic analysis tools to facilitate security analysis of large networks. The SiLK tool suite supports the efficient collection, storage and analysis of network flow data, enabling network security analysts to rapidly query large historical traffic data sets.

The tools in SiLK suite can be grouped into two categories:

- The packing tools are responsible for collecting flow records, converting them to the SiLK format, categorizing them, and storing them in the data repository.
- The analysis tools read SiLK flow records from the data repository and can display, sort, or group the flow records by various attributes and compute the flow volume of each group.

This document describes the testing procedures used to verify that the tools in the SiLK suite are implemented correctly and work as advertised.

1.1 Legal notice

SiLK 3.24

Copyright 2025 Carnegie Mellon University.

NO WARRANTY. THIS CARNEGIE MELLON UNIVERSITY AND SOFTWARE ENGINEERING INSTITUTE MATERIAL IS FURNISHED ON AN "AS-IS" BASIS. CARNEGIE MELLON UNIVERSITY MAKES NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, AS TO ANY MATTER INCLUDING, BUT NOT LIMITED TO, WARRANTY OF FITNESS FOR PURPOSE OR MERCHANTABILITY, EXCLUSIVITY, OR RESULTS OBTAINED FROM USE OF THE MATERIAL. CARNEGIE MELLON UNIVERSITY DOES NOT MAKE ANY WARRANTY OF ANY KIND WITH RESPECT TO FREEDOM FROM PATENT, TRADEMARK, OR COPYRIGHT INFRINGEMENT.

Licensed under a GNU GPL 2.0-style license, please see LICENSE.txt or contact permission@sei.cmu.edu for full terms.

[DISTRIBUTION STATEMENT A] This material has been approved for public release and unlimited distribution. Please see Copyright notice for non-US Government use and distribution.

© 2009–2025 Carnegie Mellon University

 **Software Engineering Institute** | Carnegie Mellon

This Software includes and/or makes use of Third-Party Software each subject to its own license.

DM25-0915

1.2 Structure of this document

This document begins with a general description of SiLK and of some conventions used in the tests.

The remainder of the document consists of the tests themselves, broken down by functional area. Each test is referenced by the requirement it tests, and is broken down into the following sections:

Prerequisites If the test requires some conditions to be satisfied that are outside the scope of the test, they will be mentioned here. This section may not be present if there are no special prerequisites for running the test.

Preparation Steps to conduct prior to the test. Some of these steps may be unnecessary to repeat between tests. If something goes wrong during this phase, the test is considered impossible to run due to error.

Procedure Steps to conduct during the test. These steps should be performed in order each time the test is run.

Expected results The tester should verify that these items occur at the appropriate points in the test procedure. If they do not, the test is considered a failure.

2 Testing SiLK Analysis Tools

The tests for the SiLK Analysis Tools are included with the SiLK-3.24.0 source distribution. The tests are invoked by typing `make check` in an application build directory or at the top of the build tree to run the tests for all applications.

The data used to test is applications is created by a Perl script that generates text. This text is piped into the `rwttuc` application to create the SiLK flow records that are used for the tests.

The tests for an application invoke the application with various combinations of its options. Some tests are used to confirm that the application properly fails, for example, when incorrect or conflicting options are specified. Other tests confirm that the output of the application is correct. The output is assumed to be correct if the MD5 hash of the output matches an expected value. The expected value is determined or verified either by using unrelated SiLK applications or by directly processing the output produced by the Perl script that creates the text that was piped to `rwttuc`.

The tests for an application do not attempt an exhaustive permutation of all options, as that would require an extraordinary amount of time for the tests to complete. Knowledge of the software's source code is used to select options that exercise the majority of the application's functionality. When possible, unrelated options are used simultaneously to exercise multiple parts of the source code.

2.1 Prerequisites

The tests of the SiLK Analysis Tools require that Perl be installed on the system, and that the `Digest::MD5` Perl module is installed.

2.2 Preparation

The tests assume you have configured and built SiLK. The tests in this section use the application binaries as they exist in the build tree. The tests do not require that you install SiLK prior to running the tests.

2.3 Procedure

1. Go to the top of the directory where you built SiLK.
2. Type `make check`.

The full lists of tests that `make check` runs are listed in [Section 9](#).

2.4 Expected results

The tests will take several minutes to run.

During the tests, you may see the following sorts of output.

- The following indicates a test that successfully passed.

```
PASS: tests/rwstats-version.pl
```

- The following indicates a test has failed. For this failed test, information about why the test failed may be available in the file `tests/rwstats-sip24-top-pkt-p2.pl.log`.

```
FAIL: tests/rwstats-sip24-top-pkt-p2.pl
```

- The following indicates that the test was skipped. For this skipped test, information about why the test was skipped may be available in the file `tests/rwcut-icmp-type.pl.log`.

```
SKIP: tests/rwcut-icmp-type.pl
```

A test can be skipped for two reasons.

1. The test is not applicable. For example, there is no need to test IPv6 functionality if SiLK was not compiled with IPv6 support.
 2. A file or application that the test requires is not present. This can occur if you fail to build the SiLK tools prior to testing, so that `make check` is building the tools and testing them. Some tests use other tools in SiLK suite, and the tests will be skipped if the required tools are not available.
- The following indicates that no tests exist for the applications or libraries in the named directory.

```
Making check in plugins
```

```
make[2]: Nothing to be done for 'all'.
```

When you run `make check` from the top-level directory and all tests are successful, you should see output similar to the following once all processing stops, and the exit status of `make` should be 0.

```
make[2]: Nothing to be done for 'check'.
make[2]: Nothing to be done for 'check-am'.
```

If one or more tests in a directory (e.g., `src/rwcut`) fails, `make` will stop processing once it finishes running the tests in that particular directory, and `make` will exit with a non-zero status. The end of the output will resemble

```
=====
See src/rwcut/test-suite.log
Please report to netsa-help@cert.org
=====
make[4]: *** [test-suite.log] Error 1
make[3]: *** [check-TESTS] Error 2
make[2]: *** [check-am] Error 2
make[1]: *** [check-recursive] Error 1
make: *** [check-recursive] Error 1
```

In each directory that `make` visits, a summary of the results of running the tests in that directory is displayed. The summary resembles the following:

```
=====
Testsuite summary for SiLK 3.6.0
=====
# TOTAL: 51
# PASS: 45
# SKIP: 5
# XFAIL: 0
# FAIL: 1
# XPASS: 0
# ERROR: 0
=====
```

where

TOTAL is the number of tests that were run

PASS is the number of tests that passed

SKIP is the number of tests that were skipped

XFAIL will always be 0

FAIL is the number of tests that failed

XPASS will always be 0

ERROR is the number of tests that had a fatal error

When the sum of PASS and SKIP equals TOTAL, the **make** command exits with a status of 0 to indicate that no test failed.

If either FAIL or ERROR is non-zero, one or more tests failed and the return status of **make** will be non-zero.

In each directory, details about why a test was skipped or why a test failed can be found in the **test-suite.log** file in that directory as well as in the ***.log** files in the **tests** subdirectory of that directory.

3 Testing **rwscanquery**

rwscan is an application that reads SiLK flow records representing incoming traffic, attempts to find external hosts that are scanning the monitored network, and produces textual output describing what it found. Although the design concept of **rwscan** has it running periodically on the SiLK data files and inserting its results into a database, **rwscan** operates like most SiLK analysis tools: it is a self-contained program that reads SiLK flow records from the files listed on the command line or from the standard input and it produces textual output.

rwscanquery is a script that queries the database populated by the results from invocations of **rwscan**. Depending on the report that the user requests, **rwscanquery** will create textual output, binary IPset files, or files of SiLK flow records.

One of report options available from **rwscanquery** allows an analyst to provide a time window and an IPset of internal hosts to determine what external hosts scanned those internal hosts during the time window. However, the results from the **rwscan** program include the (external) hosts that are scanning the network, but they do not include the (internal) hosts that were the target of a scan. Thus, to produce its report, the **rwscanquery** program first asks the database for the external hosts that were scanning during the time window, then it uses **rwfilter** to find flow records from the scanning IPs that targeted the IPs in the IPset file provided by the analyst.

There are additional report options in **rwscanquery** that operate similarly. For all of these report types to produce output, **rwscanquery** must invoke other SiLK analysis tools (e.g., **rwsetbuild**, **rwfilter**), and **rwscanquery** requires access to a SiLK data repository.

The tests for **rwscan** and **rwscanquery** are included with the SiLK-3.24.0 source distribution. The tests are invoked by typing **make check** in the **src/rwscan** directory. (If you type **make check** at the top of the build tree, the **rwscan** tests will be invoked as **make** recursively descends into each directory.)

The tests are written in Perl. The tests use fictional data and they will confirm that **rwscan** finds potential scanners and that **rwscanquery** can query a SiLK data repository to produce the various reports that it supports.

Since **rwscan** is a self-contained program and the results from **rwscan** are textual, the results from one **rwscan** invocation are easy to compare with previous invocations. Ensuring that **rwscanquery** is operating correctly is a greater challenge, since it invokes other tools. This document describes the tests that check the behavior of **rwscanquery**.

3.1 Prerequisites

The tests of **rwscan** and **rwscanquery** require that the following tools are installed on the system:

- the `sqlite3` program
- Perl 5.6 or later
- the Perl module `Digest::MD5`
- the Perl module `DBD::SQLite`

3.2 Preparation

The test scripts assume you have configured and built `rwscan`, `rwscanquery`, and all the libraries they require. The scripts use the application binary as it exists in the build tree, and the scripts do not require that you install SiLK prior to running the tests.

During the test, a temporary directory is created, and files and subdirectories are created in this directory. The directory is created in the location specified by the `TMPDIR` environment variable, or in `/tmp` when the `TMPDIR` environment variable is not set.

3.3 Procedure

1. Go to `src/rwscan` subdirectory in the directory tree where you built SiLK.
2. Type `make check`. This will invoke the tests that check the behaviors of all the applications in the `src/rwscan` directory, including `rwscan` and `rwscanquery`.

The following behaviors are tested.

1. Verify that `rwscan` query produces the expected textual output when running over fictional data.
2. Write the results from `rwscan` into a SQLite database.
3. Verify that `rwscanquery` can query the SQLite database and export textual output that matches the results from `rwscan`.
4. Verify that `rwscanquery` can produce textual output summarizing the scan volume seen per day.
5. Verify that `rwscanquery` can query the SQLite database for a particular scanning subnet and write the result as text.
6. Verify that `rwscanquery` can query the SQLite database for scanning IP addresses contained in an IPset. The results from `rwscanquery` are written as text.
7. Verify that `rwscanquery` can query the SQLite database over a particular time window and write the result as text.
8. Verify that `rwscanquery` can query the SQLite database and write an IPset file containing the scanning IPs for all records in the database.
9. Verify that `rwscanquery` can query the SQLite database and write an IPset file containing the scanning IPs that targeted a subnet of internal IP addresses.
10. Verify that `rwscanquery` can query the SQLite database and write an IPset file containing the scanning IPs that targeted internal IP addresses listed in an IPset file.

11. Verify that `rwscanquery` can query the SQLite database and write a SiLK flow file containing incoming records that originated from all scanning IPs.
12. Verify that `rwscanquery` can query the SQLite database and write a SiLK flow file containing incoming records that originated from (external) scanning IPs specified by one subnet that targeted (internal) IPs specified by another subnet.
13. Verify that `rwscanquery` can query the SQLite database and write a SiLK flow file containing incoming records that originated from scanning IPs listed in an IPset file that targeted IPs specified by a subnet.
14. Verify that `rwscanquery` can query the SQLite database and write a SiLK flow file containing incoming records that originated from scanning IPs specified by a subnet that targeted IPs listed in an IPset file.
15. Verify that `rwscanquery` can query the SQLite database and write a SiLK flow file containing outgoing records that originated from internal IPs and that may have been responses to activity by the scanning IPs for all internal IPs and scanning IPs.
16. Verify that `rwscanquery` can query the SQLite database and write a SiLK flow file containing outgoing records that originated from internal IPs specified by a subnet and that may have been responses to activity by scanning IPs listed in an IPset file.
17. Verify that `rwscanquery` can query the SQLite database and write a SiLK flow file containing outgoing records that originated from internal IPs specified by a subnet and that may have been responses to activity by scanning IPs specified by another subnet.
18. Verify that `rwscanquery` can query the SQLite database and write a SiLK flow file containing outgoing records that may have been responses from internal IPs listed in an IPset file and that may have been responses to activity by scanning IPs specified by a subnet.

3.4 Expected results

The tests may take several minutes to run.

During the tests, you may see the following sorts of output.

- The following indicates a test that successfully passed.

```
PASS: tests/rwscanquery-sqlite.pl
```

- The following indicates a test has failed. For this failed test, information about why the test failed may be available in the file `tests/rwscanquery-sqlite.pl.log`.

```
FAIL: tests/rwscanquery-sqlite.pl
```

- The following indicates that the test was skipped. For this skipped test, information about why the test was skipped may be available in the file `tests/rwscanquery-sqlite.pl.log`.

```
SKIP: tests/rwscanquery-sqlite.pl
```

A test will be skipped if a file or application that the test requires is not present. This can occur if the prerequisites described above are not available, or it can occur if you fail to build the SiLK tools prior to testing, so that `make check` is building the tools and testing them. Some tests use other tools in SiLK suite, and the tests will be skipped if the required tools are not available.

Once all processing stops, you should see output similar to the following to summarize the results of running the tests.

```
=====
Testsuite summary for SiLK 3.6.0
=====
# TOTAL: 13
# PASS: 12
# SKIP: 1
# XFAIL: 0
# FAIL: 0
# XPASS: 0
# ERROR: 0
=====
```

where

TOTAL is the number of tests that were run

PASS is the number of tests that passed

SKIP is the number of tests that were skipped

XFAIL will always be 0

FAIL is the number of tests that failed

XPASS will always be 0

ERROR is the number of tests that had a fatal error

When the sum of PASS and SKIP equals TOTAL, the `make` command exits with a status of 0 to indicate that no test failed.

If either FAIL or ERROR is non-zero, one or more tests failed and the return status of `make` will be non-zero.

Details about why a test was skipped or why a test failed can be found in the `test-suite.log` file in the `src/rwscanquery` directory as well as in the `*.log` files in the `src/rwscanquery/tests` directory.

4 Testing rwsender and rwreceiver

`rwsender` is a daemon which transfers files over the network to one or more `rwreceiver` daemons. An `rwreceiver` may accept files from multiple `rwsenders`. Either `rwsender` or `rwreceiver` may act as the server and accept connections from `rwreceiver` or `rwsender` processes acting as clients. The connection between `rwsender` and `rwreceiver` may be encrypted using GnuTLS.

rwsender and **rwreceiver** do not require the files they transfer to have any particular format; they treat the contents of the files as a stream of bytes.

The tests will determine whether **rwsender** can successfully send files to **rwreceiver** processes, and whether an **rwreceiver** can successfully receive files from **rwsender** processes. If SiLK was configured with GnuTLS support, tests will also be conducted using GnuTLS.

Tests are included with the SiLK-3.24.0 distribution that run tests on **rwsender** and **rwreceiver**. To run the tests, go into the **src/sendrcv** directory and type **make check**. (If you type **make check** at the top of the build tree, the tests will be invoked as **make** recursively descends into each directory.) The tests invoke the daemons, have them connect, send files, and shut down. Some of the tests will involve shutting down one side of the connection during file transfer to verify that the other side handles that situation correctly.

4.1 Prerequisites

The tests of **rwsender** and **rwreceiver** require that the following tools are installed on the system:

- Python 2.6 or later
- Perl 5.6 or later
- the Perl module Digest::MD5

4.2 Preparation

The test script assumes you have configured and built **rwsender**, **rwreceiver**, and all the libraries they require. The script uses the application binaries as they exist in the build tree, and the script does not require that you install SiLK prior to running the tests.

During many of the tests, a temporary directory is created, and files and subdirectories are created in this directory. The directory is created in the location specified by the TMPDIR environment variable, or in **/tmp** when the TMPDIR environment variable is not set.

4.3 Procedure

1. Go to **src/sendrcv** subdirectory in the directory tree where you built SiLK.
2. Type **make check**. This will invoke some basic checks on **rwsender** and **rwreceiver** and then invoke the scripts that attempt to connect them.

The **rwsender/rwreceiver** tests check the following behaviors:

1. **Use of **rwreceiver** init script.** Confirm that the shell script designed for the **/etc/init.d** directory supports starting, stopping, and checking the status of **rwreceiver**.
2. **Use of **rwsender** init script.** Confirm that the shell script designed for the **/etc/init.d** directory supports starting, stopping, and checking the status of **rwsender**.

3. **Simple connection to 127.0.0.1.** With `rwreceiver` acting as a server and `rwsender` acting as a client, check whether `rwsender` and `rwreceiver` start correctly, establish a connection when connecting as the IPv4 localhost address, and shut down cleanly.
4. **Simple connection to localhost.** This test is similar to the previous, except the connection is made using “localhost”.
5. **Simple connection to ::1.** This test is similar to the previous, except the connection is made using the IPv6 localhost address. This test is skipped when IPv6 networking support is not available.
6. **GnuTLS connection.** With `rwreceiver` acting as a server and `rwsender` acting as a client, check whether `rwsender` and `rwreceiver` start correctly, establish a connection using GnuTLS, and shut down cleanly. This test uses certificates that are included in the SiLK source code. This test is skipped when GnuTLS support is not available.
7. **GnuTLS connection with other certificates.** With `rwsender` acting as a server and `rwreceiver` acting as a client, check whether `rwsender` and `rwreceiver` start correctly, establish a connection using GnuTLS, and shut down cleanly. This test uses certificates that are included in the SiLK source code and different than those used in the previous test. This test is skipped when GnuTLS support is not available.
8. **Failed connection: mismatched certifiates.** With `rwsender` acting as a server and `rwsender` acting as a client, check whether `rwsender` and `rwreceiver` start correctly, attempt to establish a connection, have the connection rejected due to having their certificates signed by different authorities, and shut down cleanly. `rwreceiver` uses the certificates from the previous test, while `rwsender` uses the certificates used two tests ago. This test is skipped when GnuTLS support is not available.
9. **Failed connection: expired certificate.** With `rwreceiver` acting as a server and `rwsender` acting as a client, check whether `rwsender` and `rwreceiver` start correctly, attempt to establish a connection, have the connection rejected due to an expired TLS certificate, and shut down cleanly. This test uses certificates that are included in the SiLK source code. This test is skipped when GnuTLS support is not available.
10. **Failed connection: expired authority.** With `rwreceiver` acting as a server and `rwsender` acting as a client, check whether `rwsender` and `rwreceiver` start correctly, attempt to establish a connection, have the connection rejected due to a certificate signed by an expired certificate authority, and shut down cleanly. This test uses certificates that are included in the SiLK source code. This test is skipped when GnuTLS support is not available.
11. **Stop rwreceiver server.** With `rwreceiver` acting as a server and `rwsender` acting as a client, check whether `rwsender` and `rwreceiver` start correctly, establish a connection, and begin to transfer files. During file transfer, send `rwreceiver` a SIGTERM, causing it to shut down cleanly. Restart `rwreceiver` and verify that the connection is reestablished and that file transfer resumes. Finally, check whether `rwsender` and `rwreceiver` shut down cleanly.
12. **Stop rwreceiver server when using GnuTLS.** This test is similar to the previous, except the connections are made with GnuTLS. This test uses certificates that are included in the SiLK source code. This test is skipped when GnuTLS support is not available.
13. **Stop rwsender server.** With `rwsender` acting as a server and `rwreceiver` acting as a client, check whether `rwsender` and `rwreceiver` start correctly, establish a connection, and begin to transfer files. During file transfer, send `rwsender` a SIGTERM, causing it to shut down cleanly. Restart `rwsender` and verify that the connection is reestablished and that file transfer resumes. Finally, check whether `rwsender` and `rwreceiver` shut down cleanly.
14. **Stop rwsender server when using GnuTLS.** This test is similar to the previous, except the connections are made with GnuTLS. This test uses certificates that are included in the SiLK source code. This test is skipped when GnuTLS support is not available.

15. **Stop `rwreceiver` client.** With `rwsender` acting as a server and `rwreceiver` acting as a client, check whether `rwsender` and `rwreceiver` start correctly, establish a connection, and begin to transfer files. During file transfer, send `rwreceiver` a SIGTERM, causing it to shut down cleanly. Restart `rwreceiver` and verify that the connection is reestablished and that file transfer resumes. Finally, check whether `rwsender` and `rwreceiver` shut down cleanly.
16. **Stop `rwreceiver` client using GnuTLS.** This test is similar to the previous, except the connections are made with GnuTLS. This test uses certificates that are included in the SiLK source code. This test is skipped when GnuTLS support is not available.
17. **Stop `rwsender` client.** With `rwreceiver` acting as a server and `rwsender` acting as a client, check whether `rwsender` and `rwreceiver` start correctly, establish a connection, and begin to transfer files. During file transfer, send `rwsender` a SIGTERM, causing it to shut down cleanly. Restart `rwsender` and verify that the connection is reestablished and that file transfer resumes. Finally, check whether `rwsender` and `rwreceiver` shut down cleanly.
18. **Stop `rwsender` client when using GnuTLS.** This test is similar to the previous, except the connections are made with GnuTLS. This test uses certificates that are included in the SiLK source code. This test is skipped when GnuTLS support is not available.
19. **Kill `rwreceiver` server.** With `rwreceiver` acting as a server and `rwsender` acting as a client, check whether `rwsender` and `rwreceiver` start correctly, establish a connection, and begin to transfer files. During file transfer, send `rwreceiver` a SIGKILL, causing it to abruptly shut down. Check whether `rwsender` handles the sudden loss of connectivity. Restart `rwreceiver` and verify that the connection is reestablished and that file transfer resumes. Finally, check whether `rwsender` and `rwreceiver` shut down cleanly.
20. **Kill `rwreceiver` server when using GnuTLS.** This test is similar to the previous, except the connections are made with GnuTLS. This test uses certificates that are included in the SiLK source code. This test is skipped when GnuTLS support is not available.
21. **Kill `rwsender` server.** With `rwsender` acting as a server and `rwreceiver` acting as a client, check whether `rwsender` and `rwreceiver` start correctly, establish a connection, and begin to transfer files. During file transfer, send `rwsender` a SIGKILL, causing it to abruptly shut down. Check whether `rwreceiver` handles the sudden loss of connectivity. Restart `rwsender` and verify that the connection is reestablished and that file transfer resumes. Finally, check whether `rwsender` and `rwreceiver` shut down cleanly.
22. **Kill `rwsender` server when using GnuTLS.** This test is similar to the previous, except the connections are made with GnuTLS. This test uses certificates that are included in the SiLK source code. This test is skipped when GnuTLS support is not available.
23. **Kill `rwreceiver` client.** With `rwsender` acting as a server and `rwreceiver` acting as a client, check whether `rwsender` and `rwreceiver` start correctly, establish a connection, and begin to transfer files. During file transfer, send `rwreceiver` a SIGKILL, causing it to abruptly shut down. Check whether `rwsender` handles the sudden loss of connectivity. Restart `rwreceiver` and verify that the connection is reestablished and that file transfer resumes. Finally, check whether `rwsender` and `rwreceiver` shut down cleanly.
24. **Kill `rwreceiver` client when using GnuTLS.** This test is similar to the previous, except the connections are made with GnuTLS. This test uses certificates that are included in the SiLK source code. This test is skipped when GnuTLS support is not available.
25. **Kill `rwsender` client.** With `rwreceiver` acting as a server and `rwsender` acting as a client, check whether `rwsender` and `rwreceiver` start correctly, establish a connection, and begin to transfer files. During file transfer, send `rwsender` a

SIGKILL, causing it to abruptly shut down. Check whether **rwreceiver** handles the sudden loss of connectivity. Restart **rwsender** and verify that the connection is reestablished and that file transfer resumes. Finally, check whether **rwsender** and **rwreceiver** shut down cleanly.

26. **Kill rwsender client when using GnuTLS.** This test is similar to the previous, except the connections are made with GnuTLS. This test uses certificates that are included in the SiLK source code. This test is skipped when GnuTLS support is not available.
27. **Multiple connections.** Start two **rwreceiver** processes acting as clients and two **rwsender** processes acting as servers. Check whether each of the **rwreceiver** clients establish a connection with each of the **rwsender** servers. Verify that files from each **rwsender** are sent to each **rwreceiver**. Check whether all four daemons shut down cleanly.
28. **Multiple connections when using GnuTLS.** This test is similar to the previous, except the connections are made with GnuTLS. This test uses certificates that are included in the SiLK source code. This test is skipped when GnuTLS support is not available.
29. **Filtering.** Start two **rwreceiver** processes acting as clients and a single **rwsender** process acting as a server. Check whether each of the **rwreceiver** clients establish a connection with **rwsender**. Use filtering rules on **rwsender** so that a subset of the files are sent to each **rwreceiver**. Verify that the correct files are sent. Check whether all three daemons shut down cleanly.
30. **Post processing.** Start **rwreceiver** acting as a server and **rwsender** acting as a client. Establish a connection and successfully transfer files. For each file, verify that the command specified **rwreceiver**'s **--post-command** switch is executed. Check whether the daemons shut down cleanly.

4.4 Expected results

The tests may take several minutes to run.

During the tests, you will see the following sorts of output.

- The following indicates a test that successfully passed.

```
PASS: tests/sendrcv-testConnectOnlyIPv4Addr.pl
```

- The following indicates a test has failed. For this failed test, information about why the test failed may be available in the file `tests/sendrcv-testConnectOnlyIPv6Addr.pl.log`.

```
FAIL: tests/sendrcv-testConnectOnlyIPv6Addr.pl
```

- The following indicates that the test was skipped. For this skipped test, information about why the test was skipped may be available in the file `tests/sendrcv-testConnectOnlyTLS.pl.log`.

```
SKIP: tests/sendrcv-testConnectOnlyTLS.pl
```

A test can be skipped for the following reason:

1. The test is not applicable. For example, there is no need to test GnuTLS functionality if SiLK was not compiled with GnuTLS support.

Once all processing stops, you should see output similar to the following to summarize the results of running the tests.

```
=====
Testsuite summary for SiLK 3.6.0
=====
# TOTAL: 30
# PASS: 20
# SKIP: 10
# XFAIL: 0
# FAIL: 0
# XPASS: 0
# ERROR: 0
=====
```

where

TOTAL is the number of tests that were run

PASS is the number of tests that passed

SKIP is the number of tests that were skipped

XFAIL will always be 0

FAIL is the number of tests that failed

XPASS will always be 0

ERROR is the number of tests that had a fatal error

When the sum of PASS and SKIP equals TOTAL, the **make** command exits with a status of 0 to indicate that no test failed.

If either FAIL or ERROR is non-zero, one or more tests failed and the return status of **make** will be non-zero.

Details about why a test was skipped or why a test failed can be found in the **test-suite.log** file in the **src/sendrcv** directory as well as in the ***.log** files in the **src/sendrcv/tests** directory.

A note on tests that fail: The Python code that drives the test makes heavy use of Python threads, and there have been instances where a test fails due to errors in Python, not because of errors in the **rwsender** or **rwreceiver** daemons.

5 Testing rwflowappend

The **rwflowappend** daemon is used to support multiple copies of the data store, or to allow the data to be stored on a machine separate from the machine where **rwflowpack** is running. Typically an **rwsender-rwreceiver** pair is used to move the data files from **rwflowpack** to **rwflowappend**. For testing purposes, the method used to inject files into **rwflowappend** is immaterial.

The tests for `rwflowappend` are included with the SiLK-3.24.0 source distribution. The tests are invoked by typing `make check-rwflowappend` in the `src/rwflowpack` directory. (If you type `make check` at the top of the build tree, the `rwflowappend` tests will be invoked as `make` recursively descends into each directory.)

The tests are written in a combination of Perl and Python. The tests will confirm that the `rwflowappend` daemon can start, process files, and terminate cleanly. The tests also confirm that `rwflowappend` handles unusual input files correctly.

5.1 Prerequisites

The tests of `rwflowappend` require that the following tools are installed on the system:

- Python 2.6 or later
- Perl 5.6 or later
- the Perl module `Digest::MD5`

5.2 Preparation

The test scripts assume you have configured and built `rwflowappend` and all the libraries it requires. The scripts use the application binary as it exists in the build tree, and the scripts do not require that you install SiLK prior to running the tests.

During many of the tests, a temporary directory is created, and files and subdirectories are created in this directory. The directory is created in the location specified by the `TMPDIR` environment variable, or in `/tmp` when the `TMPDIR` environment variable is not set.

5.3 Procedure

1. Go to `src/rwflowpack` subdirectory in the directory tree where you built SiLK.
2. Type `make check-rwflowappend`. This will invoke the tests that check the behavior of `rwflowappend`.

The `rwflowappend` tests check the following behaviors:

1. **Use of `rwflowappend` init script.** Confirm that the shell script designed for the `/etc/init.d` directory supports starting, stopping, and checking the status of `rwflowappend`.
2. **Append IPv4.** Check whether `rwflowappend` properly handles two files that exist in its incoming directory when `rwflowappend` is invoked. `rwflowappend` will create a new hourly data file, and append the second file to that hourly file. Both input files will be moved to the archive directory. When `rwflowappend` receives a signal, it should shut down cleanly. This test uses input files that contain only IPv4 data.
3. **Append IPv6.** This test is similar to the previous, except it uses a data file that contains IPv6 data. This test is only invoked when SiLK has been compiled with IPv6 support.

4. **Post processing.** Check whether `rwflowappend` properly handles the `--hour-file-command` and `--post-command` switches to notice a new hourly file and to process an incoming file after `rwflowappend` has processed it. This test is similar to the “Append IPv4” test; in addition, the `--hour-file-command` will write the name of the hourly file to a text file, and the `--post-command` will copy the incoming files to a separate location. When `rwflowappend` receives a signal, it should shut down cleanly.
5. **Time window.** Check whether `rwflowappend` properly handles the `--reject-hours-past` and `--reject-hours-future` switches. Files containing records with start times before the `--reject-hours-past` or after the `--reject-hours-future` times are stored in the error directory. All other files should appear in the archive directory and corresponding data files should be created. When `rwflowappend` receives a signal, it should shut down cleanly.
6. **Bad input.** Check whether `rwflowappend` properly handles unusual files in its incoming directory. One file is a SiLK data file that contains no records; `rwflowappend` should move this file to the archive directory and not create an hourly data file. The second unusual file is a file that does not contain the SiLK file header. `rwflowappend` should move this file into its error directory.
7. **Many input files.** Check whether `rwflowappend` properly handles combining about 16,925 incremental files into 432 hourly files. The incremental files exist in `rwflowappend`’s incoming directory when it is invoked. To create an each hourly file, `rwflowappend` will combine approximately 39 incremental files. The input files will be deleted. When `rwflowappend` receives a signal, it should shut down cleanly. To create the incremental files, the test runs `rwflowpack` in sending mode which creates 432 incremental files, and then the test runs `rwsplit` on each of those files. This test uses input files that contain only IPv4 data.

5.4 Expected results

The tests may take several minutes to run.

During the tests, you may see the following sorts of output.

- The following indicates a test that successfully passed.

```
PASS: tests/rwflowappend-version.pl
```

- The following indicates a test has failed. For this failed test, information about why the test failed may be available in the file `tests/rwflowappend-append-ipv4.pl.log`.

```
FAIL: tests/rwflowappend-append-ipv4.pl
```

- The following indicates that the test was skipped. For this skipped test, information about why the test was skipped may be available in the file `tests/rwflowappend-append-ipv6.pl.log`.

```
SKIP: tests/rwflowappend-append-ipv6.pl
```

A test can be skipped for two reasons.

1. The test is not applicable. For example, there is no need to test IPv6 functionality if SiLK was not compiled with IPv6 support.

2. A file or application that the test requires is not present. This can occur if you fail to build the SiLK tools prior to testing, so that **make check** is building the tools and testing them. Some tests use other tools in SiLK suite, and the tests will be skipped if the required tools are not available.

Once all processing stops, you should see output similar to the following to summarize the results of running the tests.

```
=====
Testsuite summary for SiLK 3.6.0
=====
# TOTAL: 8
# PASS: 7
# SKIP: 1
# XFAIL: 0
# FAIL: 0
# XPASS: 0
# ERROR: 0
=====
```

where

TOTAL is the number of tests that were run

PASS is the number of tests that passed

SKIP is the number of tests that were skipped

XFAIL will always be 0

FAIL is the number of tests that failed

XPASS will always be 0

ERROR is the number of tests that had a fatal error

When the sum of PASS and SKIP equals TOTAL, the **make** command exits with a status of 0 to indicate that no test failed.

If either FAIL or ERROR is non-zero, one or more tests failed and the return status of **make** will be non-zero.

Details about why a test was skipped or why a test failed can be found in the **test-suite.log** file in the **src/rwflowpack** directory as well as in the ***.log** files in the **src/rwflowpack/tests** directory.

6 Testing flowcap

The flowcap daemon listens on user-specified network ports to collect NetFlow v5 and/or IPFIX flow records that are created by flow generators. Examples of flow generators include routers and software that processes packet capture (**libpcap**) data. flowcap converts the flow records into a SiLK format and stores the records in temporary files. These files are later processed

by **rwflowpack**. The typical way to transfer files from flowcap to **rwflowpack** is via an **rwsender**–**rwreceiver** pair, though the administrator is free to use other software (such as **scp** or **rsync**).

At a minimum, the tests will determine whether flowcap can receive NetFlow v5 packets when listening on an IPv4 port. If flowcap was built with libfixbuf support, tests will be run to test receiving IPFIX packets. If IPv6 networking support is enabled, tests will be conducted with flowcap listening on an IPv6 port. If SiLK is built with support for storing IPv6 flow records, a test is run that sends IPFIX packets containing IPv6 addresses to flowcap listening on an IPv6 port.

The tests for flowcap are included with the SiLK-3.24.0 source distribution. The tests are invoked by typing **make check** in the **src/flowcap** directory. (If you type **make check** at the top of the build tree, the flowcap tests will be invoked as **make** recursively descends into each directory.)

The tests are written in a combination of Perl and Python. The tests will confirm that the flowcap daemon can start, read data from the network, write the data into files, and terminate cleanly. Verifying that the files produced by flowcap are consistent is sufficient; it is not necessary in these tests to confirm that **rwflowpack** can process the files.

6.1 Prerequisites

The tests of flowcap require that the following tools are installed on the system:

- Python 2.6 or later
- Perl 5.6 or later
- the Perl module Digest::MD5
- the Perl module Socket6

6.2 Preparation

The test scripts assume you have configured and built flowcap and all the libraries it requires. The scripts use the application binary as it exists in the build tree, and the scripts do not require that you install SiLK prior to running the tests.

During many of the tests, a temporary directory is created, and files and subdirectories are created in this directory. The directory is created in the location specified by the TMPDIR environment variable, or in **/tmp** when the TMPDIR environment variable is not set.

6.3 Procedure

1. Go to **src/flowcap** subdirectory in the directory tree where you built SiLK.
2. Type **make check**. This will invoke the scripts that check the behavior of flowcap.

The flowcap tests check the following behaviors:

1. **Use of flowcap init script.** Confirm that the shell script designed for the **/etc/init.d** directory supports starting, stopping, and checking the status of flowcap.

2. **Collect NetFlow v5 records when listening as 127.0.0.1.** Check whether flowcap properly starts, accepts NetFlow v5 UDP packets on a UDP port bound to the IPv4 localhost address, converts the NetFlow v5 packets to SiLK flow records, and shuts down cleanly.
3. **Collect NetFlow v5 records when listening as any host.** Check whether flowcap properly starts, accepts NetFlow v5 UDP packets from the IPv4 localhost address when listening on a UDP port bound to the any address, converts the NetFlow v5 packets to SiLK flow records, and shuts down cleanly.
4. **Collect NetFlow v5 records when listening as ::1.** Check whether flowcap properly starts, accepts NetFlow v5 UDP packets from the IPv6 localhost when listening on a UDP port bound to the IPv6 localhost address, converts the NetFlow v5 packets to SiLK flow records, and shuts down cleanly.
5. **Collect IPFIX records when listening as 127.0.0.1.** Check whether flowcap properly starts, accepts IPFIX packets on a TCP port bound to the IPv4 localhost address, converts the IPFIX packets to SiLK flow records, and shuts down cleanly. The IPFIX packets contain only IPv4 addresses.
6. **Collect IPFIX records when listening as any host.** Check whether flowcap properly starts, accepts IPFIX packets from the IPv4 localhost address when listening on a TCP port bound to the any addresses, converts the IPFIX packets to SiLK flow records, and shuts down cleanly. The IPFIX packets contain only IPv4 addresses.
7. **Collect IPFIX records over UDP when listening as 127.0.0.1.** Check whether flowcap properly starts, accepts IPFIX packets on a UDP port bound to the IPv4 localhost address, converts the IPFIX packets to SiLK flow records, and shuts down cleanly. The IPFIX packets contain only IPv4 addresses.
8. **Collect IPFIX records when listening as ::1.** Check whether flowcap properly starts, accepts IPFIX packets from the IPv6 localhost address when listening on a TCP port bound to the IPv6 localhost address, converts the IPFIX packets to SiLK flow records, and shuts down cleanly. The IPFIX packets contain only IPv4 addresses.
9. **Collect IPv6 IPFIX records when listening as ::1.** Check whether flowcap properly starts, accepts IPFIX packets from the IPv6 localhost address when listening on a TCP port bound to the IPv6 localhost address, converts the IPFIX packets to SiLK flow records, and shuts down cleanly. The IPFIX packets contain only IPv6 addresses.

6.4 Expected results

The tests may take several minutes to run.

During the tests, you will see the following sorts of output.

- The following indicates a test that successfully passed.

```
PASS: tests/flowcap-version.pl
```

- The following indicates a test has failed. For this failed test, information about why the test failed may be available in the file `tests/flowcap-append-ipv4.pl.log`.

```
FAIL: tests/flowcap-append-ipv4.pl
```

- The following indicates that the test was skipped. For this skipped test, information about why the test was skipped may be available in the file `tests/flowcap-ipfix.pl.log`.

SKIP: `tests/flowcap-ipfix.pl`

A test can be skipped for two reasons.

1. The test is not applicable. For example, there is no need to test IPFIX functionality if SiLK was not compiled with IPFIX support.
2. A file or application that the test requires is not present. This can occur if you fail to build the SiLK tools prior to testing, so that `make check` is building the tools and testing them. Some tests use other tools in SiLK suite, and the tests will be skipped if the required tools are not available.

Once all processing stops, you should see output similar to the following to summarize the results of running the tests.

```
=====
Testsuite summary for SiLK 3.19.1
=====
# TOTAL: 12
# PASS: 11
# SKIP: 1
# XFAIL: 0
# FAIL: 0
# XPASS: 0
# ERROR: 0
=====
```

where

TOTAL is the number of tests that were run

PASS is the number of tests that passed

SKIP is the number of tests that were skipped

XFAIL will always be 0

FAIL is the number of tests that failed

XPASS will always be 0

ERROR is the number of tests that had a fatal error

When the sum of PASS and SKIP equals TOTAL, the `make` command exits with a status of 0 to indicate that no test failed.

If either FAIL or ERROR is non-zero, one or more tests failed and the return status of `make` will be non-zero.

Details about why a test was skipped or why a test failed can be found in the `test-suite.log` file in the `src/flowcap` directory as well as in the `*.log` files in the `src/flowcap/tests` directory.

7 Testing `rwflowpack`

`rwflowpack` is the heart of the SiLK packing system. It may either collect NetFlow v5 and/or IPFIX flow records itself (similar to `flowcap`), or it may process the following types of files:

- files created by `flowcap`
- files containing NetFlow v5 PDUs, such as those created by NetFlow Collector
- files generated by the `yaf` program which contain IPFIX flow records
- files containing SiLK flow records generated by other SiLK applications

`rwflowpack` is responsible for deciding how and where each flow record gets written into the data store. `rwflowpack` splits the flow data by hour and chooses a *flowtype* (also called a *class/type* pair) for the record according to “packing logic”. The packing logic normally categorizes data as incoming or outgoing, and it chooses an appropriate file format for the data.

There are four input-modes for `rwflowpack`.

- In “stream” input mode, `rwflowpack` opens an input “stream” for every *probe* listed in the `sensor.conf` file. These streams can be network ports where `rwflowpack` will read NetFlow v5 or IPFIX records, or they can be directories that are routinely polled for files containing NetFlow v5 PDUs, IPFIX records, or SiLK files.
- In “fcbfiles” input mode, `rwflowpack` polls a directory for files created by `flowcap`. In this mode, the probe definitions in the `sensor.conf` file are ignored, and instead `rwflowpack` uses the probe name written into each file’s header.
- In “pdufile” input mode, `rwflowpack` reads NetFlow v5 PDUs from a single file specified on the command line, then `rwflowpack` exits.
- In “respool” input mode, `rwflowpack` does not recategorize the data; instead, `rwflowpack` reads SiLK flow files and puts each record into a flow file using the sensor and class/type values that already exist on the record.

There are two output-modes for `rwflowpack`. In the first, `rwflowpack` writes the data directly to the data store; this is called “local-storage” mode. In the second (called “sending” mode), `rwflowpack` stores the flow records in temporary files, and an `rwflowappend` process is responsible for writing the flow records into the data store. Typically `rwflowpack` and `rwflowappend` are running on separate machines, and an `rwsender-rwreceiver` pair is used to transfer the temporary files between the machines.

The tests for `rwflowpack` are included with the SiLK-3.24.0 source distribution. The tests are invoked by typing `make check-rwflowpack` in the `src/rwflowpack` directory. (If you type `make check` at the top of the build tree, the `rwflowpack` tests will be invoked as `make` recursively descends into each directory.)

The tests are written in a combination of Perl and Python. The tests will confirm that the `rwflowpack` daemon can start, process files, and terminate cleanly. The tests also confirm that `rwflowpack` handles unusual input files correctly.

7.1 Prerequisites

The tests of `rwflowpack` require that the following tools are installed on the system:

- Python 2.6 or later
- Perl 5.6 or later
- the Perl module Digest::MD5
- the Perl module Socket6

7.2 Preparation

The test scripts assume you have configured and built **rwflowpack** and all the libraries it requires. The scripts use the application binary as it exists in the build tree, and the scripts do not require that you install SiLK prior to running the tests.

During many of the tests, a temporary directory is created, and files and subdirectories are created in this directory. The directory is created in the location specified by the `TMPDIR` environment variable, or in `/tmp` when the `TMPDIR` environment variable is not set.

7.3 Procedure

1. Go to `src/rwflowpack` subdirectory in the directory tree where you built SiLK.
2. Type `make check-rwflowpack`. This will invoke the tests that check the behavior of **rwflowpack**.

The **rwflowpack** tests check the following behaviors (unless otherwise stated, **rwflowpack** is running in “stream” input mode and “local-storage” output mode):

1. **Use of **rwflowpack** init script.** Confirm that the shell script designed for the `/etc/init.d` directory supports starting, stopping, and checking the status of **rwflowpack**.
2. **Sensor configuration.** Verify that **rwflowpack** correctly parses a sensor configuration file that contains both valid and invalid probe and sensor definitions.
3. **Pack SiLK IPv4 file.** Check whether **rwflowpack** starts, uses its directory poller to find a file (that was present when **rwflowpack** was started), reads the SiLK flow records from the file, creates files and directories in its data directory, moves the incoming file to its archive directory, and exits cleanly when it receives a signal. This test uses an input file that contains only IPv4 data.
4. **Pack SiLK IPv6 file.** This test is similar to the previous, except it uses a data file that contains IPv6 data. This tests is only invoked when SiLK has been compiled with IPv6 support.
5. **Directory polling check.** This test is similar to the previous test, except the file is put into the polling directory after **rwflowpack** has started. This ensures that the directory poller works as expected.
6. **Pack IPFIX IPv4 file.** Check whether **rwflowpack** starts, uses its directory poller to find a file, reads the IPFIX records from the file, creates files and directories in its data directory, moves the incoming file to its archive directory, and exits cleanly when it receives a signal. This test uses an input file that contains only IPv4 data. This test is only invoked when SiLK has been compiled with IPFIX support.

7. **Pack IPFIX IPv6 file.** This test is similar to the previous, except it uses a data file that contains IPv6 data. This test is only invoked when SiLK has been compiled with both IPFIX and IPv6 support.
8. **Pack IPFIX from network (127.0.0.1).** Check whether `rwflowpack` starts, reads IPFIX records on a TCP socket bound to an IPv4 address, creates files and directories in its data directory, and exits cleanly when it receives a signal. This test uses an input file that contains only IPv4 data. This test is only invoked when SiLK has been compiled with IPFIX support.
9. **Pack IPFIX from network (::1).** This test is similar to the previous, except `rwflowpack` binds to an IPv6 address. This test is only invoked when SiLK has been compiled with both IPFIX and IPv6 networking support. This test requires the Perl Socket6 module.
10. **Pack NetFlow v5 file.** Check whether `rwflowpack` starts, uses its directory poller to find a file, reads the NetFlow v5 PDU records from the file, creates files and directories in its data directory, moves the incoming file to its archive directory, and exits cleanly when it receives a signal. This test also verifies that the `--packing-logic` switch works as expected.
11. **Run in “sending” output-mode.** Check whether `rwflowpack` starts, uses its directory poller to find a file, reads the SiLK flow records from the file, creates files in its sending directory, moves the incoming file to its archive directory, and exits cleanly when it receives a signal. This test uses an input file that contains only IPv4 data. This test also verifies that the `--pack-interfaces` switch causes the “in” and “out” fields to appear in the output files.
12. **Run in “sending” output-mode and apply a command.** Check whether `rwflowpack` starts, uses its directory poller to find incoming files, reads the SiLK flow records from the files, creates files in its sending directory, moves the incoming file to its archive directory, invokes a command on the incoming files after moving them to the archive directory, and exits cleanly when it receives a signal. This test uses an input file that contains only IPv4 data.
13. **Run in “fcfiles” input-mode.** Check whether `rwflowpack` starts, finds a file in its incoming directory, reads the probe name and flowcap records from the file, creates files and directories in its data directory, moves the incoming file to its archive directory, and exits cleanly when it receives a signal. This test uses an input file that contains only IPv4 data.
14. **Run in “respool” input-mode.** Check whether `rwflowpack` starts, uses its directory poller to find incoming files, reads the SiLK flow records from the files, creates files and directories in its data directory based on the sensor and class/type data that exists on the flow records, moves the input files to the archive directory, and exits cleanly. This test uses an input file that contains only IPv4 data.
15. **Run in “pdufile” input-mode.** Check whether `rwflowpack` starts, reads the NetFlow v5 PDUs from a file specified on the command line, creates files and directories in its data directory, moves the PDU file to its archive directory, and exits cleanly.
16. **Packing multiple streams.** Check whether `rwflowpack` properly starts, polls two directories (containing SiLK flow files) and listens on two network ports (collecting NetFlow v5 PDUs), and exits cleanly. The test creates data files for three sensors, where the first sensor contains the data from one poll directory and one network port, the second sensor contains the remaining poll directory, and the third sensor contains the remaining network port.
17. **Packing multiple streams.** Check whether `rwflowpack` properly starts, polls two directories containing SiLK flow files and two other directories containing files of NetFlow v5 PDUs, and exits cleanly. The test creates data files for three sensors, where the first sensor contains the data from one SiLK directory and one NetFlow v5 directory, the second sensor contains the remaining SiLK directory, and the third sensor contains the remaining NetFlow v5 directory.

18. **Discarding flows matching CIDR block.** Check whether `rwflowpack` properly starts, uses its directory poller to find a file, reads the SiLK flow records from the file, discards records that have a source or destination IP in a particular CIDR block, creates files and directories in its data directory containing the remaining flows, moves the incoming file to its archive directory, and exits cleanly when it receives a signal. This test uses an input file that contains only IPv4 data.
19. **Discarding flows not matching CIDR block.** This test is similar to the previous, except flow records that do not match the specified CIDR block are discarded.
20. **Categorizing and discarding flows matching an IPv4 IPset.** Check whether `rwflowpack` properly starts, uses its directory poller to find a file, reads the SiLK flow records from the file, discards records that have a source or destination IP in an IPset containing IPv4 addresses, properly categorizes each flow by comparing its source and destination IP to an IPv4 IPset, creates files and directories in its data directory, moves the incoming file to its archive directory, and exits cleanly when it receives a signal. This test uses an input file that contains only IPv4 data.
21. **Categorizing and discarding flows matching an IPv6 IPset.** This test is similar to the previous, except the flow records and the IPset files contain IPv6 addresses.
22. **Bad SiLK input files.** Check whether `rwflowpack` properly handles unusual files in a directory it is polling for SiLK files. One test file is a SiLK data file that contains no records; `rwflowpack` should move this file to the archive directory and not create any hourly data files. Another file is one that does not contain the SiLK file header. `rwflowpack` should move this file into its error directory.
23. **Bad flowcap input files.** Check whether `rwflowpack`, running in “fcfiles” input mode, properly handles unusual files its incoming directory. The first test file is a flowcap file that contains no records; `rwflowpack` should move this file to the archive directory and not create any hourly data files. Another file is one that does not contain the SiLK file header. `rwflowpack` should move this file into its error directory. The final test file is a SiLK data file that does not contain the proper header; `rwflowpack` should move this file into the error directory.
24. **Bad NetFlow input files.** Check whether `rwflowpack` properly handles unusual files in a directory it is polling for NetFlow v5 files. `rwflowpack` should treat all these files as invalid and move them to the error directory. The checks include (1) a file that has the correct header and is the correct size but contains a record count of zero, (2) a file that has the correct header but it too small, (3) a file that claims it is NetFlow v8, and (4) a file containing plain text.
25. **Bad IPFIX input files.** Check whether `rwflowpack` properly handles unusual files in a directory it is polling for IPFIX files. `rwflowpack` should treat all these files as invalid and move them to the error directory. The checks include a file that has the correct header but contains no records, and a file containing plain text. This test is only invoked when SiLK has been compiled with IPFIX support.

7.4 Expected results

The tests may take several minutes to run.

During the tests, you may see the following sorts of output.

- The following indicates a test that successfully passed.

```
PASS: tests/rwflowpack-version.pl
```

- The following indicates a test has failed. For this failed test, information about why the test failed may be available in the file `tests/rwflowpack-pack-silk.pl.log`.

FAIL: tests/rwflowpack-pack-silk.pl

- The following indicates that the test was skipped. For this skipped test, information about why the test was skipped may be available in the file `tests/rwflowpack-pack-silk-ipv6.pl.log`.

SKIP: tests/rwflowpack-pack-silk-ipv6.pl

A test can be skipped for two reasons.

1. The test is not applicable. For example, there is no need to test IPv6 functionality if SiLK was not compiled with IPv6 support.
2. A file or application that the test requires is not present. This can occur if you fail to build the SiLK tools prior to testing, so that `make check` is building the tools and testing them. Some tests use other tools in SiLK suite, and the tests will be skipped if the required tools are not available.

Once all processing stops, you should see output similar to the following to summarize the results of running the tests.

```
=====
Testsuite summary for SiLK 3.6.0
=====
# TOTAL: 25
# PASS:  24
# SKIP:  1
# XFAIL: 0
# FAIL:  0
# XPASS: 0
# ERROR: 0
=====
```

where

TOTAL is the number of tests that were run

PASS is the number of tests that passed

SKIP is the number of tests that were skipped

XFAIL will always be 0

FAIL is the number of tests that failed

XPASS will always be 0

ERROR is the number of tests that had a fatal error

When the sum of PASS and SKIP equals TOTAL, the **make** command exits with a status of 0 to indicate that no test failed.

If either FAIL or ERROR is non-zero, one or more tests failed and the return status of **make** will be non-zero.

Details about why a test was skipped or why a test failed can be found in the **test-suite.log** file in the **src/rwflowpack** directory as well as in the ***.log** files in the **src/rwflowpack/tests** directory.

8 Testing **rwpollexec**

The **rwpollexec** daemon is used to run a user-defined command on files that appear in a directory which **rwpollexec** periodically examines for new files. **rwpollexec** is intended to provide a stand-alone program that operates similarly to the **--post-command** argument available on **rwflowappend**.

The tests for **rwpollexec** are included with the SiLK-3.24.0 source distribution. The tests are invoked by typing **make check** in the **src/rwpollexec** directory. (If you type **make check** at the top of the build tree, the **rwpollexec** tests will be invoked as **make** recursively descends into each directory.)

The tests are written in a combination of Perl and Python. The tests will confirm that the **rwpollexec** daemon can start, notices files, execute subprocesses on those files, send signals to subprocesses, properly dispose of files, and terminate cleanly.

8.1 Prerequisites

The tests of **rwpollexec** require that the following tools are installed on the system:

- Python 2.6 or later
- Perl 5.6 or later
- the Perl module Digest::MD5

8.2 Preparation

The test scripts assume you have configured and built **rwpollexec** and all the libraries it requires. The scripts use the application binary as it exists in the build tree, and the scripts do not require that you install SiLK prior to running the tests.

During many of the tests, a temporary directory is created, and files and subdirectories are created in this directory. The directory is created in the location specified by the TMPDIR environment variable, or in **/tmp** when the TMPDIR environment variable is not set.

8.3 Procedure

1. Go to **src/rwpollexec** subdirectory in the directory tree where you built SiLK.
2. Type **make check**. This will invoke the scripts that check the behavior of **rwpollexec**.

The **rwpollexec** tests check the following behaviors:

1. **Use of `rwpollexec` init script.** Confirm that the shell script designed for the `/etc/init.d` directory supports starting, stopping, and checking the status of `rwpollexec`.
2. **Handle processes that exit successfully.** Check whether `rwpollexec` properly handles the case when it invokes a command that completes successfully (exit status is 0). The command is invoked sequentially on each of the two files that exist in `rwpollexec`'s incoming directory when `rwpollexec` is invoked. `rwpollexec` should move the files to the archive directory once the command is completed. When `rwpollexec` receives a signal, it should shut down cleanly.
3. **Handle processes that exit unsuccessfully.** This test is similar to the previous, except in this test the command does not complete successfully (i.e., exits with a non-zero status). In this case, the files should be put into the error directory. When `rwpollexec` receives a signal, it should shut down cleanly.
4. **Handle processes that exit due to a signal.** This test is similar to the first, except in this test the command is terminated due to a signal. In this case, the files should be put into the error directory. When `rwpollexec` receives a signal, it should shut down cleanly.
5. **Handle “slow” processes.** Check whether `rwpollexec` properly handles subprocesses that do not exit after a period of time, where the subprocesses will exit when they receive a `SIGTERM`. When `rwpollexec` is invoked, there are two files in its incoming directory. `rwpollexec` invokes a command on one file, but the command does not exit. `rwpollexec` sends a `SIGTERM` to the command, at which point the command exits with a status of 0. `rwpollexec` repeats the steps for the second file, and the command exits with a status of 1. The first file should appear in the archive directory, and the second in the error directory. When `rwpollexec` receives a signal, it should shut down cleanly.
6. **Handle “hanging” processes.** This test is similar to the previous, except the subprocesses do not exit when they receive a `SIGTERM`. Once `rwpollexec` sends the `SIGTERM` and the process fails to exit, `rwpollexec` sends a `SIGKILL` to terminate the subprocess. Both input files should be moved to the error directory. When `rwpollexec` receives a signal, it should shut down cleanly.
7. **Handle many types of processes sequentially.** This test is a combination of all of the above tests. `rwpollexec` invokes a command on each of the 12 files that exists in its incoming directory. `rwpollexec` does not invoke the command on the next file until the current command terminates. The command either exits on its own, or `rwpollexec` must send a signal to the process to terminate it. The input files will be moved to the archive or error directory as appropriate. When `rwpollexec` receives a signal, it should shut down cleanly.
8. **No archive directory.** This test is identical to the previous test, except the archive directory is not used. For this test, files whose commands exit successfully should be removed from the file system.
9. **Handle many types of processes simultaneously.** This test is similar to the previous test, except `rwpollexec` is allowed to invoke 4 subprocesses simultaneously. The input files will be moved to the archive or error directory as appropriate. When `rwpollexec` receives a signal, it should shut down cleanly.

8.4 Expected results

The tests may take several minutes to run.

During the tests, you may see the following sorts of output.

- The following indicates a test that successfully passed.

PASS: tests/rwpollexec-version.pl

- The following indicates a test has failed. For this failed test, information about why the test failed may be available in the file tests/rwpollexec-killed.pl.log.

FAIL: tests/rwpollexec-killed.pl

Once all processing stops, you should see output similar to the following to summarize the results of running the tests.

```
=====
Testsuite summary for SiLK 3.6.0
=====
# TOTAL: 11
# PASS: 11
# SKIP: 0
# XFAIL: 0
# FAIL: 0
# XPASS: 0
# ERROR: 0
=====
```

where

TOTAL is the number of tests that were run

PASS is the number of tests that passed

SKIP is the number of tests that were skipped, and should always be 0 for **rwpollexec** tests

XFAIL will always be 0

FAIL is the number of tests that failed

XPASS will always be 0

ERROR is the number of tests that had a fatal error

When PASS equals TOTAL, the **make** command exits with a status of 0 to indicate that no test failed.

If either FAIL or ERROR is non-zero, one or more tests failed and the return status of **make** will be non-zero.

Details about why a test failed can be found in the **test-suite.log** file in the **src/rwpollexec** directory as well as in the ***.log** files in the **src/rwpollexec/tests** directory.

9 Detail of Analysis Tool Testing

This section provides a detailed listing of the tests that will be invoked when you follow the instructions in [Section 2](#).

9.1 Simple help check

The following tests verify the `--help` and `--help-fields` switches work.

```
flowcap --help
```

```
num2dot --help
```

```
rwaddrcount --help
```

```
rwaggbag --help-fields
```

```
rwaggbag --help
```

```
rwaggbag --help-fields
```

```
rwaggbagbuild --help
```

```
rwaggbag --help-fields
```

```
rwaggbagcat --help
```

```
rwaggbag --help-fields
```

```
rwaggbagtool --help
```

```
rwappend --help
```

```
rwbag --help
```

```
rwbagbuild --help
```

```
rwbagcat --help
```

```
rwbagtool --help
```

```
rwcat --help
```

```
rwcompare --help
```

```
rwallformats --help
```

```
rwrttd2split --help
```

rwcount --help

rwcut --help

rwfileinfo --help

rwfglob --help

rwfilter --help

rwflowappend --help

rwflowpack --help

rwguess --help

rwpackchecker --help

rw pdu2silk --help

rwgroup --help

rwidsquery --help

rwipaexport --help

rwipaimport --help

rwipfix2silk --help

rw2yaf2silk --help

rw silk2ipfix --help

rwmatch --help

rwnetmask --help

rwgeoip2ccmap --help

rwip2cc --help

rwmapbuild --help

rwmapcat --help

rwmaplookup --help

rwpollexec --help

rwrandomizeip --help

rwrecgenerator --help

rwresolve --help

rwscan --help

rwscanquery --help

rwset --help

rwsetbuild --help

rwsetcat --help

rwsetmember --help

rwsettool --help

mapsid --help

rwsiteinfo --help

rwcombine --help

rwdedupe --help

rwsort --help

rwsplit --help

rwstats --help

```
rwstats --legacy-help
```

```
rswswapbytes --help
```

```
rwtotal --help
```

```
rwttuc --help
```

```
rwuniq --help
```

```
rwreceiver --help
```

```
rwsender --help
```

9.2 Simple version check

The following tests verify the `--version` switch works.

```
flowcap --version
```

```
num2dot --version
```

```
rwaddrcount --version
```

```
rwaggbag --version
```

```
rwaggbagbuild --version
```

```
rwaggbagcat --version
```

```
rwaggbagtool --version
```

```
rwappend --version
```

```
rwbag --version
```

```
rwbagbuild --version
```

```
rwbagcat --version
```

```
rwbagtool --version
```

rwcat --version

rwcompare --version

rwallformats --version

rwrttd2split --version

rwcount --version

rwcut --version

rwfileinfo --version

rwfglob --version

rwfilter --version

rwflowappend --version

rwflowpack --version

rwguess --version

rwpackchecker --version

rw pdu2silk --version

rwgroup --version

rwidsquery --version

rwipaexport --version

rwipaimport --version

rwipfix2silk --version

rw2yaf2silk --version

rw silk2ipfix --version

rwmatch --version

rwnetmask --version

rwgeoip2ccmap --version

rwip2cc --version

rwpmapbuild --version

rwpmapcat --version

rwpmaplookup --version

rwpollexec --version

rwrandomizeip --version

rwrecgenerator --version

rwresolve --version

rwscan --version

rwscanquery --version

rwset --version

rwsetbuild --version

rwsetcat --version

rwsetmember --version

rwsettool --version

mapsid --version

rwsiteinfo --version

rwcombine --version

`rwdedupe --version`

`rwsort --version`

`rwsplit --version`

`rwstats --version`

`rwswapbytes --version`

`rwtotal --version`

`rwuc --version`

`rwuniq --version`

`rwreceiver --version`

`rwsender --version`

9.3 Command without arguments

The following tests verify the application does not crash when invoked with no switches or arguments. Most of these tests will result in the application exiting with a non-zero exit status.

`flowcap`

`rwaddrcount`

`rwaggbag`

`rwaggbagbuild`

`rwaggbagcat`

`rwaggbagtool`

`rwappend`

`rwbag`

`rwbagbuild`

rwbagcat

rwbagtool

rwcat

rwcompare

rwallformats

rwrttd2split

rwcount

rwcut

rwfileinfo

rwfglob

rwfilter

rwflowappend

rwflowpack

rwguess

rwpackchecker

rw pdu2silk

rwgroup

rwidsquery

rwipaexport

rwipaimport

rwipfix2silk

rwpyaf2silk

rwsilk2ipfix

rwmatch

rwnetmask

rwgeoip2ccmap

rwip2cc

rwpmapbuild

rwpmapcat

rwpmaplookup

rwpollexec

rwrandomizeip

rwrecgenerator

rwscan

rwset

rwsetbuild

rwsetcat

rwsetmember

rwsettool

mapsid

rwsiteinfo

rwcombine

rwdedupe
rwsort
rwsplit
rwstats
rswapbytes
rwtotal
rwtuc
rwuniq
rwreceiver
rwsender

9.4 Command with null input

The following tests verify the application does not crash when invoked with completely empty (null) input. Most of these tests will result in the application exiting with a non-zero exit status.

```
num2dot </dev/null

rwaddrcount --print-recs </dev/null

rwaggbag --key=protocol --counter=records \
  --output-path=/dev/null </dev/null

rwaggbagbuild --fields=protocol,records </dev/null \
| rwaggbagcat

rwaggbagcat /dev/null

rwaggbagtool --output-path=/dev/null </dev/null

cp empty.rwf /tmp/rwappend-null-input-out \
&& rwappend --create /tmp/rwappend-null-input-out /dev/null

rwbag --sport-flows=/dev/null </dev/null
```

```
rwbagbuild </dev/null

rwbagcat --minkey=50 --maxkey=100 </dev/null

rwbagtool --minkey=50 --maxkey=100 </dev/null

rwcat </dev/null

rwcompare data.rwf /dev/null

rwcourt </dev/null

rwcut </dev/null

rwfilter --input-pipe=/dev/null --all=/dev/null

rwgroup --id-fields=3 /dev/null

rwnetmask --sip=prefix-length=24 </dev/null

rwgeoip2ccmap </dev/null

rwip2cc </dev/null

rwpmmapbuild </dev/null

rwpmmapcat </dev/null

rwpmmaplookup </dev/null

rwrandomizeip </dev/null

rwrecgenerator </dev/null

rwresolve </dev/null

rwscan --scan-mode=2 /dev/null

rwset --sip-file=/dev/null </dev/null

rwsetbuild </dev/null >/dev/null
```

```

rwsetcat </dev/null

rwsetmember 10.x.x.x </dev/null

rwsettool </dev/null >/dev/null

rwcombine --ignore-fields=1 </dev/null

rwdedupe --ignore-fields=1 </dev/null

rwsort --fields=1 </dev/null

rwsplit --basename=/tmp/rwsplit-null-input-null_input \
        --flow-limit=100 /dev/null

rwstats --fields=sip --count=10 </dev/null

rswapbytes --big-endian </dev/null

rwtotal --sport </dev/null

rwtuc /dev/null

rwuniq --fields=1 </dev/null

```

9.5 Command with empty SiLK file

The following tests verify the application works correctly when invoked with a SiLK file that contains no data section.

```

rwaddrcount --print-rec empty.rwf

rwaddrcount --print-stat empty.rwf

rwaggbag --key=sport --counter=records empty.rwf \
| rwaggbagcat

rwbag --proto-bytes=stdout empty.rwf \
| rwbagcat --key-format=decimal

rwbag --sport-flow=stdout empty.rwf \
| rwbagcat --key-format=decimal

```

```

rwbagbuild --bag-input=/dev/null --key-type=any-IPv6      \
  --counter-type=sum-bytes                                \
| rwbagcat

rwcourt --bin-size=3600 empty.rwf

rwcourt empty.rwf

rwcourt --fields=3-8 empty.rwf

rwfileinfo --fields=7 --no-title empty.rwf

rwfilter --proto=0- --pass=stdout empty.rwf              \
| rwcat --compression-method=none --byte-order=little   \
  --ipv4-output

rwgroup --id-fields=3 empty.rwf                          \
| rwcat --compression-method=none --byte-order=little   \
  --ipv4-output

rwsilk2ipfix empty.rwf                                   \
| rwipfix2silk -                                          \
| rwcat --compression-method=none --byte-order=little   \
  --ipv4-output

rwmatch --relate=1,2 empty.rwf empty.rwf -              \
| rwcat --compression-method=none --byte-order=little   \
  --ipv4-output

rwnetmask --nhip-prefix=16 empty.rwf                    \
| rwcat --compression-method=none --byte-order=little   \
  --milliseconds --ipv4-output

rwrandomizeip --seed=38901 empty.rwf -                  \
| rwcat --compression-method=none --byte-order=little   \
  --ipv4-output --milliseconds

rwscan --scan-mode=2 empty.rwf

rwsetbuild /dev/null /tmp/rwscan-empty-input-emptyset    \
&& rwscan --trw-sip-set=/tmp/rwscan-empty-input-emptyset empty.rwf

rwset --sip-file=stdout empty.rwf                       \
| rwsetcat

```



```

rwsetbuild /dev/null \
| rwsetcat --net=v4:T,13,17,20/10,14,18

rwsetbuild /dev/null \
| rwsetcat --net=v6:T,13,17,20/10,14,18

rwcombine empty.rwf --output-path=/dev/null \
--print-statistics=stdout

rwcombine empty.rwf \
| rwuniq --fields=1-5 --ipv6-policy=ignore \
--timestamp-format=epoch \
--values=bytes,packets,records,stime,etime \
--sort-output --delimited --no-title

rwdedupe empty.rwf \
| rwuniq --fields=1-5 --ipv6-policy=ignore \
--timestamp-format=epoch \
--values=bytes,packets,records,stime,etime \
--sort-output --delimited --no-title

cat /dev/null \
| rwsort --fields=9,1 --presorted-input --xargs=- \
| rwcat --compression-method=none --byte-order=little \
--ipv4-output

rwsort --field=9,1 --presorted-input empty.rwf \
| rwcat --compression-method=none --byte-order=little \
--ipv4-output

rwsort --field=9,1 empty.rwf \
| rwcat --compression-method=none --byte-order=little \
--ipv4-output

rwsplit --basename=/tmp/rwsplit-empty-input-empty_input \
--flow-limit=100 empty.rwf

cat /dev/null \
| rwstats --fields=dip --count=10 --top --ipv6-policy=ignore \
--presorted-input --xargs=-

rwstats --fields=dip --count=10 --top --ipv6-policy=ignore \
--presorted-input empty.rwf

rwstats --fields=dip --count=10 --top \
--ipv6-policy=ignore empty.rwf

```

```

rswswapbytes --big-endian empty.rwf - \
| rwfileinfo --no-title --field=byte-order,count-records -

rswswapbytes --little-endian empty.rwf - \
| rwfileinfo --no-title --field=byte-order,count-records -

rswswapbytes --little-endian empty.rwf - \
| rswswapbytes --swap-endian - - \
| rwfileinfo --no-title --field=byte-order,count-records -

rwttotal --sport empty.rwf

cat /dev/null \
| rwuniq --fields=sport --presorted-input -xargs=-

rwuniq --fields=sport --presorted-input empty.rwf

rwuniq --fields=sport --sort-output empty.rwf

```

9.6 Checking successful exit status

The following tests perform a variety of checks. In all cases, the application should exit with a zero exit status.

```

rwaggbagbuild --fields=sip4,sum-bytes /dev/null \
| rwaggbagtool --scalar-multiply=sip4=1000 --output-path=/dev/null

mapsid 99999

mapsid 9999

mapsid S9999

rwcombine empty.rwf

rwdedupe empty.rwf

```

9.7 Checking for non-zero exit status

The following tests perform a variety of checks for error conditions. In all cases, the application should exit with a non-zero exit status.

```

rwaddrcount --print-recs

```

```

rwaddrcount empty.rwf

rwaggbag --key=protocol --counter=records >/dev/null

rwaggbag empty.rwf >/dev/null

rwaggbagbuild --fields=protocol,records >/dev/null

rwaggbagbuild >/dev/null

rwaggbagcat --fields=protocol,ignore /dev/null

rwaggbagcat --missing-fields=protocol=0 /dev/null

echo 17,1771 \
| rwaggbagbuild --fields=protocol,records --columns-separator=, \
| rwaggbagcat --fields=protocol,records --missing-field=sport=0

rwaggbag --key=sport --counter=records data.rwf \
| rwaggbagtool \
    --backup-path=/tmp/rwaggbagtool-bad-backup-no-inplace-backup \
    --output-path=/dev/null --add - >/dev/null

rwaggbag --key=sport --counter=records \
    --output-path=/tmp/rwaggbagtool-bad-inplace-devnull-sport_rec \
    data.rwf \
&& rwaggbagtool --modify-inplace --output-path=/dev/null \
    --add /tmp/rwaggbagtool-bad-inplace-devnull-sport_rec \
    >/dev/null

rwaggbagbuild --fields=sip4,sum-bytes /dev/null \
| rwaggbagtool --scalar-multiply=invalid --output-path=/dev/null

rwaggbagbuild --fields=sip4,sum-bytes /dev/null \
| rwaggbagtool --scalar-multiply=0 --output-path=/dev/null

touch /tmp/rwappend-null-output-in \
&& rwappend --create /tmp/rwappend-null-output-in empty.rwf

rwappend stdout empty.rwf >/dev/null

rwbag --sport-flows=/dev/null

rwbag empty.rwf

```

```

echo 443,18446744073709551615 \
| rwbagbuild --bag-input=- --delimiter-, --key-type=sport \
  --counter-type=sum-bytes --output-path=/dev/null

echo 443 \
| rwbagbuild --bag-input=- --delimiter-, \
  --default-count 18446744073709551615 --key-type=sport \
  --counter-type=sum-bytes --output-path=/dev/null

rwbagcat --mincounter=101 --maxcounter=99 /dev/null

rwbagcat --minkey=101 --maxkey=99 /dev/null

rwbagtool \
  --backup-path=/tmp/rwbagtool-bad-backup-no-inplace-backup \
  --output-path=/dev/null \
  --add bag1-v4.bag >/dev/null

rwbagtool --modify-inplace --output-path=/dev/null \
  --add bag1-v4.bag >/dev/null

rwbagtool --mincounter=101 --maxcounter=99 /dev/null

rwbagtool --minkey=101 --maxkey=99 /dev/null

rwbagtool --scalar-multiply=18446744073709551615 \
  --output-path=/dev/null /dev/null

rwcompare data.rwf data.rwf data.rwf

rwfglob --data-rootdir=. --print-missing \
  --start-date=2009/02/12:16 --end-date=2009/02/12:14

rwfilter --fail=/dev/null empty.rwf

rwfilter --pass=/dev/null empty.rwf

rwfilter --print-stats empty.rwf

rwfilter --all=/dev/null

rwfilter --proto=1 empty.rwf

rwidquery --intype=fast

```

```

rwidsquery --intype=rule --dry-run \
    /tmp/rwidsquery-rule-no-date-rule 2>&1

rwipaexport /dev/null

rwipaexport --catalog=my-cat --time=2009/02/14:00:00 /dev/null

rwipaimport /dev/null

rwset --sip=- empty.rwf \
| rwipaimport --catalog=my-cat --description=my-description \
    --start-time=2009/02/12:00:00 \
    --end-time=2009/02/14:23:59:59 -

rwnetmask --sip=prefix-length=24

rwnetmask empty.rwf

rwset --sip-file=/dev/null

rwset empty.rwf

rwset --sip-file=stdout empty.rwf \
| rwsetmember 10.x.x.x

rwsettool --backup-path=/tmp/rwsettool-backup-no-inplace-backup \
    --output-path=/dev/null --union set1-v4.set >/dev/null

rwsettool --modify-inplace --output-path=/dev/null \
    --union set1-v4.set >/dev/null

./rwsettool --sample set1-v4.set >/dev/null

# Uses an exceptionally long path name not included here
rwsiteinfo --delimited --fields=class,type,sensor \
    --sensors=@/AbcdefghijklmnopqrstuvwxyzBCDEF/..... \
    --site-config-file rwsiteinfo-site.conf

rwcombine --ignore-fields=1

rwdedupe --ignore-fields=1

rwsort --fields=1

```

```

rwsort empty.rwf

rwsplit --flow-limit=100 empty.rwf

rwsplit --basename=/tmp/rwsplit-missing-limit-missing_limit empty.rwf

rwsplit --basename=/tmp/rwsplit-multiple-limit-multiple_limit \
  --ip-limit=200 --flow-limit=900 empty.rwf

rwstats --fields=sip --count=10

rwstats empty.rwf

rswswapbytes --big-endian

rswswapbytes empty.rwf /dev/null

rwttotal --sport --dport empty.rwf

rwttotal --sport

rwttotal empty.rwf

rwuniq --fields=1

rwuniq empty.rwf

```

9.8 Perform a checksum of the output—success

The following tests perform a variety of checks. The output of the command is gathered and compared to a known good checksum (MD5). In all cases, the application should exit with a zero exit status.

```

rwcut --fields=1,3,2,4,5 --no-title --ipv6-policy=ignore \
  --ip-format=decimal data.rwf \
| num2dot --ip-fields=1,3

rwcut --fields=1,2 --no-title --ipv6-policy=ignore \
  --ip-format=decimal --no-final-delimiter data.rwf \
| num2dot --ip-fields=2,1

rwcut --fields=1,3,2,4,5 --no-title \
  --ipv6-policy=ignore data.rwf

```

```
rwaddrcount --print-rec --sort-ips --column-separator=/ \
--no-final-delimiter data.rwf

rwaddrcount --print-stat --output-path=/dev/null \
--copy-input=stdout data.rwf \
| rwaddrcount --print-stat

rwaddrcount --print-rec --sort-ips --delimited=, data.rwf

rwaddrcount --use-dest --print-rec --sort-ips data.rwf

rwaddrcount --use-dest --print-stat data.rwf

rwaddrcount --print-rec --sort-ips --ip-format=decimal \
--max-byte=2000 data.rwf

rwaddrcount --use-dest --print-rec --sort-ips \
--max-packet=20 data.rwf

rwaddrcount --print-ips --sort-ips --ip-format=zero-padded \
--max-record=10 data.rwf

rwaddrcount --print-rec --sort-ips --ip-format=decimal \
--min-byte=2000 data.rwf

rwaddrcount --use-dest --print-rec --sort-ips \
--min-packet=20 data.rwf

rwaddrcount --print-ips --sort-ips --ip-format=zero-padded \
--min-record=10 data.rwf

rwaddrcount --print-rec --use-dest --sort-ips data.rwf data.rwf

rwaddrcount --print-rec --sort-ips --no-columns \
--no-title data.rwf

rwaddrcount --print-ips --sort-ips --no-title data.rwf

rwaddrcount --print-rec data.rwf \
| sort

rwaddrcount --set-file=stdout data.rwf \
| rwsetcat
```

```

rwaddrcount --print-stat data.rwf

cat data.rwf \
| rwaddrcount --print-rec --use-dest --sort-ips

rwaggbag --key=sensor,class,type --counter=records data.rwf \
| rwaggbagcat

rwaggbag --key=sport --counter=records \
--output-path=/dev/null --copy-input=stdout data.rwf \
| rwaggbag --key=sport --counter=records \
| rwaggbagcat

rwaggbag --keys=application,dcc --counters=records,sum-bytes \
data-v6.rwf \
| rwaggbagcat

rwaggbag --keys=application,dcc --counters=records,sum-bytes \
--ipv6-policy=ignore data.rwf \
| rwaggbagcat

rwaggbag --keys=scc,proto --counters=sum-bytes,sum-packets \
data-v6.rwf \
| rwaggbagcat

rwaggbag --keys=scc,proto --counters=sum-bytes,sum-packets \
--ipv6-policy=ignore data.rwf \
| rwaggbagcat

rwaggbag --key=sport --counter=records data.rwf \
| rwaggbagcat --delimited

rwaggbag --key=dipv4 --counter=sum-bytes data.rwf \
| rwaggbagcat --ip-format=decimal

rwaggbag --key=dipv4 --counter=sum-packets data.rwf \
| rwaggbagcat --ip-format=zero-padded

rwaggbag --key=dipv6 --counter=sum-packets \
--ipv6-policy=force data-v6.rwf \
| rwaggbagcat

rwaggbag --key=dport --counter=records,sum-packets,sum-bytes \
data.rwf \
| rwaggbagcat

```



```

rwaggbag --key=dport,icmpType,icmpCode,proto \
  --counter=records data.rwf
| rwaggbagcat

rwaggbag --key=dur --counter=sum-bytes data.rwf \
| rwaggbagcat

cat /dev/null \
| rwaggbag --key=sport --counter=records -xargs=- \
| rwaggbagcat

rwaggbag --key=sport --counter=records empty.rwf \
| rwaggbagcat

rwaggbag --key=etime --counter=records data.rwf \
| rwaggbagcat --timestamp-format=epoch

rwaggbag --key=icmpType,icmpCode,dport,proto \
  --counter=records data.rwf \
| rwaggbagcat

rwfilter --proto=1 --pass=- data.rwf \
| rwaggbag --key=icmpType,icmpCode --counter=records \
| rwaggbagcat

rwaggbag --key=sport --counter=records \
  empty.rwf data.rwf empty.rwf \
| rwaggbagcat

rwaggbag --key=sport --counter=records data.rwf \
| rwaggbagcat --no-column --column-sep=,

rwaggbag --key=sport --counter=records data.rwf \
| rwaggbagcat --no-titles

rwfilter --type=in,inweb \
  --pass=/tmp/rwaggbag-ports-protocol-multi-in data.rwf \
&& rwfilter --type=in,inweb --fail=- data.rwf \
| rwaggbag --key=sport,dport,proto --counter=records \
  /tmp/rwaggbag-ports-protocol-multi-in - \
| rwaggbagcat

rwaggbag --key=sport,dport,proto --counter=records \
  --output-path=/tmp/rwaggbag-ports-protocol-v6-tmp \
  data-v6.rwf \
&& rwaggbagcat /tmp/rwaggbag-ports-protocol-v6-tmp

```

```

rwaggbag --key=sport,dport,proto --counter=records data.rwf \
| rwaggbagcat

rwaggbag --key=proto --counter=records data.rwf \
| rwaggbagcat

rwaggbag --key=sipv4 --counter=sum-bytes data.rwf \
| rwaggbagcat

rwaggbag --key=sipv6 --counter=sum-bytes data-v6.rwf \
| rwaggbagcat

cat data.rwf
| rwaggbag --key=sport --counter=records \
| rwaggbagcat

rwaggbag --key=stime --counter=sum-packets,records data.rwf \
| rwaggbagcat

rwaggbag --key=stime,proto --counter=records data.rwf \
| rwaggbagcat

rwuniq --fields=sensor,class,type data.rwf \
| rwaggbagbuild \
| rwaggbagcat

rwaggbag --keys=scc,proto --counters=sum-bytes,sum-packets \
--ipv6-policy=ignore data.rwf \
| rwaggbagcat \
| rwaggbagbuild \
| rwaggbagcat

rwcut --fields=application,dcc,bytes,sport data.rwf \
| rwaggbagbuild --fields=application,dcc,sum-bytes,ignore \
--constant-field=records=1 \
| rwaggbagcat

rwcut --fields=scc,proto,bytes,packets data.rwf \
| rwaggbagbuild --fields=scc,proto,sum-bytes,sum-packets \
| rwaggbagcat

rwcut --fields=dip,bytes data.rwf \
| rwaggbagbuild --fields=dipv4,sum-bytes \
| rwaggbagcat --ip-format=decimal

```

```

rwuniq --fields=dip --value=packets --no-final data.rwf \
| sed 1s/dIP/dIPv4/ \
| sed 1s/Packets/sum-Packets/ \
| rwaggbagbuild \
| rwaggbagcat --ip-format=zero-padded \

rwuniq --fields=etime data.rwf \
| rwaggbagbuild \
| rwaggbagcat --timestamp-format=epoch \

rwaggbagbuild --fields=protocol,records </dev/null \
| rwaggbagcat \

rwuniq --fields=sport,dport,proto data-v6.rwf \
--output-path=/tmp/rwaggbagbuild-ports-protocol-v6-tmp \
&& rwaggbagbuild /tmp/rwaggbagbuild-ports-protocol-v6-tmp \
| rwaggbagcat \

rwcute --fields=sport,dport,proto data.rwf \
| rwaggbagbuild --constant-field=records=1 \
| rwaggbagcat \

rwcute --fields=sip,bytes --delimited=, data.rwf \
| rwaggbagbuild --fields=sip4,sum-bytes --column-separator=, \
| rwaggbagcat \

rwcute --fields=sip,bytes --delimited --no-title data-v6.rwf \
| rwaggbagbuild --fields=sip6,sum-bytes \
--output-path=/tmp/rwaggbagbuild-sip6-bytes-tmp \
--compression-method=best \
&& rwaggbagcat /tmp/rwaggbagbuild-sip6-bytes-tmp \

rwcute --fields=stime,packets,protocol data.rwf \
| rwaggbagbuild --fields=stime,sum-packets,ignore \
--constant-field=records=1 \
| rwaggbagcat \

rwcute --fields=stime,protocol data.rwf \
| rwaggbagbuild --constant=records=1 \
| rwaggbagcat \

rwaggbag --key=protocol --counter=records,sum-bytes data.rwf \
| rwaggbagcat --fields=protocol,records,sum-bytes \

rwaggbag --key=protocol --counter=records,sum-bytes data.rwf \
| rwaggbagcat --fields=sport,dport,protocol,sum-bytes,records \
--missing dport=0 --missing sport=n/a \

```

```

rwaggbag --key=sipv4,protocol --counter=records data.rwf \
| rwaggbagcat --fields=sipv4,protocol,records

rwaggbag --key=sipv6,protocol --counter=records data.rwf \
| rwaggbagcat --fields=sipv6,protocol,records

rwaggbag --key=protocol --counter=records,sum-bytes data.rwf \
| rwaggbagcat --fields=records,protocol

rwaggbag --key=protocol --counter=records,sum-bytes data.rwf \
| rwaggbagcat --fields=sport,protocol,sum-bytes,records

rwaggbag --key=sport --counter=records \
--output-path=/tmp/rwaggbagcat-sport_rec data.rwf \
&& rwaggbag --key=dport --counter=records data.rwf \
| rwaggbagcat --fields=sport,dport,records --missing dport=0 \
--missing sport=0 /tmp/rwaggbagcat-sport_rec -

rwaggbag --key=protocol --counter=records,sum-bytes data.rwf \
| rwaggbagcat

rwfilter --type=in,inweb --pass=- data.rwf \
| rwaggbag --key=sport,dport,proto --counter=records \
--output-path=/tmp/rwaggbagtool-add-bags-in \
&& rwfilter --type=out,outweb --pass=- data.rwf \
| rwaggbag --key=sport,dport,proto --counter=records \
--output-path=/tmp/rwaggbagtool-add-bags-out \
&& rwaggbagtool --add /tmp/rwaggbagtool-add-bags-in \
/tmp/rwaggbagtool-add-bags-out \
| rwaggbagcat

rwaggbag --keys=application,dcc --counters=records,sum-bytes \
--ipv6-policy=ignore data.rwf \
| rwaggbagtool --insert-field=any-cc=uu \
| rwaggbagcat

rwaggbag --keys=scc,proto --counters=sum-bytes,sum-packets \
data.rwf \
| rwaggbagtool --min-field=scc=xx --max-field=scc=xx stdin \
| rwaggbagcat

rwaggbag --keys=scc,proto --counters=sum-bytes,sum-packets \
--ipv6-policy=force \
--output-path=/tmp/rwaggbagtool-country-code-sip-v4v6-tmp \
data.rwf \
&& rwaggbag --keys=scc,proto --counters=sum-bytes,sum-packets \
data-v6.rwf \

```

```

| rwaggbagtool --add - \
  /tmp/rwaggbagtool-country-code-sip-v4v6-tmp \
| rwaggbagcat

echo 10.0.0.0/8 \
| rwsetbuild --record-version=4 \
  - /tmp/rwaggbagtool-dip-complement-10-tmp \
&& rwaggbag --key=sipv4,dipv4 --counter=sum-packets,sum-bytes \
  data.rwf \
| rwaggbagtool \
  --set-complement=dipv4=/tmp/rwaggbagtool-dip-complement-10-tmp \
| rwaggbagcat

rwbagcat --delimited=, bag1-v4.bag \
| sed 's/^/99,/' \
| rwaggbagbuild --fields=records,sipv4,sum-bytes \
  --column-separator=, \
  --output-path=/tmp/rwaggbagtool-divide-zero-max-ab1 \
&& rwbagcat --delimited=, bag2-v4.bag \
| sed 's/^/33,/' \
| rwaggbagbuild --fields=records,sipv4,sum-bytes \
  --column-separator=, \
  --output-path=/tmp/rwaggbagtool-divide-zero-max-ab2 \
&& rwaggbagtool --subtract \
  --output-path=/tmp/rwaggbagtool-divide-zero-max-ab3 \
  /tmp/rwaggbagtool-divide-zero-max-ab1 \
  /tmp/rwaggbagtool-divide-zero-max-ab2 \
; rwaggbagtool --divide --output-path=/dev/null \
  /tmp/rwaggbagtool-divide-zero-max-ab1 \
  /tmp/rwaggbagtool-divide-zero-max-ab3 \
; rwaggbagtool --divide --output-path=/dev/null \
  --zero-divisor-result=error \
  /tmp/rwaggbagtool-divide-zero-max-ab1 \
  /tmp/rwaggbagtool-divide-zero-max-ab3 \
; rwaggbagtool --divide --zero-divisor-result=no-change \
  /tmp/rwaggbagtool-divide-zero-max-ab1 \
  /tmp/rwaggbagtool-divide-zero-max-ab3 \
| rwaggbagcat \
; rwaggbagtool --divide --zero-divisor-result=max \
  /tmp/rwaggbagtool-divide-zero-max-ab1 \
  /tmp/rwaggbagtool-divide-zero-max-ab3 \
| rwaggbagcat \
; rwaggbagtool --divide --zero-divisor-result=54321 \
  /tmp/rwaggbagtool-divide-zero-max-ab1 \
  /tmp/rwaggbagtool-divide-zero-max-ab3 \
| rwaggbagcat \
; rwaggbagtool --divide --zero-divisor-result=remove \
  /tmp/rwaggbagtool-divide-zero-max-ab1 \
  /tmp/rwaggbagtool-divide-zero-max-ab3 \
| rwaggbagcat

```

```

rwbagcat bag1-v4.bag \
| rwaggbagbuild --fields=sipv4,sum-bytes \
--output-path=/tmp/rwaggbagtool-divide-aggbag1 \
&& rwbagcat bag3-v4.bag \
| rwaggbagbuild --fields=sipv4,sum-bytes \
| rwaggbagtool --divide /tmp/rwaggbagtool-divide-aggbag1 - \
| rwaggbagcat \

rwaggbag --key=sport --counter=records \
--output-path=/tmp/rwaggbagtool-inplace-backup-sport_rec \
data.rwf \
&& rwaggbag --key=sport --counter=sum-packets \
--output-path=/tmp/rwaggbagtool-inplace-backup-sport_pkts \
data.rwf \
&& cp /tmp/rwaggbagtool-inplace-backup-sport_pkts \
/tmp/rwaggbagtool-inplace-backup-output \
&& rwaggbagtool --modify-inplace \
--backup-path=/tmp/rwaggbagtool-inplace-backup-backup \
--output-path=/tmp/rwaggbagtool-inplace-backup-output \
--insert-field=records=0 --insert-field=sum-packets=0 \
--add /tmp/rwaggbagtool-inplace-backup-sport_rec \
/tmp/rwaggbagtool-inplace-backup-output \
&& cmp /tmp/rwaggbagtool-inplace-backup-sport_pkts \
/tmp/rwaggbagtool-inplace-backup-backup \
&& rwaggbagcat /tmp/rwaggbagtool-inplace-backup-output \

mkdir /tmp/my-temp \
&& rwaggbag --key=sport,dport --counter=records \
--output-file=/tmp/my-temp/ports_rec data.rwf \
&& rwaggbag --key=sipv4,dipv4 --counter=sum-packets \
--output-file=/tmp/my-temp/ips_pkts data.rwf \
&& cp /tmp/my-temp/ports_rec /tmp/my-temp/save \
&& ./rwaggbagtool --modify-inplace \
--backup-path=/tmp/my-temp/backup \
--output-path=/tmp/my-temp/ports_rec \
--add /tmp/my-temp/ips_pkts /tmp/my-temp/ports_rec \
; cmp /tmp/my-temp/ports_rec /tmp/my-temp/save \
; rm -f /tmp/my-temp/ips_pkts /tmp/my-temp/ports_rec \
; test 0 -eq `ls /tmp/my-temp | wc -l` \

mkdir /tmp/my-temp \
&& rwaggbag --key=sport,dport --counter=records \
--output-file=/tmp/my-temp/ports_rec data.rwf \
&& rwaggbag --key=sport,dport --counter=sum-packets \
--output-file=/tmp/my-temp/ports_pkts data.rwf \
&& cp /tmp/my-temp/ports_rec /tmp/my-temp/save \
&& ./rwaggbagtool --modify-inplace \
--backup-path=/tmp/my-temp/x/y/z \
--output-path=/tmp/my-temp/ports_rec \

```

```

        --insert-field=records=0 --insert-field=sum-packets=0 \
        --add /tmp/my-temp/ports_pkts /tmp/my-temp/ports_rec \
; cmp /tmp/my-temp/ports_rec /tmp/my-temp/save \
; rm -f /tmp/my-temp/ports_pkts /tmp/my-temp/ports_rec \
; test 1 -eq 'ls /tmp/my-temp | wc -l' \
; rwbagcat /tmp/my-temp/*

rwaggbag --key=sport --counter=records \
        --output-path=/tmp/rwaggbagtool-inplace-no-backup-sport_rec \
        data.rwf \
&& rwaggbag --key=sport --counter=sum-packets \
        --output-path=/tmp/rwaggbagtool-inplace-no-backup-sport_pkts \
        data.rwf \
&& rwaggbagtool --modify-inplace \
        --output-path=/tmp/rwaggbagtool-inplace-no-backup-sport_pkts \
        --insert-field=records=0 --insert-field=sum-packets=0 \
        --add /tmp/rwaggbagtool-inplace-no-backup-sport_rec \
        /tmp/rwaggbagtool-inplace-no-backup-sport_pkts \
&& rwaggbagcat /tmp/rwaggbagtool-inplace-no-backup-sport_pkts

rwaggbag --key=sport --counter=records \
        --output-path=/tmp/rwaggbagtool-inplace-noexist-sport_rec \
        data.rwf \
&& rwaggbagtool --modify-inplace \
        --output-path=/tmp/rwaggbagtool-inplace-noexist-output \
        --add /tmp/rwaggbagtool-inplace-noexist-sport_rec \
&& rwaggbagcat /tmp/rwaggbagtool-inplace-noexist-output

rwaggbag --key=sport --counter=records \
        --output-path=/tmp/rwaggbagtool-inplace-stdout-sport_rec \
        data.rwf \
&& rwaggbagtool --modify-inplace \
        --add /tmp/rwaggbagtool-inplace-stdout-sport_rec \
| rwaggbagcat

rwaggbag --key=sport,dport,proto \
        --counter=sum-packets,sum-bytes data.rwf \
| rwaggbagtool --max-field=sport=1024 --max-field=dport=1024 \
| rwaggbagcat

rwaggbag --key=sport,dport,proto \
        --counter=sum-packets,sum-bytes data.rwf \
| rwaggbagtool --min-field=sum-bytes=100000 \
| rwaggbagcat

rwaggbag --key=sport,dport,proto \
        --counter=sum-packets,sum-bytes data.rwf \
| rwaggbagtool --min-field=sport=100 --max-field=sport=99 \
| rwaggbagcat --no-titles

```

```

rwaggbag --key=sport,dport,proto \
--counter=sum-packets,sum-bytes data.rwf \
| rwaggbagtool --min-field=sport=1024 \
| rwaggbagcat

rwaggbag --key=proto --counter=sum-bytes data.rwf \
--output-path=/tmp/rwaggbagtool-multiply-divide-protobytes \
&& rwaggbagtool --scalar-multiply=10 \
/tmp/rwaggbagtool-multiply-divide-protobytes \
| rwaggbagtool --divide - \
/tmp/rwaggbagtool-multiply-divide-protobytes \
| rwaggbagcat

printf 'NOTE: This is my notefile' > /tmp/note ; \
rwaggbag --note-add='NOTE: rwaggbag note' \
--key=sport,dport,proto --counter=records \
--output-path=/tmp/rwaggbag_ports_pro_rec data.rwf ; \
rwaggbagcat /tmp/rwaggbag_ports_pro_rec ; \
cat /tmp/rwaggbag_ports_pro_rec \
| rwfileinfo --fields=annotations - ; \
rwaggbagtool --add /tmp/rwaggbag_ports_pro_rec \
| rwfileinfo --fields=annotations - ; \
rwaggbagtool --note-strip --add /tmp/rwaggbag_ports_pro_rec \
| rwfileinfo --fields=annotations - ; \
rwaggbagtool --note-strip --note-file-add=/tmp/note \
--add /tmp/rwaggbag_ports_pro_rec \
| rwfileinfo --fields=annotations - ; \
echo 655,655,65,65 \
| rwaggbagbuild --note-add='NOTE: rwaggbagbuild note' \
--fields=sport,dport,proto,records --column-separator=, \
| rwaggbagtool --note-add='NOTE: rwaggbagtool note' \
--add - /tmp/rwaggbag_ports_pro_rec \
| rwfileinfo --fields=annotations - ; \
echo 655,655,65,65 \
| rwaggbagbuild --note-add='NOTE: rwaggbagbuild note' \
--fields=sport,dport,proto,records --column-separator=, \
| rwaggbagtool --note-add='NOTE: rwaggbagtool note' \
--to-bag=proto,records \
--add - /tmp/rwaggbag_ports_pro_rec \
| rwfileinfo --fields=annotations - ; \
echo 10.10.10.10,10101010 \
| rwaggbagbuild --note-add='NOTE: rwaggbagbuild note' \
--fields=dIPv4,sum-bytes --column-separator=, \
| rwaggbagtool --note-add='NOTE: rwaggbagtool note' \
--to-ipset=dIPv4 - \
| rwfileinfo --fields=annotations -

rwaggbag --key=sport,dport,proto,input \
--counter=sum-bytes,sum-packets data.rwf \

```



```

| rwaggbagtool --remove=input,sum-packets \
| rwaggbagcat

rwaggbag --key=sipv4,sport,dport,proto \
--counter=sum-bytes,sum-packets data.rwf \
| rwaggbagtool --select=sport,dport,proto,sum-bytes \
| rwaggbagcat

rwbagcat bag1-v4.bag \
| rwaggbagbuild --fields=sipv4,sum-bytes \
| rwaggbagtool --scalar-multiply=2 \
| rwaggbagcat

rwbagcat bag1-v4.bag \
| rwaggbagbuild --fields=sipv4,sum-bytes \
| rwaggbagtool --scalar-multiply=sum-bytes=2 \
| rwaggbagcat

rwaggbag --key=sport,dport,proto \
--counter=sum-bytes,sum-packets,records data.rwf \
| rwaggbagtool --scalar-multiply records=2 \
--scalar-multiply sum-packets=0 --scalar-multiply 5 \
--scalar-multiply records=2 \
| rwaggbagcat

rwbagcat bag1-v4.bag \
| rwaggbagbuild --fields=sipv4,sum-bytes \
| rwaggbagtool --scalar-multiply=3 \
| rwaggbagcat

rwaggbag --key=sport,dport,proto --counter=records data.rwf \
| rwaggbagtool --scalar-multiply 4294967296 \
--scalar-multiply 4294967296 \
| rwaggbagcat

rwaggbag --key=sipv4,dipv4 --counter=sum-packets,sum-bytes \
data.rwf \
--output-path=/tmp/rwaggbagtool-remove-insert-tmp \
&& rwaggbagtool --remove=dipv4,sum-packets \
--insert-field=dipv4=0.0.0.0 \
/tmp/rwaggbagtool-remove-insert-tmp \
| rwaggbagcat

rwaggbag --key=sipv4,dipv4 --counter=sum-packets,sum-bytes \
data.rwf \
| rwaggbagtool --select=sipv4,sum-bytes \
--insert-field=dipv4=0.0.0.0 \
| rwaggbagcat

```

```

rwaggbag --key=sipv4,dipv4 --counter=sum-packets,sum-bytes \
--output-path=/tmp/rwaggbagtool-sip-intersect-10-tmp \
data.rwf \
&& echo 10.0.0.0/8 \
| rwsetbuild --record-version=4 \
| rwaggbagtool --set-intersect=sipv4=- \
/tmp/rwaggbagtool-sip-intersect-10-tmp \
| rwaggbagcat

rwfilter --type=in,inweb --pass=- data.rwf \
| rwaggbag --key=sport,dport,proto --counter=records \
--output-path=/tmp/rwaggbagtool-subtract-bags-in \
&& rwfilter --type=out,outweb --pass=- data.rwf \
| rwaggbag --key=sport,dport,proto --counter=records \
| rwaggbagtool --subtract /tmp/rwaggbagtool-subtract-bags-in - \
| rwaggbagcat

rwaggbag --key=sport,dport,proto \
--counter=sum-packets,sum-bytes data.rwf \
--output-path=/tmp/rwaggbagtool-subtract-self-aggbag-tmp \
&& rwaggbagtool --subtract \
/tmp/rwaggbagtool-subtract-self-aggbag-tmp \
/tmp/rwaggbagtool-subtract-self-aggbag-tmp \
| rwaggbagcat --no-titles

rwaggbag --key=sport,dport,proto \
--counter=sum-packets,sum-bytes data.rwf \
--output-path=/tmp/rwaggbagtool-subtract-self-to-bag-tmp \
&& rwaggbagtool --subtract \
/tmp/rwaggbagtool-subtract-self-to-bag-tmp \
/tmp/rwaggbagtool-subtract-self-to-bag-tmp \
--to-bag=sport,sum-bytes \
| rwbagcat

rwaggbag --key=sipv4,dipv4 \
--counter=sum-packets,sum-bytes,records data.rwf \
--output-path=/tmp/rwaggbagtool-subtract-self-to-ipset-tmp \
&& rwaggbagtool --subtract \
/tmp/rwaggbagtool-subtract-self-to-ipset-tmp \
/tmp/rwaggbagtool-subtract-self-to-ipset-tmp \
--to-ipset=sipv4 \
| rwsetcat --cidr=1

rwaggbag --key=sport,dport --counter=sum-bytes data.rwf \
| rwaggbagtool --to-bag=sport,sum-bytes \
| rwbagcat

rwaggbag --key=sipv6,dipv6 --counter=records data-v6.rwf \
| rwaggbagtool --to-ipset=dipv6 \
| rwsetcat

```

```

rwaggbag --key=sipv4,sport,dport,proto \
--counter=records data.rwf \
| rwaggbagtool --to-ipset=sipv4 \
--output-path=/tmp/rwaggbagtool-to-ipset-sipv4-tmp \
&& rwsetcat /tmp/rwaggbagtool-to-ipset-sipv4-tmp

cp data.rwf /tmp/rwappend-create-exists-out \
&& rwappend --create \
/tmp/rwappend-create-exists-out empty.rwf empty.rwf \
&& rwcat --compression-method=none --byte-order=little \
--ipv4-output /tmp/rwappend-create-exists-out

rwappend --create=data.rwf \
/tmp/rwappend-create-template-out data.rwf \
&& rwcat --compression-method=none --byte-order=little \
--ipv4-output /tmp/rwappend-create-template-out

rwappend --create /tmp/rwappend-create-out empty.rwf data.rwf \
&& rwcat --compression-method=none --byte-order=little \
--ipv4-output /tmp/rwappend-create-out

rwcat --byte-order=little empty.rwf > \
/tmp/rwappend-multiple-file-little-out \
&& rwappend \
/tmp/rwappend-multiple-file-little-out empty.rwf data.rwf empty.rwf \
&& rwcat --compression-method=none --byte-order=little \
--ipv4-output /tmp/rwappend-multiple-file-little-out

rwcat --byte-order=big empty.rwf > \
/tmp/rwappend-one-file-big-out \
&& rwappend /tmp/rwappend-one-file-big-out data.rwf \
&& rwcat --compression-method=none --byte-order=little \
--ipv4-output /tmp/rwappend-one-file-big-out

rwbag --sport-flows=/dev/null --copy-input=stdout data.rwf \
| rwbag --sport-flows= \
| rwbagcat --key-format=decimal

rwbag --bag-file=dip-country,sum-packets,- data-v6.rwf \
| rwbagcat --delimited

rwbag --dip-bytes=stdout data-v6.rwf \
| rwbagcat

rwbag --dip-bytes=stdout data.rwf \
| rwbagcat

```

```

rwbag --dip-flows=stdout data-v6.rwf \
| rwbagcat --key-format=zero-padded

rwbag --dip-flows=stdout data.rwf \
| rwbagcat --key-format=zero-padded

rwbag --dip-packets=stdout data-v6.rwf \
| rwbagcat

rwbag --dip-packets=stdout data.rwf \
| rwbagcat --key-format=decimal

rwbag --pmap-file=ip-map-v6.pmap \
--bag-file=dip-pmap:service-host,bytes,- data-v6.rwf \
| rwbagcat --pmap-file=ip-map-v6.pmap

rwbag --dport-bytes=- data.rwf \
| rwbagcat --key-format=decimal --no-final-delimiter -

rwbag --dport-flow=stdout data.rwf \
| rwbagcat --key-format=decimal --delimited

rwbag --dport-flow=stdout data.rwf \
| rwbagcat --key-format=decimal

rwbag --dport-packets=stdout data.rwf \
| rwbagcat --key-format=decimal --no-columns

rwbag --pmap-file=service-port:proto-port-map.pmap \
--bag-file=dport-pmap:service-port,packets,- data.rwf \
| rwbagcat --pmap-file=service-port:proto-port-map.pmap

rwbag --bag-file=flags,records,- data.rwf \
| rwbagcat

rwbag --sport-flow=stdout empty.rwf data-v6.rwf empty.rwf data.rwf \
| rwbagcat --key-format=decimal

rwbag --sport-flow=stdout empty.rwf data-v6.rwf data-v6.rwf \
| rwbagcat --key-format=decimal

rwbag --sport-flow=stdout data.rwf empty.rwf data.rwf \
| rwbagcat --key-format=decimal

```

```
rwbag --proto-bytes=- data.rwf \
| rwbagcat --key-format=decimal --minkey=1 --maxkey=20 \
  --zero-counts

rwbag --proto-flow=stdout data.rwf \
| rwbagcat --key-format=decimal --minkey=1

rwbag --proto-packets=stdout data.rwf \
| rwbagcat --key-format=decimal --maxkey=17

rwbag --bag-file=sip-country,bytes,- data.rwf \
| rwbagcat

rwbag --bag-file=sensor,sum-packets,- data.rwf \
| rwbagcat --delimited

rwbag --sip-bytes=stdout data-v6.rwf \
| rwbagcat

rwbag --sip-bytes=stdout data.rwf \
| rwbagcat

rwbag --sip-flows=/dev/null --sip-packets=stdout data-v6.rwf \
| rwbagcat

rwbag --sip-flows=/dev/null --sip-packets=stdout data.rwf \
| rwbagcat

rwbag --sip-flows=stdout data-v6.rwf \
| rwbagcat

rwbag --sip-flows=stdout data.rwf \
| rwbagcat

rwbag --sip-packets=stdout --sip-bytes=/dev/null data-v6.rwf \
| rwbagcat

rwbag --sip-packets=stdout --sip-bytes=/dev/null data.rwf \
| rwbagcat

rwbag --sip-packets=stdout data-v6.rwf \
| rwbagcat

rwbag --sip-packets=stdout data.rwf \
| rwbagcat
```

```

rwbag --pmap-file=ip-map.pmap \
    --bag-file=sip-pmap:service-host,flows,- data.rwf \
| rwbagcat --pmap-file=ip-map.pmap

rwbag --sport-bytes=- data.rwf \
| rwbagcat --key-format=decimal --delimited=, -

rwbag --sport-flow=stdout data.rwf \
| rwbagcat --key-format=decimal --column-separator=,

rwbag --sport-packets=stdout data.rwf \
| rwbagcat --key-format=decimal --column-separator=, \
    --no-final-delim

cat data.rwf \
| rwbag --sport-flows=stdout \
| rwbagcat --key-format=decimal

rwbag --bag-file=stime,sum-bytes,stdout data.rwf \
| rwbagcat --key-format=iso-time

rwuniq --fields=sport --flows --no-title \
    --delimited=, data.rwf \
| rwbagbuild --bag-input=stdin --delimiter=, \
| rwbagcat --key-format=decimal

rwuniq --fields=sip --flows --no-title data-v6.rwf \
| rwbagbuild --bag-input=stdin \
| rwbagcat --key-format=decimal

rwuniq --fields=sport --flows --no-title data.rwf \
| rwbagbuild --bag-input=stdin \
| rwbagcat --key-format=decimal

rwbagcat bag1-v4.bag bag1-v4.bag bag1-v4.bag \
| rwbagbuild --bag-input=- --key-type=sip v4 \
    --counter-type=sum-bytes \
| rwbagcat

rwcut --delimited --fields=dip,packets --no-title data-v6.rwf \
| rwbagbuild --bag-input=- --key-type=dip-country \
| rwbagcat --delimited

rwcut --fields=dip,bytes --no-title data-v6.rwf \
| rwbagbuild --bag-input=- --key-type=dip-pmap \
    --pmap-file=ip-map-v6.pmap \
| rwbagcat --pmap-file=ip-map-v6.pmap

```

```

rwcut --fields=protocol,dport,packets \
      --column-sep=, --no-title data.rwf \
| rwbagbuild --pmap-file=service-port:proto-port-map.pmap \
      --delimiter=, --bag-input=- --key-type=dport-pmap \
| rwbagcat --pmap-file=service-port:proto-port-map.pmap

rwcut --integer-tcp-flags --fields=flags \
      --delimited --no-title data.rwf \
| rwbagbuild --bag-input=- --key-type=flags \
| rwbagcat

rwset --sip-file=stdout data.rwf \
| rwbagbuild --set-input=stdin --output-path=stdout \
| rwbagcat

echo 65535,100 \
| rwbagbuild --bag-input=stdin --delimiter=, --key-type=sport \
      --counter-type=sum-bytes \
| rwbagcat

echo 65536,100 \
| rwbagbuild --bag-input=stdin --delimiter=, --key-type=dport \
      --counter-type=sum-bytes \
| rwbagcat

echo 255,100 \
| rwbagbuild --bag-input=stdin --delimiter=, \
      --key-type=protocol --counter-type=sum-bytes \
| rwbagcat

echo 256,100 \
| rwbagbuild --bag-input=stdin --delimiter=, \
      --key-type=protocol --counter-type=sum-bytes \
| rwbagcat

rwcut --no-columns --fields=sip,bytes --no-title data.rwf \
| rwbagbuild --bag-input=- --key-type=sip-country \
| rwbagcat

rwcut --integer-sensor --fields=sensor,packets \
      --no-title data.rwf \
| rwbagbuild --bag-input=stdin --key-type=sensor \
| rwbagcat --delimited

rwset --sip-file=stdout data.rwf \
| rwbagbuild --set-input=stdin --default-count=200 \
| rwbagcat

```

```

rwsset --dip-file=stdout data-v6.rwf \
| rwbagbuild --set-input=- --key-type=dip-country \
| rwbagcat

rwsset --sip-file=- data.rwf \
| rwbagbuild --pmap-file=ip-map.pmap --set-input=stdin \
--key-type=sip-pmap \
| rwbagcat --pmap-file=ip-map.pmap

rwsset --sip-file=stdout data-v6.rwf \
| rwbagbuild --set-input=stdin \
| rwbagcat

rwsset --sip-file=stdout data.rwf \
| rwbagbuild --set-input=stdin \
| rwbagcat

rwcute --no-final-delimiter --fields=sip --no-title data.rwf \
| rwbagbuild --pmap-file=ip-map.pmap --bag-input=- \
--key-type=sip-pmap \
| rwbagcat --pmap-file=ip-map.pmap

rwcute --timestamp-format=epoch,no-msec \
--fields=stime,bytes --no-title data.rwf \
| rwbagbuild --bag-input=- --key-type=stime \
| rwbagcat --key-format=iso-time

rwbag --sip-flows=stdout data-v6.rwf \
| rwbagcat --key-format=decimal --bin-ips=binary

rwbag --sip-flows=stdout data.rwf \
| rwbagcat --key-format=decimal --bin-ips=binary

rwbag --sip-flows=stdout data-v6.rwf \
| rwbagcat --key-format=decimal --bin-ips=decimal

rwbag --sip-flows=stdout data.rwf \
| rwbagcat --key-format=decimal --bin-ips=decimal

rwbag --sip-flows=stdout data-v6.rwf \
| rwbagcat --key-format=decimal --bin-ips

rwbag --sip-flows=stdout data.rwf \
| rwbagcat --key-format=decimal --bin-ips

rwbag --sip-flows=stdout data.rwf \
| rwbagcat --network-structure=12TS,12

```



```

rwbagcat --network-structure=14TS,14 bag2-v4.bag

rwbag --sip-flows=stdout data-v6.rwf \
| rwbagcat --network-structure=v6:48,T/48,64,123,112

rwbag --sip-flows=stdout data-v6.rwf \
| rwbagcat --network-structure=v6:T60S

rwbag --sip-flows=stdout data.rwf \
| rwbagcat --network-structure=ATS

rwbagtool --add bag1-v4.bag bag1-v6.bag \
| rwbagcat --network=v4:TH14/

rwbagcat --network-structure=v4:T/8,13,14,15,16 bag1-v4.bag

rwbagcat --network-structure=v6:T/48,61,62,63,64 bag1-v6.bag

rwbagcat --network-structure=v6:61,63T/60,61,63,64,62,41 \
bag2-v6.bag

rwbagcat --network-structure bag2-v4.bag

rwbagcat --network-structure=v6: bag2-v6.bag

rwbagcat --network-structure=v4: bag3-v6.bag

rwbag --sip-flows=stdout data-v6.rwf \
| rwbagcat --network-structure=v6:

rwbag --sip-flows=stdout data.rwf \
| rwbagcat --network-structure

rwbag --bag-file=proto,packet,stdout data.rwf \
| rwbagcat --sort-counter=decreasing

cat data.rwf | rwbag --bag-file=proto,packet,- \
| rwbagcat --sort-counter=increasing

rwbag --bag-file=sipv4,byte,stdout data.rwf \
| rwbagcat --key-format=zero-padded --sort-counter

rwbag --sport-bytes=stdout data.rwf \
| rwbagcat --key-format=decimal --mincounter=2000

```

```
rwbag --sport-flows=stdout data.rwf \
| rwbagcat --key-format=decimal --mincounter=10

rwbag --sport-packets=stdout data.rwf \
| rwbagcat --key-format=decimal --mincounter=20

rwbag --sport-bytes=stdout data.rwf \
| rwbagcat --key-format=decimal --maxcounter=2000

rwbag --sport-flows=stdout data.rwf \
| rwbagcat --key-format=decimal --maxcounter=10

rwbag --sport-packets=stdout data.rwf \
| rwbagcat --key-format=decimal --maxcounter=20

rwbagtool --add bag1-v4.bag bag2-v4.bag \
| rwbagcat

rwbagtool --add bag1-v6.bag bag2-v6.bag \
| rwbagcat

rwbagtool --add bag2-v4.bag bag1-v4.bag \
| rwbagcat

rwbagtool --add bag2-v6.bag bag1-v6.bag \
| rwbagcat

rwbagtool --add bag1-v4.bag bag2-v4.bag \
| rwbagtool --subtract - bag1-v4.bag bag2-v4.bag \
| rwbagcat

rwbagtool --add bag1-v6.bag bag2-v6.bag \
| rwbagtool --subtract - bag1-v6.bag bag2-v6.bag \
| rwbagcat

rwbag --sport-flows=stdout data.rwf \
| rwbagtool --add stdin \
| rwbagcat --key-format=decimal

rwbagtool --compare=eq bag1-v4.bag bag3-v4.bag \
| rwbagcat

rwbagtool --compare=eq bag1-v6.bag bag3-v6.bag \
| rwbagcat
```

```
rwbagtool --compare=ge bag1-v4.bag bag3-v4.bag \
| rwbagcat

rwbagtool --compare=ge bag1-v6.bag bag3-v6.bag \
| rwbagcat

rwbagtool --compare=ge bag2-v4.bag bag1-v4.bag \
| rwbagcat

rwbagtool --compare=ge bag2-v6.bag bag1-v6.bag \
| rwbagcat

rwbagtool --compare=le bag1-v4.bag bag2-v4.bag \
| rwbagcat

rwbagtool --compare=le bag1-v6.bag bag2-v6.bag \
| rwbagcat

echo 10.4.0.0/14 \
| rwsetbuild \
| rwbagtool --complement-intersect=- bag2-v4.bag \
| rwbagcat

echo 2001:db8:a:4::/62 \
| rwsetbuild \
| rwbagtool --complement-intersect=- bag2-v6.bag \
| rwbagcat

rwbag --sip-flows=stdout data-v6.rwf \
| rwbagtool --coverset --ipset-record-version=4 \
| rwsetcat

rwbag --sip-flows=stdout data.rwf \
| rwbagtool --coverset --ipset-record-version=4 \
| rwsetcat

rwbag --sip-flows=stdout data-v6.rwf \
| rwbagtool --coverset \
| rwsetcat

rwbag --sip-flows=stdout data.rwf \
| rwbagtool --coverset \
| rwsetcat

rwbagtool --divide bag1-v4.bag bag3-v4.bag \
| rwbagcat
```

```

rwbagtool --divide bag1-v6.bag bag3-v6.bag \
| rwbagcat

cp bag2-v4.bag /tmp/rwbagtool-inplace-backup-output \
&& rwbagtool --modify-inplace \
    --backup-path=/tmp/rwbagtool-inplace-backup-backup \
    --output-path=/tmp/rwbagtool-inplace-backup-output \
    --add bag1-v4.bag /tmp/rwbagtool-inplace-backup-output \
&& cmp bag2-v4.bag /tmp/rwbagtool-inplace-backup-backup \
&& rwbagcat /tmp/rwbagtool-inplace-backup-output

mkdir /tmp/my-temp \
&& cp bag2-v4.bag /tmp/my-temp/output \
&& rwbagtool --modify-inplace --backup-path=/tmp/my-temp/backup \
    --output-path=/tmp/my-temp/output --add \
    bag1-v4.bag /tmp/my-temp/output /tmp/my-temp/nosuch \
; cmp bag2-v4.bag /tmp/my-temp/output \
; rm -f /tmp/my-temp/output \
test 0 -eq 'ls /tmp/my-temp | wc -l'

mkdir /tmp/my-temp \
&& cp bag2-v4.bag /tmp/my-temp/output \
&& rwbagtool --modify-inplace --backup-path=/tmp/my-temp/x/y/z \
    --output-path=/tmp/my-temp/output \
    --add bag1-v4.bag /tmp/my-temp/output \
; cmp bag2-v4.bag /tmp/my-temp/output \
; rm -f /tmp/my-temp/output \
; test 1 -eq 'ls /tmp/my-temp | wc -l' \
; rwbagcat /tmp/my-temp/*

cp bag2-v4.bag /tmp/rwbagtool-inplace-no-backup-output \
&& rwbagtool --modify-inplace \
    --output-path=/tmp/rwbagtool-inplace-no-backup-output \
    --add bag1-v4.bag /tmp/rwbagtool-inplace-no-backup-output \
&& rwbagcat /tmp/rwbagtool-inplace-no-backup-output

rwbagtool --modify-inplace \
    --output-path=/tmp/rwbagtool-inplace-noexist-output \
    --add bag1-v4.bag bag2-v4.bag \
&& rwbagcat /tmp/rwbagtool-inplace-noexist-output

rwbagtool --modify-inplace --add bag1-v4.bag bag2-v4.bag \
| rwbagcat

echo 10.4.0.0/14 \
| rwsetbuild \
| rwbagtool --intersect=- bag2-v4.bag \
| rwbagcat

```

```

echo 2001:db8:a:4::/62 \
| rwssetbuild \
| rwbagtool --intersect=- bag2-v6.bag \
| rwbagcat

rwbag --sip-flows=stdout data-v6.rwf \
| rwbagtool --invert \
| rwbagcat --key-format=decimal

rwbag --sip-flows=stdout data.rwf \
| rwbagtool --invert \
| rwbagcat --key-format=decimal

rwbag --sport-flows=stdout data.rwf \
| rwbagtool --maxcounter=10 \
| rwbagcat --key-format=decimal

rwbagtool --maximize bag3-v4.bag bag1-v4.bag \
| rwbagcat

rwbagtool --maximize bag3-v6.bag bag1-v6.bag \
| rwbagcat

rwbag --sport-flows=stdout data.rwf \
| rwbagtool --maxkey=1024 \
| rwbagcat --key-format=decimal

rwbag --sport-flows=stdout data.rwf \
| rwbagtool --mincounter=10 \
| rwbagcat --key-format=decimal

rwbagtool --minimize bag1-v4.bag bag3-v4.bag \
| rwbagcat

rwbagtool --minimize bag1-v6.bag bag3-v6.bag \
| rwbagcat

rwbag --sport-flows=stdout data.rwf \
| rwbagtool --minkey=1024 \
| rwbagcat --key-format=decimal

printf 'NOTE: This is my notefile' > /tmp/note ; \
rwbag --note-add='NOTE: rwbag note' \
--proto-bytes=/tmp/rwbag_pro_byt data.rwf ; \
rwbagcat /tmp/rwbag_pro_byt ; \
cat /tmp/rwbag_pro_byt \

```

```

| rwfileinfo --fields=annotations - ; \
rwbagtool --add /tmp/rwbag_pro_byt \
| rwfileinfo --fields=annotations - ; \
rwbagtool --note-strip --add /tmp/rwbag_pro_byt \
| rwfileinfo --fields=annotations - ; \
rwbagtool --note-strip --note-file-add=/tmp/note \
--add /tmp/rwbag_pro_byt \
| rwfileinfo --fields=annotations - ; \
echo 443,344 \
| rwbagbuild --note-add='NOTE: rwbagbuild note' \
--bag-input=- --delimiter=, \
--key-type=sport --counter-type=packets \
| rwbagtool --note-add='NOTE: rwbagtool note' \
--add - /tmp/rwbag_pro_byt \
| rwfileinfo --fields=annotations - ; \
echo 10.10.10.10,10101010 \
| rwbagbuild --note-add='NOTE: rwbagbuild note' \
--bag-input=- --delimiter=, \
--key-type=dIPv4 --counter-type=bytes \
| rwbagtool --note-add='NOTE: rwbagtool note' --coverset - \
| rwfileinfo --fields=annotations - \

rwbag --sport-flows=stdout data.rwf \
| rwbagtool --add --output-path=stdout \
| rwbagcat --key-format=decimal \

rwbagtool --scalar-multiply=2 bag1-v4.bag \
| rwbagcat \

rwbagtool --scalar-multiply=2 bag1-v6.bag \
| rwbagcat \

echo 443,3689348814741910323 \
| rwbagbuild --bag-input=- --delimiter=, --key-type=sport \
--counter-type=sum-bytes \
| rwbagtool --scalar-multiply=5 \
| rwbagcat \

echo 443,3689348814741910323 \
| rwbagbuild --bag-input=- --delimiter=, --key-type=sport \
--counter-type=sum-bytes \
| rwbagtool --scalar-multiply=6 \
| rwbagcat \

rwbagtool --subtract bag1-v4.bag bag2-v4.bag \
| rwbagcat \

rwbagtool --subtract bag1-v6.bag bag2-v6.bag \
| rwbagcat \

```

```

rwbagtool --subtract bag2-v4.bag bag1-v4.bag \
| rwbagcat

rwbagtool --subtract bag2-v6.bag bag1-v6.bag \
| rwbagcat

rwcatt --byte-order=big data-v6.rwf \
| rwcatt --fields=1-15,20,21,26-29 --timestamp-format=epoch \
--delimited

rwcatt --byte-order=big data.rwf \
| rwcatt --fields=1-15,20,21,26-29 --ipv6-policy=ignore \
--timestamp-format=epoch --ip-format=decimal \
--delimited

rwcatt --byte-order=little data-v6.rwf \
| rwcatt --fields=1-15,20,21,26-29 --timestamp-format=epoch \
--delimited

rwcatt --byte-order=little data.rwf \
| rwcatt --fields=1-15,20,21,26-29 --ipv6-policy=ignore \
--timestamp-format=epoch --ip-format=decimal \
--delimited

rwcatt --milliseconds data-v6.rwf \
| rwcatt --fields=1-15,20,21,26-29 --timestamp-format=epoch \
--delimited

rwcatt --milliseconds data.rwf \
| rwcatt --fields=1-15,20,21,26-29 --ipv6-policy=ignore \
--timestamp-format=epoch --ip-format=decimal \
--delimited

rwcatt empty.rwf data.rwf empty.rwf \
| rwcatt --fields=1-15,20,21,26-29 --ipv6-policy=ignore \
--timestamp-format=epoch --ip-format=decimal \
--delimited

cat data.rwf \
| rwcatt --fields=1-15,20,21,26-29 --ipv6-policy=ignore \
--timestamp-format=epoch --ip-format=decimal \
--delimited

rwcatt --note-add='my command line note' empty.rwf \
| rwcatt --fields=7,14 -

```

```

echo 'my stdin note' \
| rwcat --note-file-add= empty.rwf \
| rwfileinfo --fields=7,14 -

rwcat data-v6.rwf \
| rwcut --fields=1-15,20,21,26-29 --timestamp-format=epoch \
--delimited

rwcat data.rwf \
| rwcut --fields=1-15,20,21,26-29 --ipv6-policy=ignore \
--timestamp-format=epoch --ip-format=decimal \
--delimited

cat data.rwf \
| rwcat \
| rwcut --fields=1-15,20,21,26-29 --ipv6-policy=ignore \
--timestamp-format=epoch --ip-format=decimal \
--delimited

ls -l empty.rwf data.rwf empty.rwf \
| rwcat --xargs=stdin \
| rwcut --fields=1-15,20,21,26-29 --ipv6-policy=ignore \
--timestamp-format=epoch --ip-format=decimal \
--delimited

ls -l empty.rwf data.rwf empty.rwf \
| rwcat --xargs \
| rwcut --fields=1-15,20,21,26-29 --ipv6-policy=ignore \
--timestamp-format=epoch --ip-format=decimal \
--delimited

rwcat --byte-order=big data.rwf \
| rwcompare data.rwf -

rwcat --byte-order=big \
--output-path=/tmp/rwcompare-big-big data.rwf \
&& rwcompare data.rwf /tmp/rwcompare-big-big

rwcat --byte-order=little data.rwf \
| rwcompare - data.rwf

rwfilter --stime=2009/02/13:20:00-2009/02/13:20 --sensor=S2 \
--proto=6 --aport=80,8080,443 --pass=stdout data-v6.rwf \
| rwallformats --no-invocation --basename=/tmp/sk-teststmp \
&& md5 /tmp/sk-teststmp*

```



```

rwfilter --stime=2009/02/13:20:00-2009/02/13:20 --sensor=S2 \
        --proto=6 --aport=80,8080,443 --pass=stdout data.rwf \
| rwallformats --no-invocation --basename=/tmp/sk-teststmp \
&& md5 /tmp/sk-teststmp*

rwcount --bin-size=1 --load-scheme=1 data.rwf

rwcount --bin-size=1800 --load-scheme=middle-spike data.rwf

rwcount --bin-size=1800 \
        --load-scheme=time-proportional data.rwf

rwcount --bin-size=1800 --load-scheme=maximum-volume data.rwf

rwcount --bin-size=1800 --load-scheme=minimum-volume data.rwf

rwcount --bin-size=30 --load-scheme=2 data.rwf

rwcount --bin-size=3600 --load-scheme=end-spike \
        --bin-slots data.rwf

rwcount --bin-size=3600 --no-title data.rwf

rwcount --bin-size=86400 --load-scheme=start-spike \
        --timestamp-format=epoch data.rwf

rwcount --bin-size=900 --load-scheme=3 data.rwf

rwcount --bin-size=3600 --load-scheme=1 --column-separator=/ \
        --no-final-delimiter data.rwf

rwcount --bin-size=3600 --load-scheme=1 \
        --output-path=/dev/null --copy-input=stdout data.rwf \
| rwcount --bin-size=86400 --load-scheme=1 \
        --timestamp-format=epoch

rwcount --bin-size=3600 --load-scheme=1 --delimited=, data.rwf

rwcount --bin-size=3600 --load-scheme=0 \
        --end-time=2009/02/14T19:30:00 data.rwf

rwcount --bin-size=3600 --load-scheme=1 \
        --timestamp-format=default data.rwf

```

```

rwcoun --bin-size=3600 --load-scheme=1 \
--timestamp-format=m/d/y data.rwf

rwcoun --bin-size=0.500 --skip-zero --load-scheme=1 \
--start-time=2009/02/14T20:00:00 data.rwf

rwcoun --bin-size=0.1 --load-scheme=2 data.rwf

rwcoun --bin-size=3600 \
--load-scheme=1 empty.rwf data.rwf data-v6.rwf empty.rwf

rwcoun --bin-size=3600 \
--load-scheme=1 data-v6.rwf empty.rwf data-v6.rwf empty.rwf

rwcoun --bin-size=3600 \
--load-scheme=1 empty.rwf data.rwf empty.rwf data.rwf

rwcoun --bin-size=3600 --load-scheme=1 --no-columns \
--no-title data.rwf

rwcoun data.rwf

rwsort --fields=stime --reverse data.rwf \
| rwcoun --load-scheme=1

rwcoun --bin-size=3600 --load-scheme=0 \
--start-epoch=2009/02/12T20:00:00 \
--end-epoch=2009/02/13T20:00:00 data.rwf

rwcoun --bin-size=3600 --load-scheme=0 --skip-zero \
--start-time=2009/02/11T20:30:00 data.rwf

rwcoun --bin-size=604800 --load-scheme=0 \
--start-time=2009/02/10:00:00:00 data.rwf

rwcoun --bin-size=3600 --load-scheme=bin-uniform \
--start-time=2009/02/12T20:30:00 data.rwf

cat data.rwf \
| rwcoun --bin-size=3600 --load-scheme=1

rwcun --fields=1-5 --ipv6-policy=force data.rwf

rwcun --fields=1-5 --ipv6-policy=ignore data.rwf

```

```
rwcut --fields=1-5 data-v6.rwf

rwcut --fields=stype,sip,dtype,dip,dtype --delimited \
    --num-recs=10000 data.rwf

rwcut --all-fields --delimited data-v6.rwf

rwcut --all-fields --delimited data.rwf

rwcut --fields=7,6 --column-separator=/ data.rwf

rwcut --fields=5,4,3 --column-separator=, --no-columns data.rwf

rwcut --fields=5 --output-path=/dev/null \
    --copy-input=stdout data.rwf \
| rwcut --fields=5

rwcut --fields=sip,scc,dip,dcc data-v6.rwf

rwcut --fields=sip,scc,dip,dcc --ipv6=ignore data.rwf

rwcut --delimited data.rwf

rwcut --fields=2 --delimited --ip-format=zero-padded data.rwf

rwcut --dry-run --ipv6-policy=ignore data.rwf

rwcut --fields=8,initialFlags,sessionFlags data.rwf

rwcut --plugin=flowrate.so \
    --fields=bytes,packets,dur,pkts/sec,bytes/sec,bytes/packet,payload-bytes,payload-rate data.rwf

rwfilter --proto=58 --pass=- data-v6.rwf \
| rwcut --fields=4,5 --icmp-type-and-code

rwfilter --proto=1 --pass=- data.rwf \
| rwcut --fields=4,5 --icmp-type-and-code

rwfilter --proto=58 --pass=- data-v6.rwf \
| rwcut --fields=icmpTypeCode

rwfilter --proto=1 --pass=- data.rwf \
| rwcut --fields=icmpTypeCode
```

```

/usr/bin/env INCOMING_FLOWTYPES=all/in,all/inweb \
    OUTGOING_FLOWTYPES=all/out,all/outweb \
rwcut --plugin=int-ext-fields.so --delimited \
    --fields=ext-ip,ext-port,int-ip,int-port,proto,type \
    data.rwf

rwcut --plugin=int-ext-fields.so --delimited \
    --incoming-flowtypes=all/in,all/inweb \
    --outgoing-flowtypes=all/out,all/outweb \
    --fields=ext-ip,ext-port,int-ip,int-port,proto,type \
    data-v6.rwf

rwcut --plugin=int-ext-fields.so --delimited \
    --incoming-flowtypes=all/in,all/inweb \
    --outgoing-flowtypes=all/out,all/outweb \
    --fields=ext-ip,ext-port,int-ip,int-port,proto,type \
    data.rwf

rwcut --fields=9,11 --timestamp-format=default data.rwf

rwcut --fields=9,11 --timestamp-format=m/d/y,no-msec data.rwf

rwcut --fields=attributes,application data.rwf

rwcut --fields=5 --delimited data-v6.rwf data.rwf

rwcut --fields=5 --delimited data.rwf data.rwf

rwcut --fields=5,4,3 --no-columns data.rwf

rwcut --fields=5,4,3 --no-final-delimiter data.rwf

rwcut --fields=5,4,3 --no-title < data.rwf

rwcut --pmap-file=servhost:ip-map-v6.pmap \
    --fields=dst-servhost data-v6.rwf

rwcut --pmap-file=servhost:ip-map.pmap \
    --fields=dst-servhost data.rwf

rwcut --pmap-file=service-port:proto-port-map.pmap \
    --pmap-file=ip-map-v6.pmap \
    --fields=src-service-host,src-service-port,src-service-host,src-service-port data-v6.rwf

```

```

rwcut --pmap-file=service-port:proto-port-map.pmap \
      --pmap-file=ip-map.pmap \
      --fields=src-service-host,src-service-port,src-service-host,src-service-port data.rwf

rwcut --pmap-file=proto-port-map.pmap \
      --fields=sval,dval data.rwf

rwcut --pmap-file=ip-map-v6.pmap \
      --fields=src-service-host data-v6.rwf

rwcut --pmap-file=ip-map.pmap \
      --fields=src-service-host data.rwf

rwcut --python-file=pysilk-plugin.py \
      --fields=scc,py-scc,dcc,py-dcc \
      --num-recs=10000 data.rwf

rwcut --python-file=pysilk-plugin.py --fields=3-5,lower_port \
      --num-recs=10000 data.rwf

rwcut --python-file=pysilk-plugin.py \
      --fields=lower_port,lower_port data.rwf

rwcut --python-file=pysilk-plugin.py \
      --fields=sip,dip,sport,dport,server_ipv6 \
      --num-recs=10000 data-v6.rwf

rwcut --python-file=pysilk-plugin.py \
      --fields=sip,dip,server_ip,sport,dport,lower_port_simple,protocol,proto_name \
      --num-recs=10000 --delimited=, data.rwf

rwcut --fields=3-5 --num-recs=3000 data.rwf

rwcut --fields=9,10 --timestamp-format=epoch --num-recs=3000 \
      --start-rec-num=2000 data.rwf

rwcut --fields=12 --integer-sensor --num-recs=3000 \
      --end-rec-num=2000 data.rwf

rwcut --fields=sip,dip --delimited=, --num-recs=3000 \
      --end-rec-num=20000 data.rwf

rwcut --fields=sport,dport --start-rec-num=30000 \
      --end-rec-num=40000 data.rwf

```

```

rwcut --fields=in,out,nhip --delimited=, \
    --tail-recs=2000 data.rwf

rwcut --fields=class,type,sensor --tail-recs=2000 \
    --num-recs=1000 data.rwf

rwcut --fields=dip,dport,sip,sport --delimited \
    --tail-recs=1000 --num-recs=2000 data.rwf

rwcut --fields=1 --delimited --ip-format=decimal data.rwf

rwcut --fields=sensor,class,type data.rwf

rwcut --plugin=skplugin-test.so --ipv6-policy=ignore \
    --no-columns \
    --fields=bytes,copy-bytes,text-bytes,quant-bytes,sip,copy-sip, copy-sip data.rwf

cat data.rwf \
| rwcut --fields=3-8

rwcut --fields=9 --timestamp-format=epoch \
    --no-final-delimiter data.rwf

rwcut --fields=9-11 data.rwf

rwfileinfo --fields=1,5-6 --no-title data.rwf

rwfileinfo --fields=count-records data.rwf

cat data.rwf \
| rwfileinfo --fields=count-records -

rwfileinfo --fields=command-lines,version data.rwf

rwfglob --data-rootdir=. --print-missing \
    --start-date=2009/02/12:12 --end-date=2009/02/12:14 \
    --flowtypes=@/tmp/flowtype.txt 2>&1

rwfglob --data-rootdir=. --print-missing \
    --start-date=2009/02/12:12 --end-date=2009/02/12:14 \
    --sensors=@/tmp/sensor.txt 2>&1

rwfglob --data-rootdir=. --print-missing \
    --start-date=2009/02/12:12 --end-date=2009/02/12:14 \
    --type=@/tmp/type.txt --sensor=@/tmp/sensor.txt 2>&1

```

```

rwfglob --data-rootdir=. --print-missing \
--start-date=2009/02/12:12 --end-date=2009/02/12:14 \
--type=@/tmp/type.txt 2>&1

rwfglob --data-rootdir=. --print-missing \
--start-date=2009/02/12:12 --end-date=2009/02/12:14 \
--class=all 2>&1

rwfglob --data-rootdir=. --print-missing \
--start-date=2009/02/12:12 --end-date=2009/02/12:14 \
--flowtypes=all/in,all/outweb 2>&1

rwfglob --data-rootdir=. --print-missing \
--start-date=2009/02/12:12 --end-date=2009/02/12:14 \
--sensors=4,6-8,10 2>&1

rwfglob --data-rootdir=. --print-missing \
--start-date=2009/02/12:12 --end-date=2009/02/12:14 \
--sensors=S4,S6,S7,S8,S10 2>&1

rwfglob --data-rootdir=. --print-missing \
--start-date=2009/02/13 --no-summary 2>&1

rwfglob --data-rootdir=. --print-missing \
--start-date=2009/02/12:12 \
--end-date=2009/02/12:14 2>&1

rwfglob --data-rootdir=. --print-missing \
--start-date=2009/02/12:12 2>&1

rwfglob --data-rootdir=. --print-missing --no-summary \
--start-date=2009/02/13 \
--sensors=S13 --type=out 2>&1

rwfglob --data-rootdir=. --print-missing --no-summary \
--start-date=2009/02/13:00 \
--sensors=S13 --type=out 2>&1

rwfglob --data-rootdir=. --print-missing --no-summary \
--start-date=1234483200 \
--sensors=S13 --type=out 2>&1

rwfglob --data-rootdir=. --print-missing --no-summary \
--start-date=2009/02/13T14:15:16 \
--sensors=S13 --type=out 2>&1

```

```

rwfglob --data-rootdir=. --print-missing --no-summary \
--start-date=1234534516 \
--sensors=S13 --type=out 2>&1

rwfglob --data-rootdir=. --print-missing --no-summary \
--start-date=2009/02/13 --end-date=2009/02/13 \
--sensors=S13 --type=out 2>&1

rwfglob --data-rootdir=. --print-missing --no-summary \
--start-date=2009/02/13:00 --end-date=2009/02/13 \
--sensors=S13 --type=out 2>&1

rwfglob --data-rootdir=. --print-missing --no-summary \
--start-date=1234483200 --end-date=2009/02/13 \
--sensors=S13 --type=out 2>&1

rwfglob --data-rootdir=. --print-missing --no-summary \
--start-date=2009/02/13T14:15:16 --end-date=2009/02/13 \
--sensors=S13 --type=out 2>&1

rwfglob --data-rootdir=. --print-missing --no-summary \
--start-date=1234534516 --end-date=2009/02/13 \
--sensors=S13 --type=out 2>&1

rwfglob --data-rootdir=. --print-missing --no-summary \
--start-date=2009/02/13 --end-date=2009/02/14 \
--sensors=S13 --type=out 2>&1

rwfglob --data-rootdir=. --print-missing --no-summary \
--start-date=2009/02/13:00 --end-date=2009/02/14 \
--sensors=S13 --type=out 2>&1

rwfglob --data-rootdir=. --print-missing --no-summary \
--start-date=1234483200 --end-date=2009/02/14 \
--sensors=S13 --type=out 2>&1

rwfglob --data-rootdir=. --print-missing --no-summary \
--start-date=2009/02/13T14:15:16 --end-date=2009/02/14 \
--sensors=S13 --type=out 2>&1

rwfglob --data-rootdir=. --print-missing --no-summary \
--start-date=1234534516 --end-date=2009/02/14 \
--sensors=S13 --type=out 2>&1

rwfglob --data-rootdir=. --print-missing --no-summary \
--start-date=2009/02/13 --end-date=1234569600 \
--sensors=S13 --type=out 2>&1

```



```

rwfglob --data-rootdir=. --print-missing --no-summary \
--start-date=2009/02/13:00 --end-date=1234569600 \
--sensors=S13 --type=out 2>&1

rwfglob --data-rootdir=. --print-missing --no-summary \
--start-date=1234483200 --end-date=1234569600 \
--sensors=S13 --type=out 2>&1

rwfglob --data-rootdir=. --print-missing --no-summary \
--start-date=2009/02/13T14:15:16 --end-date=1234569600 \
--sensors=S13 --type=out 2>&1

rwfglob --data-rootdir=. --print-missing --no-summary \
--start-date=1234534516 --end-date=1234569600 \
--sensors=S13 --type=out 2>&1

rwfglob --data-rootdir=. --print-missing --no-summary \
--start-date=2009/02/13 --end-date=2009/02/13T15:16:17 \
--sensors=S13 --type=out 2>&1

rwfglob --data-rootdir=. --print-missing --no-summary \
--start-date=2009/02/13:00 \
--end-date=2009/02/13T15:16:17 \
--sensors=S13 --type=out 2>&1

rwfglob --data-rootdir=. --print-missing --no-summary \
--start-date=1234483200 --end-date=2009/02/13T15:16:17 \
--sensors=S13 --type=out 2>&1

rwfglob --data-rootdir=. --print-missing --no-summary \
--start-date=2009/02/13T14:15:16 \
--end-date=2009/02/13T15:16:17 \
--sensors=S13 --type=out 2>&1

rwfglob --data-rootdir=. --print-missing --no-summary \
--start-date=1234534516 --end-date=2009/02/13T15:16:17 \
--sensors=S13 --type=out 2>&1

rwfglob --data-rootdir=. --print-missing --no-summary \
--start-date=2009/02/13 --end-date=1234538177 \
--sensors=S13 --type=out 2>&1

rwfglob --data-rootdir=. --print-missing --no-summary \
--start-date=2009/02/13:00 --end-date=1234538177 \
--sensors=S13 --type=out 2>&1

```

```

rwfglob --data-rootdir=. --print-missing --no-summary \
--start-date=1234483200 --end-date=1234538177 \
--sensors=S13 --type=out 2>&1

rwfglob --data-rootdir=. --print-missing --no-summary \
--start-date=2009/02/13T14:15:16 --end-date=1234538177 \
--sensors=S13 --type=out 2>&1

rwfglob --data-rootdir=. --print-missing --no-summary \
--start-date=1234534516 --end-date=1234538177 \
--sensors=S13 --type=out 2>&1

rwfglob --data-rootdir=. --print-missing \
--start-date=2009/02/12:12 --end-date=2009/02/12:14 \
--type=inweb --sensor=S12 2>&1

rwfglob --data-rootdir=. --print-missing \
--start-date=2009/02/12:12 --end-date=2009/02/12:14 \
--type=out 2>&1

rwfilter --active-time=2009/02/13:00:00-2009/02/13:00:05 \
--pass=stdout data.rwf \
| rwcatt --compression-method=none --byte-order=little \
--ipv4-output

rwfilter --any-address=2001:db8:c0:a8::x:c1:ff,c0:x \
--fail=stdout data-v6.rwf \
| rwcatt --compression-method=none --byte-order=little

rwfilter --any-address=192.168.192-255.x \
--fail=stdout data.rwf \
| rwcatt --compression-method=none --byte-order=little \
--ipv4-output

rwfilter --any-cidr=2001:db8:c0:a8::c0:0/107,2001:db8:c0:a8::e0:0/107 \
--fail=stdout data-v6.rwf \
| rwcatt --compression-method=none --byte-order=little

rwfilter --any-cidr=192.168.192.0/18 --fail=stdout data.rwf \
| rwcatt --compression-method=none --byte-order=little \
--ipv4-output

rwfilter --pmap-file=ip-map-v6.pmap \
--pmap-any-service-host=dhcp \
--pass=stdout data-v6.rwf \
| rwcatt --compression-method=none --byte-order=little

```

```

rwfilter --pmap-file=ip-map.pmap --pmap-any-service-host=dhcp \
  --pass=stdout data.rwf \
| rwcat --compression-method=none --byte-order=little \
  --ipv4-output

echo 192.168.192-255.x \
| rwsetbuild - - \
| rwfilter --anyset=- --fail=stdout data.rwf \
| rwcat --compression-method=none --byte-order=little \
  --ipv4-output

rwfilter --aport=25 --proto=6 --pass=stdout data.rwf \
| rwcat --compression-method=none --byte-order=little \
  --ipv4-output

rwfilter --application=80 --pass=stdout data.rwf \
| rwcat --compression-method=none --byte-order=little \
  --ipv4-output

rwfilter --data-rootdir=. --print-missing \
  --start-date=2009/02/12:12 --end-date=2009/02/12:14 \
  --sensors=@/tmp/sensor2.txt --type=@/tmp/type.txt \
  --all=/dev/null 2>&1 \

rwfilter --type=@/tmp/type.txt --pass=stdout data.rwf \
| rwcat --compression-method=none --byte-order=little \
  --ipv4-output

rwfilter --attributes=T/T --pass=stdout data.rwf \
| rwcat --compression-method=none --byte-order=little \
  --ipv4-output

rwfilter --attributes=c/- --pass=stdout data.rwf \
| rwcat --compression-method=none --byte-order=little \
  --ipv4-output

rwfilter --bytes-per-packet=39-60 --pass=stdout data.rwf \
| rwcat --compression-method=none --byte-order=little \
  --ipv4-output

rwfilter --bytes=1-100 --pass=stdout data.rwf \
| rwcat --compression-method=none --byte-order=little \
  --ipv4-output

rwfilter --dcc=xg,xj,xq --pass=stdout data-v6.rwf \
| rwcat --compression-method=none --byte-order=little

```

```

rwfilter --dcc=xg,xj,xq --pass=stdout data.rwf \
| rwcatt --compression-method=none --byte-order=little \
  --ipv4-output

rwfilter --pmap-file=ip-map-v6.pmap \
  --pmap-dst-service-host='internal,internal services' \
  --pass=stdout data-v6.rwf \
| rwcatt --compression-method=none --byte-order=little

rwfilter --pmap-file=ip-map.pmap \
  --pmap-dst-service-host='internal,internal services' \
  --pass=stdout data.rwf \
| rwcatt --compression-method=none --byte-order=little \
  --ipv4-output

rwfilter --dport=25 --pass=stdout data.rwf \
| rwcatt --compression-method=none --byte-order=little \
  --ipv4-output

rwfilter --pmap-file=service:proto-port-map.pmap \
  --pmap-dst-service=TCP/HTTP,TCP/HTTPS \
  --pass=stdout data.rwf \
| rwcatt --compression-method=none --byte-order=little \
  --ipv4-output

rwfilter --dtype=2 --pass=stdout data.rwf \
| rwcatt --compression-method=none --byte-order=little \
  --ipv4-output

rwfilter --duration=1-5 --pass=stdout data.rwf \
| rwcatt --compression-method=none --byte-order=little \
  --ipv4-output

rwfilter --etime=2009/02/13:00:00-2009/02/13:00:05 \
  --pass=stdout data.rwf \
| rwcatt --compression-method=none --byte-order=little \
  --ipv4-output

rwfilter --data-rootdir=. --print-missing \
  --start-date=2009/02/12:12 --end-date=2009/02/12:14 \
  --sensors=S4,S6,S7,S8,S10 --type=in,outweb \
  --all=/dev/null 2>&1

rwfilter --flags-all=R/R --pass=stdout data.rwf \
| rwcatt --compression-method=none --byte-order=little \
  --ipv4-output

```

```

rwfilter --flags-init=S/SA --pass=stdout data.rwf \
| rwcat --compression-method=none --byte-order=little \
  --ipv4-output

rwfilter --flags-session=F,C/C --pass=stdout data.rwf \
| rwcat --compression-method=none --byte-order=little \
  --ipv4-output

rwfilter --flags-session=pa/- --pass=stdout data.rwf \
| rwcat --compression-method=none --byte-order=little \
  --ipv4-output

rwfilter --plugin=flowrate.so --bytes-per-second=100- \
  --pass=stdout data.rwf \
| rwcat --compression-method=none --byte-order=little \
  --ipv4-output

rwfilter --plugin=flowrate.so --proto=17 \
  --print-volume-statistics=stdout data.rwf

rwfilter --plugin=flowrate.so --packets-per-second=100-1000 \
  --pass=stdout data.rwf \
| rwcat --compression-method=none --byte-order=little \
  --ipv4-output

rwfilter --icmp-code=3 --pass=stdout data.rwf \
| rwcat --compression-method=none --byte-order=little \
  --ipv4-output

rwfilter --icmp-type=3 --pass=stdout data.rwf \
| rwcat --compression-method=none --byte-order=little \
  --ipv4-output

rwfilter --input-index=10 --pass=stdout data.rwf \
| rwcat --compression-method=none --byte-order=little \
  --ipv4-output

rwfilter --ip-version=4 --pass=stdout data.rwf \
| rwcat --compression-method=none --byte-order=little \
  --ipv4-output

rwfilter --proto=17 --print-volume-statistics=stdout data.rwf

rwfilter --proto=17 --max-fail=200 --fail=stdout data.rwf \
| rwcat --compression-method=none --byte-order=little \
  --ipv4-output

```

```

rwfilter --proto=17 --max-pass=100 --max-fail=200 \
--pass=/tmp/rwfilter-max-pass-fail-pass \
--fail=/tmp/rwfilter-max-pass-fail-fail data.rwf \
&& rwcut --fields=1-10 --ipv6-policy=ignore \
/tmp/rwfilter-max-pass-fail-pass \
/tmp/rwfilter-max-pass-fail-fail \

rwfilter --proto=17 --max-pass=100 --pass=stdout data.rwf \
| rwcata --compression-method=none --byte-order=little \
--ipv4-output \

rwfilter --proto=17 --pass=stdout data.rwf data.rwf data.rwf \
| rwuniq --fields=1-5 --ipv6-policy=ignore \
--timestamp-format=epoch \
--values=bytes,packets,records,stime,etime \
--sort-output --delimited --no-titles \

rwfilter --not-any-address=2001:db8:c0:a8:x:x:c0:ff:x \
--pass=stdout data-v6.rwf \
| rwcata --compression-method=none --byte-order=little \

rwfilter --not-any-address=192.168.255,192-254.x \
--pass=stdout data.rwf \
| rwcata --compression-method=none --byte-order=little \
--ipv4-output \

rwfilter --not-any-cidr=2001:db8:c0:a8::c0:0/106 \
--pass=stdout data-v6.rwf \
| rwcata --compression-method=none --byte-order=little \

rwfilter --not-any-cidr=192.168.192.0/19,192.168.224.0/20,192.168.240.0/21,192.168.248.0/22,192.168.252.0/23,192.168.254.0/24 \
--pass=stdout data.rwf \
| rwcata --compression-method=none --byte-order=little \
--ipv4-output \

echo 192.168.255,192-254.x \
| rwsetbuild - - \
| rwfilter --not-anyset=- --pass=stdout data.rwf \
| rwcata --compression-method=none --byte-order=little \
--ipv4-output \

rwfilter --not-saddr=x:x:a:fc-ff::0-ffff:0,1-fab,fad-ffff,fac \
--pass=stdout data-v6.rwf \
| rwcata --compression-method=none --byte-order=little \

rwfilter --not-saddr=10.252-255.0-255.0,1-100,102-255,101 \
--pass=stdout data.rwf \
| rwcata --compression-method=none --byte-order=little \
--ipv4-output \

```

```

rwfilter --not-scidr=2001:db8:a:fc::/62 \
--pass=stdout data-v6.rwf \
| rwcatt --compression-method=none --byte-order=little

rwfilter --not-scidr=10.254.0.0/16,10.252.0.0/16,10.255.0.0/16,10.253.0.0/16 \
--pass=stdout data.rwf \
| rwcatt --compression-method=none --byte-order=little \
--ipv4-output

echo 10.252-255.x.x \
| rwsetbuild - - \
| rwfilter --not-sipset=- --pass=stdout data.rwf \
| rwcatt --compression-method=none --byte-order=little \
--ipv4-output

rwfilter --output-index=10 --pass=stdout data.rwf \
| rwcatt --compression-method=none --byte-order=little \
--ipv4-output

rwfilter --packets=1-50 --pass=stdout data.rwf \
| rwcatt --compression-method=none --byte-order=little \
--ipv4-output

rwfilter --plugin=flowrate.so --payload-bytes=0-1000 \
--pass=stdout data.rwf \
| rwcatt --compression-method=none --byte-order=little \
--ipv4-output

rwfilter --plugin=flowrate.so --payload-rate=1000.4-2000.9 \
--pass=stdout data.rwf \
| rwcatt --compression-method=none --byte-order=little \
--ipv4-output

rwfilter --proto=17 --print-statistics --print-filenames \
--pass=/dev/null data.rwf 2>&1

rwfilter --proto=17 \
--print-volume-statistics=stdout data-v6.rwf

rwfilter --proto=17 --print-volume-statistics=stdout data.rwf

rwfilter --proto=17 --pass=stdout data.rwf \
| rwcatt --compression-method=none --byte-order=little \
--ipv4-output

```

```

rwfilter --python-expr='rec.sport==rec.dport' \
--pass=stdout data.rwf \
| rwcatt --compression-method=none --byte-order=little \
--ipv4-output

rwfilter --python-file=pysilk-plugin.py \
--print-volume data.rwf 2>&1

rwfilter --proto=17 --print-volume-statistics=stdout data.rwf

rwfilter --saddress=2001:db8:a:fc-ff::x:x \
--fail=stdout data-v6.rwf \
| rwcatt --compression-method=none --byte-order=little

rwfilter --saddress=10.252-255.x.x --fail=stdout data.rwf \
| rwcatt --compression-method=none --byte-order=little \
--ipv4-output

rwfilter --scc=xz --dcc=xz --pass=stdout data-v6.rwf \
| rwcatt --compression-method=none --byte-order=little

rwfilter --scc=xz --dcc=xz --pass=stdout data.rwf \
| rwcatt --compression-method=none --byte-order=little \
--ipv4-output

rwfilter --scc=xa,xb,xc --pass=stdout data-v6.rwf \
| rwcatt --compression-method=none --byte-order=little

rwfilter --scc=xa,xb,xc --pass=stdout data.rwf \
| rwcatt --compression-method=none --byte-order=little \
--ipv4-output

rwfilter --scidr=2001:db8:a:fc::/63,2001:db8:a:fe::/63 \
--fail=stdout data-v6.rwf \
| rwcatt --compression-method=none --byte-order=little

rwfilter --scidr=10.252.0.0/15,10.254.0.0/15 \
--fail=stdout data.rwf \
| rwcatt --compression-method=none --byte-order=little \
--ipv4-output

rwfilter --pmap-file=ip-map-v6.pmap \
--pmap-src-service-host=ntp --pass=stdout data-v6.rwf \
| rwcatt --compression-method=none --byte-order=little

```



```

rwfilter --pmap-file=ip-map.pmap --pmap-src-service-host=ntp \
--pass=stdout data.rwf \
| rwcatt --compression-method=none --byte-order=little \
--ipv4-output

echo 10.252-255.x.x \
| rwsetbuild - - \
| rwfilter --sipset=- --fail=stdout data.rwf \
| rwcatt --compression-method=none --byte-order=little \
--ipv4-output

rwfilter --sport=25 --dport=25 --pass=stdout data.rwf \
| rwcatt --compression-method=none --byte-order=little \
--ipv4-output

rwfilter --pmap-file=proto-port-map.pmap \
--pmap-sport-protocol=UDP/DHCP --pass=stdout data.rwf \
| rwcatt --compression-method=none --byte-order=little \
--ipv4-output

rwfilter --sport=25 --pass=stdout data.rwf \
| rwcatt --compression-method=none --byte-order=little \
--ipv4-output

rwfilter data.rwf data.rwf data.rwf --all-dest=stdout \
| rwfilter --input-pipe=- --proto=17 --pass=stdout \
| rwuniq --fields=1-5 --ipv6-policy=ignore \
--timestamp-format=epoch \
--values=bytes,packets,records,stime,etime \
--sort-output --delimited --no-titles

rwfilter --stime=2009/02/13:00:00-2009/02/13:00:05 \
--pass=stdout data.rwf \
| rwcatt --compression-method=none --byte-order=little \
--ipv4-output

rwfilter --stype=1 --pass=stdout data.rwf \
| rwcatt --compression-method=none --byte-order=little \
--ipv4-output

rwfilter --threads=4 --proto=17 \
--pass=stdout data.rwf data.rwf data.rwf \
| rwuniq --fields=1-5 --ipv6-policy=ignore \
--timestamp-format=epoch \
--values=bytes,packets,records,stime,etime \
--sort-output --delimited --no-titles

```

```

echo 25,6 \
| rfilter --tuple-file=- --tuple-delim=, \
    --tuple-fields=sport,proto --tuple-direction=both \
    --pass=stdout data.rwf \
| rwcat --compression-method=none --byte-order=little \
    --ipv4-output

echo 25,6 \
| rfilter --tuple-file=- --tuple-delim=, \
    --tuple-fields=sport,proto --pass=stdout data.rwf \
| rwcat --compression-method=none --byte-order=little \
    --ipv4-output

echo 25,6 \
| rfilter --tuple-file=- --tuple-delim=, \
    --tuple-fields=sport,proto --tuple-direction=reverse \
    --pass=stdout data.rwf \
| rwcat --compression-method=none --byte-order=little \
    --ipv4-output

rfilter --pmap-file=service:proto-port-map.pmap \
    --pmap-file=ip-map-v6.pmap --pmap-any-service=UDP/NTP \
    --pmap-any-service-host=ntp --pass=stdout data-v6.rwf \
| rwcat --compression-method=none --byte-order=little

rfilter --pmap-file=service:proto-port-map.pmap \
    --pmap-file=ip-map.pmap --pmap-any-service=UDP/NTP \
    --pmap-any-service-host=ntp --pass=stdout data.rwf \
| rwcat --compression-method=none --byte-order=little \
    --ipv4-output

rfilter --type=in --pass=stdout data.rwf \
| rwcat --compression-method=none --byte-order=little \
    --ipv4-output

ls -l data.rwf data.rwf data.rwf \
| rfilter --xargs=stdin --proto=17 --pass=stdout \
| rwuniq --fields=1-5 --ipv6-policy=ignore \
    --timestamp-format=epoch \
    --values=bytes,packets,records,stime,etime \
    --sort-output --delimited --no-titles

rwguess --print-all small.pdu

rwguess small.pdu

rwguess --top=2 small.pdu

```

```

rwpackchecker --print-all data.rwf empty.rwf

rwpackchecker --value max-tcp-bpp=5000 \
  --allowable-count max-tcp-bpp=2 data.rwf

rwpdu2silk small.pdu \
| rwcatt --byte-order=big --ipv4-output --compression=none

rwsort --fields=dtype data.rwf \
| rwgroup --id-fields=dtype \
| rwcatt --compression-method=none --byte-order=little \
  --ipv4-output

rwsort --fields=stype data.rwf \
| rwgroup --id-fields=stype \
| rwcatt --compression-method=none --byte-order=little \
  --ipv4-output

rwsort --fields=dcc data.rwf \
| rwgroup --id-fields=dcc \
| rwcatt --compression-method=none --byte-order=little \
  --ipv4-output

rwsort --fields=scc data.rwf \
| rwgroup --id-fields=scc \
| rwcatt --compression-method=none --byte-order=little \
  --ipv4-output

rwsort --plugin=flowrate.so --fields=bytes/sec data.rwf \
| rwgroup --plugin=flowrate.so --id-fields=bytes/sec,stime,sip \
| rwcatt --compression-method=none --byte-order=little \
  --ipv4-output

rwsort --plugin=flowrate.so --fields=payload-bytes data.rwf \
| rwgroup --plugin=flowrate.so \
  --id-fields=payload-bytes,stime,sip \
| rwcatt --compression-method=none --byte-order=little \
  --ipv4-output

rwsort --plugin=flowrate.so --fields=pckts/sec data.rwf \
| rwgroup --plugin=flowrate.so --id-fields=pckts/sec,stime,sip \
| rwcatt --compression-method=none --byte-order=little \
  --ipv4-output

rwsort --fields=5,1,3,2,4 data.rwf \
| rwgroup --id-fields=5,1,3,2,4 \

```

```

| rwuniq --fields=1-5 --ipv6-policy=ignore          \
  --timestamp-format=epoch                          \
  --values=bytes,packets,records,stime,etime        \
  --sort-output --delimited --no-title              \

rwsort --fields=1 data-v6.rwf                       \
| rwgroup --delta-field=1 --delta-value=64          \
| rwcat --compression-method=none --byte-order=little

rwsort --fields=1 data.rwf                          \
| rwgroup --delta-field=1 --delta-value=16          \
| rwcat --compression-method=none --byte-order=little \
  --ipv4-output

rwsort --fields=1,2,9 data-v6.rwf                   \
| rwgroup --id-fields=1,2 --delta-field=9 --delta-value=15 \
  --summarize --rec-threshold=5                     \
| rwcat --compression-method=none --byte-order=little

rwsort --fields=1,2,9 data.rwf                      \
| rwgroup --id-fields=1,2 --delta-field=9 --delta-value=15 \
  --summarize --rec-threshold=5                     \
| rwcat --compression-method=none --byte-order=little \
  --ipv4-output

rwsort --fields=1,2,9 data.rwf                      \
| rwgroup --id-fields=1,2 --delta-field=9 --delta-value=15 \
  --summarize                                         \
| rwcat --compression-method=none --byte-order=little \
  --ipv4-output

rwsort --fields=1,2,9 data.rwf                      \
| rwgroup --id-fields=1,2 --delta-field=9 --delta-value=15 \
| rwcat --compression-method=none --byte-order=little \
  --ipv4-output

rwsort --fields=1,2,9 data-v6.rwf                   \
| rwgroup --id-fields=1,2                           \
| rwcat --compression-method=none --byte-order=little

rwsort --fields=1,2,9 data.rwf                      \
| rwgroup --id-fields=1,2                           \
| rwcat --compression-method=none --byte-order=little \
  --ipv4-output

rwfilter --type=in,inweb --pass=stdout data-v6.rwf \
| rwsort --pmap-file=servhost:ip-map-v6.pmap       \

```

```

--fields=dst-servhost \
| rwgroup --pmap-file=servhost:ip-map-v6.pmap \
--id-fields=dst-servhost \
| rwcat --compression-method=none --byte-order=little \
--ipv4-output

rwfilter --type=in,inweb --pass=stdout data.rwf \
| rwsort --pmap-file=servhost:ip-map.pmap \
--fields=dst-servhost \
| rwgroup --pmap-file=servhost:ip-map.pmap \
--id-fields=dst-servhost \
| rwcat --compression-method=none --byte-order=little \
--ipv4-output

rwfilter --type=in,inweb --pass=stdout data-v6.rwf \
| rwsort --pmap-file=service-port:proto-port-map.pmap \
--pmap-file=ip-map-v6.pmap \
--fields=src-service-host,src-service-port \
| rwgroup --pmap-file=service-port:proto-port-map.pmap \
--pmap-file=ip-map-v6.pmap \
--id-fields=src-service-host,src-service-port \
| rwcat --compression-method=none --byte-order=little

rwfilter --type=in,inweb --pass=stdout data.rwf \
| rwsort --pmap-file=service-port:proto-port-map.pmap \
--pmap-file=ip-map.pmap \
--fields=src-service-host,src-service-port \
| rwgroup --pmap-file=service-port:proto-port-map.pmap \
--pmap-file=ip-map.pmap \
--id-fields=src-service-host,src-service-port \
| rwcat --compression-method=none --byte-order=little \
--ipv4-output

rwfilter --type=in,inweb --pass=stdout data.rwf \
| rwsort --pmap-file=proto-port-map.pmap --fields=sval \
| rwgroup --pmap-file=proto-port-map.pmap --id-fields=sval \
| rwcat --compression-method=none --byte-order=little \
--ipv4-output

rwfilter --type=in,inweb --pass=stdout data-v6.rwf \
| rwsort --pmap-file=ip-map-v6.pmap --fields=src-service-host \
| rwgroup --pmap-file=ip-map-v6.pmap \
--id-fields=src-service-host \
| rwcat --compression-method=none --byte-order=little \
--ipv4-output

rwfilter --type=in,inweb --pass=stdout data.rwf \
| rwsort --pmap-file=ip-map.pmap --fields=src-service-host \

```

```

| rwgroup --pmap-file=ip-map.pmap \
  --id-fields=src-service-host \
| rwcat --compression-method=none --byte-order=little \
  --ipv4-output \

rwsort --fields=3,4,9 data.rwf \
| rwgroup --id-fields=3,4 --delta-field=9 --delta-value=15 \
  --objective \
| rwcat --compression-method=none --byte-order=little \
  --ipv4-output \

rwsort --python-file=pysilk-plugin.py \
  --fields=lower_port data.rwf \
| rwgroup --python-file=pysilk-plugin.py \
  --id-fields=lower_port \
| rwcat --compression-method=none --byte-order=little \
  --ipv4-output \

cat data.rwf \
| rwuniq --fields=1-5 --ipv6-policy=ignore \
  --timestamp-format=epoch \
  --values=bytes,packets,records,stime,etime \
  --sort-output --delimited --no-title \

rwsort --fields=3 data.rwf \
| rwgroup --id-fields=3 --rec-threshold=20 \
  --group-offset=0.1.0.0 \
| rwcat --compression-method=none --byte-order=little \
  --ipv4-output \

rwsort --fields=3 data.rwf \
| rwgroup --id-fields=3 \
| rwcat --compression-method=none --byte-order=little \
  --ipv4-output \

rwidquery --intype=fast --year=2009 --dry-run \
  /tmp/rwidquery-fast-fast 2>&1

rwidquery --intype=full --year=2009 --dry-run \
  /tmp/rwidquery-full-full 2>&1

rwidquery --intype=rule --start-date=2009/02/11:10 \
  --end-date=2009/02/11:12 --dry-run \
  /tmp/rwidquery-rule-rule 2>&1

rwsilk2ipfix data-v6.rwf \
| rwipfix2silk --silk-output=/dev/null \
  --log-destination=stderr --print-stat 2>&1

```

```

rwsilk2ipfix data.rwf \
| rwipfix2silk --silk-output=/dev/null \
  --log-destination=stderr --print-stat 2>&1

rwsilk2ipfix data-v6.rwf --ipfix-output=/dev/null \
  --print-stat 2>&1

rwsilk2ipfix data.rwf --ipfix-output=/dev/null \
  --print-stat 2>&1

rwsilk2ipfix data-v6.rwf \
| rwipfix2silk --silk-output=stdout \
| rwcatt --compression-method=none --byte-order=little

rwsilk2ipfix data.rwf \
| rwipfix2silk --silk-output=stdout \
| rwcatt --compression-method=none --byte-order=little \
  --ipv4-output

rwsilk2ipfix empty.rwf data.rwf empty.rwf \
| rwipfix2silk \
| rwcatt --compression-method=none --byte-order=little \
  --ipv4-output

cat data.rwf \
| rwsilk2ipfix --ipfix-output=stdout \
| rwipfix2silk \
| rwcatt --compression-method=none --byte-order=little \
  --ipv4-output

rwfilter --daddr=192.168.x.x --dport=0-1024 \
  --pass=stdout data.rwf \
| rwsort --fields=1,4,2,3,5,9 \
  --output-path=/tmp/rwmatch-int-server-incoming \
&& rwfilter --saddr=192.168.x.x --sport=0-1024 \
  --pass=stdout data.rwf \
| rwsort --fields=2,3,1,4,5,9 \
  --output-path=/tmp/rwmatch-int-server-outgoing \
&& rwmatch --ipv6-policy=asv4 --time-delta=2.5 \
  --symmetric-del --relative-del --relate=1,2 \
  --relate=4,3 --relate=2,1 --relate=3,4 --relate=5,5 \
  /tmp/rwmatch-int-server-incoming \
  /tmp/rwmatch-int-server-outgoing - \
| rwcatt --plugin=cutmatch.so --ipv6-policy=asv4 \
  --fields=match,sip,sport,dip,dport,proto,type

rwfilter --daddr=2001:db8:c0:a8::/64 --sport=0-1024 \

```

```

--pass=stdout data-v6.rwf \
| rwsort --fields=1,4,2,3,5,9 \
--output-path=/tmp/rwmatch-ext-server-v6-incoming \
&& rwfilter --saddr=2001:db8:c0:a8::/64 --dport=0-1024 \
--pass=stdout data-v6.rwf \
| rwsort --fields=2,3,1,4,5,9 \
--output-path=/tmp/rwmatch-ext-server-v6-outgoing \
&& rwmatch --time-delta=2.5 --symmetric-del --relative-del \
--relate=2,1 --relate=3,4 --relate=1,2 --relate=4,3 \
--relate=5,5 /tmp/rwmatch-ext-server-v6-outgoing \
/tmp/rwmatch-ext-server-v6-incoming - \
| rwcats --compression-method=none --byte-order=little \

rwfilter --daddr=192.168.x.x --sport=0-1024 \
--pass=stdout data.rwf \
| rwsort --fields=1,4,2,3,5,9 \
--output-path=/tmp/rwmatch-ext-server-incoming \
&& rwfilter --saddr=192.168.x.x --dport=0-1024 \
--pass=stdout data.rwf \
| rwsort --fields=2,3,1,4,5,9 \
--output-path=/tmp/rwmatch-ext-server-outgoing \
&& rwmatch --time-delta=2.5 --symmetric-del --relative-del \
--relate=2,1 --relate=3,4 --relate=1,2 --relate=4,3 \
--relate=5,5 /tmp/rwmatch-ext-server-outgoing \
/tmp/rwmatch-ext-server-incoming - \
| rwcats --compression-method=none --byte-order=little \
--ipv4-output \

rwfilter --daddr=2001:db8:c0:a8::/64 --dport=0-1024 \
--pass=stdout data-v6.rwf \
| rwsort --fields=1,4,2,3,5,9 \
--output-path=/tmp/rwmatch-int-server-v6-incoming \
&& rwfilter --saddr=2001:db8:c0:a8::/64 --sport=0-1024 \
--pass=stdout data-v6.rwf \
| rwsort --fields=2,3,1,4,5,9 \
--output-path=/tmp/rwmatch-int-server-v6-outgoing \
&& rwmatch --time-delta=2.5 --symmetric-del --relative-del \
--relate=1,2 --relate=4,3 --relate=2,1 --relate=3,4 \
--relate=5,5 /tmp/rwmatch-int-server-v6-incoming \
/tmp/rwmatch-int-server-v6-outgoing - \
| rwcats --compression-method=none --byte-order=little \

rwfilter --daddr=192.168.x.x --dport=0-1024 \
--pass=stdout data.rwf \
| rwsort --fields=1,4,2,3,5,9 \
--output-path=/tmp/rwmatch-int-server-incoming \
&& rwfilter --saddr=192.168.x.x --sport=0-1024 \
--pass=stdout data.rwf \
| rwsort --fields=2,3,1,4,5,9 \

```



```

--output-path=/tmp/rwmatch-int-server-outgoing \
&& rwmatch --ipv6-policy=asv4 --time-delta=2.5 \
--symmetric-del --relative-del --relate=1,2 \
--relate=4,3 --relate=2,1 --relate=3,4 --relate=5,5 \
/tmp/rwmatch-int-server-incoming \
/tmp/rwmatch-int-server-outgoing - \
| rwcat --compression-method=none --byte-order=little \
--ipv4-output \

rwnetmask --6dip-prefix=64 --6sip-prefix=120 data-v6.rwf \
| rwcat --compression-method=none --byte-order=little \
--milliseconds \

rwnetmask --6sip-prefix-length=120 data-v6.rwf \
| rwcat --compression-method=none --byte-order=little \
--milliseconds \

rwnetmask --dip-prefix=16 --sip-prefix=24 data.rwf \
| rwcat --compression-method=none --byte-order=little \
--milliseconds --ipv4-output \

rwnetmask --sip-prefix-length=24 data.rwf \
| rwcat --compression-method=none --byte-order=little \
--milliseconds --ipv4-output \

cat data.rwf \
| rwnetmask --sip-prefix-length=24 \
| rwcat --compression-method=none --byte-order=little \
--milliseconds --ipv4-output \

rwgeoip2ccmap --input-path tests \
--output-path /tmp/country_pmap \
rwpmapcat --country-codes=/tmp/country_pmap --no-cidr \
cat /tmp/country_pmap \
| rwfileinfo --fields=format,record-version,count-records - \

cat fake-cc-v6.csv fake-cc.csv \
| rwgeoip2ccmap --input-path - --output-path /tmp/country_pmap \
rwpmapcat --country-codes=/tmp/country_pmap --no-cidr \
cat /tmp/country_pmap \
| rwfileinfo --fields=format,record-version,count-records - \

rwgeoip2ccmap --input-path=fake-cc.csv \
--output-path /tmp/country_pmap \
rwpmapcat --country-codes=/tmp/country_pmap --no-cidr \
cat /tmp/country_pmap \
| rwfileinfo --fields=format,record-version,count-records - \

```

```

rwgeoip2ccmap --input-path=fake-cc-v6.csv \
  --output-path /tmp/country_pmap
rwmapcat --country-codes=/tmp/country_pmap --no-cidr \
cat /tmp/country_pmap \
| rfileinfo --fields=format,record-version,count-records -

rwip2cc --map-file=fake-cc.pmap --print-ips=0 \
  --address=10.10.10.10

rwip2cc --map-file=fake-cc.pmap --print-ips=1 \
  --address=10.10.10.10

rwip2cc --map-file=fake-cc.pmap --address=10.10.10.10

rwcut --fields=sip --ipv6-policy=ignore --no-title \
  --delimited data.rwf \
| rwip2cc --input-file=-

echo 10.10.10.10 \
| rwip2cc --map-file=fake-cc.pmap --input-file=- --delimited=,

echo 10.10.10.10 \
| rwip2cc --input-file=-

echo 10.10.10.10 \
| rwip2cc --map-file=fake-cc.pmap --input-file=- \
  --integer-ips --column-separator=/

echo 10.10.10.10 \
| rwip2cc --map-file=fake-cc.pmap --input-file=- --no-columns

echo 10.10.10.10 \
| rwip2cc --map-file=fake-cc.pmap --input-file=- --print-ips=0

echo 10.10.10.10 \
| rwip2cc --map-file=fake-cc.pmap --input-file=- --print-ips=1

echo 10.10.10.10 \
| rwip2cc --map-file=fake-cc.pmap --input-file=- \
  --zero-pad-ips --no-final-delimiter

echo 10.10.10.10 \
| rwip2cc --map-file=fake-cc.pmap --input-file=-

/usr/bin/env SILK_ADDRESS_TYPES=address_types.pmap \
rwmapcat --no-cidr --address-types

```

```
rwmapcat --no-cidr --address-types=address_types.pmap

rwmapcat --no-cidr fake-cc.pmap

rwmapcat --no-cidr fake-cc-v6.pmap

rwmapcat --no-cidr --country-codes=fake-cc-v6.pmap

/usr/bin/env SILK_COUNTRY_CODES=fake-cc.pmap \
rwmapcat --no-cidr --country-codes

rwmapcat --delimited=, --no-cidr --map-file ip-map.pmap

rwmapcat --ip-label-to-ignore=: ip-map-v6.pmap

rwmapcat --ip-label-to-ignore=0.0.0.0 ip-map.pmap

rwmapcat --ignore-label=external ip-map.pmap

rwmapcat --ip-format=decimal --no-columns \
--output-path=stdout --map-file ip-map.pmap

rwmapcat --output-type=labels --map-file ip-map.pmap

rwmapcat --left-justify-labels ip-map.pmap

rwmapcat --output-type=mapname --map-file ip-map.pmap

rwmapcat --no-cidr-blocks ip-map-v6.pmap

rwmapcat --no-cidr-blocks --map-file ip-map.pmap

rwmapcat --output-type=type --no-titles ip-map.pmap

rwmapcat ip-map-v6.pmap

rwmapcat --ip-format=zero-padded \
--output-type=ranges ip-map.pmap

rwmapcat ip-map.pmap

rwmapcat --ignore-label=unknown proto-port-map.pmap
```

```

rwpmmapcat --output-type=labels --no-title proto-port-map.pmap

rwpmmapcat --output-type=mapname proto-port-map.pmap

rwpmmapcat --no-titles proto-port-map.pmap

rwpmmapcat --output-type=type,mapname \
    --map-file=proto-port-map.pmap

rwpmmapcat --column-sep=, --map-file=proto-port-map.pmap

cat ip-map.pmap \
| rwpmmapcat --map-file=- --no-cidr

cat ip-map.pmap \
| rwpmmapcat --no-cidr

rwpmmaplookup --country-codes=fake-cc.pmap --no-title \
    --fields=block,key,value \
    --no-files 10.10.10.10 10.200.200.200

rwpmmaplookup --map-file=ip-map.pmap --no-title \
    --fields=block,key,value \
    --no-files 172.16.17.18 172.30.31.32

rwpmmaplookup --map-file=ip-map-v6.pmap --no-title \
    --fields=block,key,value \
    --no-files 2001:db8:ac:10::11:12 2001:db8:ac:1e::1f:20

rwpmmaplookup --map-file=proto-port-map.pmap --no-title \
    --fields=block,key,value --no-files 17/0 6/0

echo 6/22 > /tmp/rwpmmaplookup-files-proto-port-file1 \
; echo 6/25 > /tmp/rwpmmaplookup-files-proto-port-file2 \
; echo 6/80 > /tmp/rwpmmaplookup-files-proto-port-file3 \
; rwpmmaplookup --map-file=proto-port-map.pmap \
    /tmp/rwpmmaplookup-files-proto-port-file1 \
    /tmp/rwpmmaplookup-files-proto-port-file2 \
    /tmp/rwpmmaplookup-files-proto-port-file3 \

rwcut --fields=sip --ipv6-policy=ignore --no-title \
    --num-rec=1000 --delimited data.rwf \
| rwsetbuild \
| /usr/bin/env SILK_ADDRESS_TYPES=address_types.pmap \
    rwpmmaplookup --ipset-files --address-types --no-final-delim

```

```

rwcut --fields=sip --no-title --start-rec=1000 --num-rec=1000 \
    --delimited data-v6.rwf \
| rwsbuild \
| rwpmaplookup --ipset-files --delimited \
    --country-codes=fake-cc-v6.pmap --fields=value,input

rwcut --fields=sip --ipv6-policy=ignore --no-title \
    --start-rec=1000 --num-rec=1000 --delimited data.rwf \
| rwsbuild \
| rwpmaplookup --country-codes=fake-cc.pmap \
    --fields=value,input --delimited --ipset-files

echo 192.168.72.72 \
| rwsbuild \
| rwpmaplookup --ipset-files --map-file=ip-map.pmap \
    --ip-format=decimal --fields=key,value,input

rwcut --fields=sip --no-title --num-rec=200 \
    --delimited data-v6.rwf \
| rwsbuild - /tmp/rwpmaplookup-ipset-ip-v6-file1 \
&& rwpmaplookup --map-file=ip-map-v6.pmap \
    --ip-format=zero-padded --fields=key,value,input \
    --ipset-files /tmp/rwpmaplookup-ipset-ip-v6-file1

/usr/bin/env SILK_ADDRESS_TYPES=address_types.pmap \
rwpmaplookup --address-types --column-sep=, \
    --no-files 10.10.10.10

/usr/bin/env SILK_COUNTRY_CODES=fake-cc-v6.pmap \
rwpmaplookup --country-codes --no-title \
    --no-files 2001:db8:a:a::a:a

/usr/bin/env SILK_COUNTRY_CODES=fake-cc.pmap \
rwpmaplookup --country-codes --no-title --no-files 10.10.10.10

rwpmaplookup --map-file=ip-map.pmap --no-title \
    --no-files 192.168.72.72

rwpmaplookup --map-file=ip-map-v6.pmap \
    --no-files 2001:db8:ac:18::ba:d

rwpmaplookup --map-file=proto-port-map.pmap --no-title \
    --no-files 17/67

/usr/bin/env SILK_COUNTRY_CODES=fake-cc.pmap \
rwpmaplookup --country-codes --no-title \
    --fields=start-block,end-block,value \
    --no-files 10.10.10.10 10.200.200.200

```

```

rwpmlookup --map-file=ip-map.pmap --no-title \
  --fields=start-block,end-block,value \
  --no-files 172.16.17.18 172.30.31.32

rwpmlookup --map-file=ip-map-v6.pmap --no-title \
  --fields=start-block,end-block,value \
  --no-files 2001:db8:ac:10::11:12 2001:db8:ac:1e::1f:20

rwpmlookup --map-file=proto-port-map.pmap --no-title \
  --fields=start-block,end-block,value \
  --no-files 17/0 6/0

rwcut --fields=sip --ipv6-policy=ignore --no-title \
  --num-rec=1000 --delimited data.rwf \
  | /usr/bin/env SILK_ADDRESS_TYPES=address_types.pmap \
  rwpmlookup --address-types --no-final-delim

rwcut --fields=sip --no-title --start-rec=1000 --num-rec=1000 \
  --delimited data-v6.rwf \
  | rwpmlookup --country-codes=fake-cc-v6.pmap \
  --fields=value,input --delimited

rwcut --fields=sip --ipv6-policy=ignore --no-title \
  --start-rec=1000 --num-rec=1000 --delimited data.rwf \
  | rwpmlookup --country-codes=fake-cc.pmap \
  --fields=value,input --delimited

echo 192.168.72.72 \
  | rwpmlookup --map-file=ip-map.pmap --ip-format=decimal \
  --fields=key,value,input

rwcut --fields=sip --no-title --num-rec=200 \
  --delimited data-v6.rwf \
  | rwpmlookup --map-file=ip-map-v6.pmap \
  --ip-format=zero-padded --fields=key,value,input

rwpmlookup --address-types=address_types.pmap \
  --fields=value --no-title -delim --no-files 10.10.10.10

rwpmlookup --country-codes=fake-cc-v6.pmap --fields=value \
  --no-title -delim --no-files 2001:db8:a:a::a:a

rwpmlookup --country-codes=fake-cc.pmap --fields=value \
  --no-title -delim --no-files 10.10.10.10

rwpmlookup --map-file=ip-map.pmap --fields=value \
  --no-title -delim --no-files 192.168.72.72

```

```

rwpmlookup --map-file=ip-map-v6.pmap --fields=value \
    --no-title -delim --no-files 2001:db8:ac:18::ba:d

rwpmlookup --map-file=proto-port-map.pmap --fields=value \
    --no-title -delim --no-files 17/67

rwrandoizeip --seed=38901 --consistent data.rwf - \
| rwcatt --compression-method=none --byte-order=little \
    --ipv4-output --milliseconds

rwrandoizeip --seed=38901 --save-table=stdout data.rwf \
    /dev/null \
| rwrandoizeip --load-table=stdin data.rwf - \
| rwcatt --compression-method=none --byte-order=little \
    --ipv4-output --milliseconds

rwrandoizeip --seed=38901 data.rwf stdout \
| rwcatt --compression-method=none --byte-order=little \
    --ipv4-output --milliseconds

cat data.rwf \
| rwrandoizeip --seed=38901 --consistent - - \
| rwcatt --compression-method=none --byte-order=little \
    --ipv4-output --milliseconds

rwrecgenerator --seed 987654321 --log-dest=none \
    --start-time=2011/01/01:00 --end-time=2011/01/01:01 \
    --time-step=1000 --silk-output-path - \
| rwcatt --ipv6=ignore \
    --fields=1-7,9-12,class,type,initialFlag,sessionFlag,attribute,application,icmpTypeCode

rwrecgenerator --seed 987654321 --log-dest=none \
    --start-time=2011/01/01:00 --end-time=2011/01/01:01 \
    --time-step=1000 --text-output-path -

echo '0.0.0.0|0.0.0.0|' \
| rwresolve --ip-fields=4,8 --column-width=20

echo '0.0.0.0|0.0.0.0|' \
| rwresolve --column-width=20

echo '0.0.0.0,0.0.0.0' \
| rwresolve --delimiter=, --column-width=20

echo '0.0.0.0|0.0.0.0' \
| rwresolve --column-width=20

```

```

echo '0.0.0.0|0.0.0.0|' \
| rwresolve --ip-fields=1 --column-width=20

echo '0.0.0.0|0.0.0.0|' \
| rwresolve --ip-fields=1,4 --column-width=20

rwfilter --daddr=192.168.0.0/16 --pass=stdout data.rwf \
| rwsort --fields=sip,proto,dip - scandata.rwf \
| rwscan --scan-mode=2

rwfilter --daddr=192.168.0.0/16 \
--pass=/tmp/rwscan-hybrid-in data.rwf \
&& rwset --dip=/tmp/rwscan-hybrid-inset /tmp/rwscan-hybrid-in \
&& rwsort --fields=sip,proto,dip \
/tmp/rwscan-hybrid-in scandata.rwf \
| rwscan --trw-sip-set=/tmp/rwscan-hybrid-inset

rwfilter --daddr=192.168.0.0/16 \
--pass=/tmp/rwscan-trw-only-in data.rwf \
&& rwset --dip=/tmp/rwscan-trw-only-inset \
/tmp/rwscan-trw-only-in \
&& rwsort --fields=sip,proto,dip \
/tmp/rwscan-trw-only-in scandata.rwf \
| rwscan --scan-mode=1 --trw-sip-set=/tmp/rwscan-trw-only-inset

rwset --sip-file=/dev/null --copy-input=stdout data.rwf \
| rwset --sip-file=- \
| rwsetcat --print-ips

rwset --dip-file=stdout data-v6.rwf \
| rwsetcat --cidr-blocks=0

rwset --dip-file=stdout data.rwf \
| rwsetcat --cidr-blocks=0

rwset --sip-file=stdout empty.rwf data.rwf empty.rwf \
| rwsetcat --cidr-blocks=0

rwset --nhip-file=stdout data-v6.rwf \
| rwsetcat

rwset --nhip-file=stdout data.rwf \
| rwsetcat

rwset --sip=stdout --dip=/dev/null data-v6.rwf \
| rwsetcat --cidr-blocks=0 --ip-format=hexadecimal

```



```
rwset --sip=stdout --dip=/dev/null data.rwf \
| rwsetcat --cidr-blocks=0

rwset --sip=/dev/null --dip=stdout data-v6.rwf \
| rwsetcat --cidr-blocks=0 --ip-format=decimal

rwset --sip=/dev/null --dip=stdout data.rwf \
| rwsetcat --cidr-blocks=0

rwset --sip-file=stdout data-v6.rwf \
| rwsetcat --cidr-blocks=0

rwset --sip-file=stdout data.rwf \
| rwsetcat --cidr-blocks=0

cat data.rwf \
| rwset --sip-file=stdout \
| rwsetcat --cidr-blocks=0

rwsetcat --cidr set1-v4.set \
| rwsetbuild \
| rwsetcat --cidr

rwsetcat --cidr set1-v6.set \
| rwsetbuild \
| rwsetcat --cidr

rwsetcat --cidr set2-v4.set \
| rwsetbuild \
| rwsetcat --cidr

rwsetcat --cidr set2-v6.set \
| rwsetbuild \
| rwsetcat --cidr

rwset --sip-file=stdout data.rwf \
| rwsetcat --cidr-blocks \
| rwsetbuild \
| rwsetcat

rwsetcat set1-v4.set \
| rwsetbuild \
| rwsetcat --cidr

rwsetcat set2-v4.set \
| rwsetbuild \
| rwsetcat --cidr
```

```

rwset --sip-file=stdout data-v6.rwf \
| rwsetcat --cidr-blocks=0 \
| rwsetbuild stdin \
| rwsetcat --cidr-blocks=0

rwset --sip-file=stdout data.rwf \
| rwsetcat \
| rwsetbuild stdin \
| rwsetcat

rwsetcat --ip-ranges --delim=, set1-v4.set \
| cut -d, -f2,3 \
| rwsetbuild --ip-ranges=, \
| rwsetcat --cidr

rwsetcat --ip-ranges --delim=, set1-v6.set \
| cut -d, -f2,3 \
| rwsetbuild --ip-ranges=, \
| rwsetcat --cidr

rwsetcat --ip-ranges --delim=, set2-v4.set \
| cut -d, -f2,3 \
| rwsetbuild --ip-ranges=, \
| rwsetcat --cidr

rwsetcat --ip-ranges --delim=, set2-v6.set \
| cut -d, -f2,3 \
| rwsetbuild --ip-ranges=, \
| rwsetcat --cidr

rwset --sip-file=stdout data.rwf \
| rwsetcat --ip-ranges --delim=, \
| cut -d, -f2,3 \
| rwsetbuild --ip-ranges=, - - \
| rwsetcat

rwsetcat --cidr-blocks set1-v4.set

rwsetcat --cidr-blocks set1-v6.set

rwsetcat --cidr-blocks set2-v4.set

rwsetcat --cidr-blocks set2-v6.set

rwset --sip-file=stdout data.rwf \
| rwsetcat --cidr-blocks

```

```
rwsetcat --count-ips --print-filename=0 set1-v4.set set2-v4.set

rwsetcat --count-ips --print-filenames set1-v4.set

rwsetcat --count-ips set1-v4.set set2-v4.set

rwsetcat --count-ips set1-v4.set

rwsetcat --count-ips set1-v6.set

rwsetcat --count-ips set2-v4.set

rwsetcat --count-ips set2-v6.set

rwset --sip-file=stdout data.rwf \
| rwsetcat --count-ips

rwset --sip-file=stdout data.rwf \
| rwsetcat --ip-format=hexadecimal stdin

rwset --sip-file=stdout data.rwf \
| rwsetcat --output-path=stdout --ip-format=decimal

rwsetcat --ip-ranges --print-filename=1 set1-v4.set

rwsetcat --ip-ranges set1-v4.set

rwsetcat --ip-ranges --ip-format=zero-padded set1-v6.set

rwsetcat --ip-ranges set2-v4.set

rwsetcat --ip-ranges --ip-format=zero-padded set2-v6.set

rwset --sip-file=stdout data.rwf \
| rwsetcat --ip-ranges

echo 10.0.0.0/8 \
| rwsetbuild \
| rwsetcat --net=v4:T,13,17,20/10,14,18

echo 10.0.0.0/8 \
| rwsetbuild \
| rwsetcat --net=v4:ST,8,13,17,20/10,14,18,7
```

```

rwsset --sip-file=stdout data.rwf \
| rwssetcat --network-structure=12TS,12

rwssetcat --network-structure=18TS,18 set1-v4.set

rwssetcat --network-structure=20TS,20 set2-v4.set

echo 2001:db8::/32 \
| rwssetbuild \
| rwssetcat --net=v6:ST,37,41,44,32/34,38,42,31

echo 2001:db8::/32 \
| rwssetbuild \
| rwssetcat --net=v6:T,37,41,44/34,38,42

rwsset --sip-file=stdout data-v6.rwf \
| rwssetcat --network-structure=v6:48,T/48,64,123,112

rwsset --sip-file=stdout data-v6.rwf \
| rwssetcat --network-structure=v6:T60S

rwsset --sip-file=stdout data.rwf \
| rwssetcat --network-structure=ATS

rwssetcat --network-structure=v6:18TS,18/48,67,56,64 set1-v6.set

rwssetcat --network-structure set1-v4.set

rwssetcat --network-structure=v6: set1-v6.set

rwssetcat --network-structure=v6:60T,60/64,67,48,56 set2-v6.set

rwssetcat --network-structure set2-v4.set

rwssetcat --network-structure=v6: set2-v6.set

rwssettool --union set3-v4.set set3-v6.set \
| rwssetcat --network-structure=v4:8TS

rwsset --sip-file=stdout data-v6.rwf \
| rwssetcat --network-structure=v6:

rwsset --sip-file=stdout data.rwf \
| rwssetcat --network-structure

```

```

rwsetcat --cidr-blocks=0 set2-v6.set \
| head -n 257

rwset --sip-file=stdout data.rwf \
| rwsetcat --ip-format=zero-padded stdin

rwsetmember --count 10.0.15.128/25 set1-v4.set set2-v4.set \
| sed 's,.*/,,,'

rwsetmember \
--count 2001:db8:0:x:x:x:x:x set1-v6.set set2-v6.set \
| sed 's,.*/,,,'

rwsetmember \
--count 2001:db8:0:f:8000::/65 set1-v6.set set2-v6.set \
| sed 's,.*/,,,'

rwsetmember --count 10.x.x.x set1-v4.set set2-v4.set \
| sed 's,.*/,,,'

rwset --sip-file=stdout data-v6.rwf \
| rwsetmember --count 2001:db8:c0:a8::x:x -

rwset --sip-file=stdout data.rwf \
| rwsetmember --count 192.168.x.x -

rwset --sip-file=stdout data-v6.rwf \
| rwsetmember 2001:db8:c0:a8::/64 stdin

rwset --sip-file=stdout data.rwf \
| rwsetmember 192.168.0.0/16 stdin

rwsettool --difference setb.set seta.set \
| rwsetcat --cidr=1 --ip-format=map-v4

rwsettool --difference seta.set setb.set \
| rwsetcat --cidr=1 --ip-format=map-v4

rwsettool --difference setc.set seta.set \
| rwsetcat --cidr=1

rwsettool --difference seta.set setc.set \
| rwsetcat --cidr=1 --ip-format=map-v4

rwsettool --difference set1-v4.set set2-v4.set \
| rwsetcat --cidr

```

```

rwsettool --difference set1-v6.set set2-v6.set \
| rwsetcat --cidr

rwsettool --difference set2-v4.set set1-v4.set \
| rwsetcat --cidr

rwsettool --difference set2-v6.set set1-v6.set \
| rwsetcat --cidr

rwsettool --difference set3-v4.set set4-v4.set \
| rwsetcat --cidr

rwsettool --difference set3-v6.set set4-v6.set \
| rwsetcat --cidr

rwsettool --difference set4-v4.set set3-v4.set \
| rwsetcat --cidr

rwsettool --difference set4-v6.set set3-v6.set \
| rwsetcat --cidr

cp set1-v4.set /tmp/rwsettool-inplace-backup-output \
&& rwsettool --modify-inplace \
    --backup-path=/tmp/rwsettool-inplace-backup-backup \
    --output-path=/tmp/rwsettool-inplace-backup-output \
    --union /tmp/rwsettool-inplace-backup-output set2-v4.set \
&& cmp set1-v4.set /tmp/rwsettool-inplace-backup-backup \
&& rwsetcat --cidr /tmp/rwsettool-inplace-backup-output

mkdir /tmp/my-temp
&& cp set1-v4.set /tmp/my-temp/output \
&& rwsettool --modify-inplace --backup-path=/tmp/my-temp/backup \
    --output-path=/tmp/my-temp/output --union \
    /tmp/my-temp/output set2-v4.set /tmp/my-temp/nosuch \
; cmp set1-v4.set /tmp/my-temp/output \
; rm /tmp/my-temp/output \
; test 0 -eq `ls /tmp/my-temp | wc -l`

mkdir /tmp/my-temp
&& cp set1-v4.set /tmp/my-temp/output \
&& rwsettool --modify-inplace --backup-path=/tmp/my-temp/x/y/z \
    --output-path=/tmp/my-temp/output \
    --union /tmp/my-temp/output set2-v4.set \
; cmp set1-v4.set /tmp/my-temp/output \
; rm -f /tmp/my-temp/output \
; test 1 -eq `ls /tmp/my-temp | wc -l` \
; rwsetcat -cidr /tmp/my-temp/*

```

```

cp set1-v4.set /tmp/rwsettool-inplace-no-backup-output \
&& rwsettool --modify-inplace \
    --output-path=/tmp/rwsettool-inplace-no-backup-output \
    --union /tmp/rwsettool-inplace-no-backup-output set2-v4.set \
&& rwsetcat --cidr /tmp/rwsettool-inplace-no-backup-output

rwsettool --modify-inplace \
    --output-path=/tmp/rwsettool-inplace-noexist-output \
    --union set1-v4.set set2-v4.set \
&& rwsetcat --cidr /tmp/rwsettool-inplace-noexist-output

rwsettool --modify-inplace --union set1-v4.set set2-v4.set \
| rwsetcat --cidr

rwsettool --intersect set1-v4.set set2-v4.set \
| rwsetcat --cidr

rwsettool --intersect set1-v6.set set2-v6.set \
| rwsetcat --cidr

rwsettool --intersect set2-v4.set set1-v4.set \
| rwsetcat --cidr

rwsettool --intersect set2-v6.set set1-v6.set \
| rwsetcat --cidr

rwsettool --intersect set3-v4.set set4-v4.set \
| rwsetcat --cidr

rwsettool --intersect set3-v6.set set4-v6.set \
| rwsetcat --cidr

rwsettool --intersect set4-v4.set set3-v4.set \
| rwsetcat --cidr

rwsettool --intersect set4-v6.set set3-v6.set \
| rwsetcat --cidr

rwsettool --mask=12 set1-v4.set \
| rwsetcat

rwsettool --mask=12 set2-v4.set \
| rwsetcat

rwsettool --mask=13 set1-v4.set \
| rwsetcat

```

| | |
|---|---|
| rwsettool --mask=13 set2-v4.set rwsetcat | \ |
| rwsettool --mask=14 set1-v4.set rwsetcat | \ |
| rwsettool --mask=14 set2-v4.set rwsetcat | \ |
| rwsettool --mask=15 set1-v4.set rwsetcat | \ |
| rwsettool --mask=15 set2-v4.set rwsetcat | \ |
| rwsettool --mask=16 set1-v4.set rwsetcat | \ |
| rwsettool --mask=16 set2-v4.set rwsetcat | \ |
| rwsettool --mask=17 set1-v4.set rwsetcat | \ |
| rwsettool --mask=17 set2-v4.set rwsetcat | \ |
| rwsettool --mask=18 set1-v4.set rwsetcat | \ |
| rwsettool --mask=18 set2-v4.set rwsetcat | \ |
| rwsettool --mask=19 set1-v4.set rwsetcat | \ |
| rwsettool --mask=19 set2-v4.set rwsetcat | \ |
| rwsettool --mask=20 set1-v4.set rwsetcat | \ |
| rwsettool --mask=20 set2-v4.set rwsetcat | \ |

| | |
|---|---|
| rwsettool --mask=21 set1-v4.set rwsetcat | \ |
| rwsettool --mask=21 set2-v4.set rwsetcat | \ |
| rwsettool --mask=22 set1-v4.set rwsetcat | \ |
| rwsettool --mask=22 set2-v4.set rwsetcat | \ |
| rwsettool --mask=23 set1-v4.set rwsetcat | \ |
| rwsettool --mask=23 set2-v4.set rwsetcat | \ |
| rwsettool --mask=24 set1-v4.set rwsetcat | \ |
| rwsettool --mask=24 set2-v4.set rwsetcat | \ |
| rwsettool --mask=25 set1-v4.set rwsetcat | \ |
| rwsettool --mask=25 set2-v4.set rwsetcat | \ |
| rwsettool --mask=26 set1-v4.set rwsetcat | \ |
| rwsettool --mask=26 set2-v4.set rwsetcat | \ |
| rwsettool --mask=27 set1-v4.set rwsetcat | \ |
| rwsettool --mask=27 set2-v4.set rwsetcat | \ |
| rwsettool --mask=28 set1-v4.set rwsetcat | \ |

| | |
|---|---|
| rwsettool --mask=28 set2-v4.set rwsetcat | \ |
| rwsettool --mask=29 set1-v4.set rwsetcat | \ |
| rwsettool --mask=29 set2-v4.set rwsetcat | \ |
| rwsettool --mask=30 set1-v4.set rwsetcat | \ |
| rwsettool --mask=30 set2-v4.set rwsetcat | \ |
| rwsettool --mask=52 set1-v6.set rwsetcat | \ |
| rwsettool --mask=52 set2-v6.set rwsetcat | \ |
| rwsettool --mask=53 set1-v6.set rwsetcat | \ |
| rwsettool --mask=53 set2-v6.set rwsetcat | \ |
| rwsettool --mask=54 set1-v6.set rwsetcat | \ |
| rwsettool --mask=54 set2-v6.set rwsetcat | \ |
| rwsettool --mask=55 set1-v6.set rwsetcat | \ |
| rwsettool --mask=55 set2-v6.set rwsetcat | \ |
| rwsettool --mask=56 set1-v6.set rwsetcat | \ |
| rwsettool --mask=56 set2-v6.set rwsetcat | \ |

| | |
|---|---|
| rwsettool --mask=57 set1-v6.set rwsetcat | \ |
| rwsettool --mask=57 set2-v6.set rwsetcat | \ |
| rwsettool --mask=58 set1-v6.set rwsetcat | \ |
| rwsettool --mask=58 set2-v6.set rwsetcat | \ |
| rwsettool --mask=59 set1-v6.set rwsetcat | \ |
| rwsettool --mask=59 set2-v6.set rwsetcat | \ |
| rwsettool --mask=60 set1-v6.set rwsetcat | \ |
| rwsettool --mask=60 set2-v6.set rwsetcat | \ |
| rwsettool --mask=61 set1-v6.set rwsetcat | \ |
| rwsettool --mask=61 set2-v6.set rwsetcat | \ |
| rwsettool --mask=62 set1-v6.set rwsetcat | \ |
| rwsettool --mask=62 set2-v6.set rwsetcat | \ |
| rwsettool --mask=63 set1-v6.set rwsetcat | \ |
| rwsettool --mask=63 set2-v6.set rwsetcat | \ |
| rwsettool --mask=64 set1-v6.set rwsetcat | \ |

```

rwsettool --mask=64 set2-v6.set      \
| rwsetcat

rwsettool --mask=65 set1-v6.set      \
| rwsetcat

rwsettool --mask=65 set2-v6.set      \
| rwsetcat

rwsettool --mask=66 set1-v6.set      \
| rwsetcat

rwsettool --mask=66 set2-v6.set      \
| rwsetcat

rwsettool --mask=67 set1-v6.set      \
| rwsetcat

rwsettool --mask=67 set2-v6.set      \
| rwsetcat

rwsettool --mask=68 set1-v6.set      \
| rwsetcat

rwsettool --mask=68 set2-v6.set      \
| rwsetcat

rwsettool --mask=69 set1-v6.set      \
| rwsetcat

rwsettool --mask=69 set2-v6.set      \
| rwsetcat

rwsettool --mask=70 set1-v6.set      \
| rwsetcat

rwsettool --mask=70 set2-v6.set      \
| rwsetcat

printf 'NOTE: This is my notefile' > /tmp/note ;      \
rwset --note-add='NOTE: rwset note'                  \
--sip-file=/tmp/rwset-sip data.rwf ;                  \
rwsetcat --cidr-blocks=0 /tmp/rwset-sip ;              \
cat /tmp/rwset-sip                                    \
| rwfileinfo --fields=annotations - ;                  \

```

```

rwsettool --union /tmp/rwset-sip \
| rwfileinfo --fields=annotations - ; \
rwsettool --note-strip --union /tmp/rwset-sip \
| rwfileinfo --fields=annotations - ; \
rwsettool --note-strip --note-file-add=/tmp/note \
--union /tmp/rwset-sip \
| rwfileinfo --fields=annotations - ; \
echo 10.10.10.10 \
| rwsetbuild --note-add='NOTE: rwsetbuild note' \
| rwsettool --note-add='NOTE: rwsettool note' \
--union - /tmp/rwset-sip \
| rwfileinfo --fields=annotations -

rwset --sip-file=stdout data.rwf \
| rwsettool --union --output-path=stdout \
| rwsetcat

rwset --sip-file=/tmp/sipset data-v6.rwf
rwsettool --sample --ratio=0.02 --seed=2749473 /tmp/sipset \
--output-path=/tmp/sampleset
rwsetcat /tmp/sampleset
rwsettool --intersect /tmp/sipset /tmp/sampleset \
| rwsetcat
rwsetcat --count /tmp/sampleset

rwset --sip-file=/tmp/sipset data.rwf
rwsettool --sample --ratio=0.02 --seed=2749473 /tmp/sipset \
--compression=none --invocation-strip \
--output-path=/tmp/sampleset
cat /tmp/sampleset
rwsettool --intersect /tmp/sipset /tmp/sampleset \
--compression=none --invocation-strip
rwsetcat --count /tmp/sampleset

rwset --sip-file=/tmp/sipset data-v6.rwf
rwsettool --sample --size=2000 /tmp/sipset \
--output-path=/tmp/sampleset
rwsetcat /tmp/sampleset
rwsettool --intersect /tmp/sipset /tmp/sampleset \
| rwsetcat
rwsettool --sample --size=3000 /tmp/sampleset \
| rwsetcat
rwsetcat --count /tmp/sampleset
rwsettool --difference /tmp/sipset /tmp/sampleset \
| rwsettool --sample --size=100 - /tmp/sampleset \
| rwsetcat --count

rwset --sip-file=/tmp/sipset data.rwf

```

```

rwsettool --sample --size=2000 /tmp/sipset \
    --compression=none --invocation-strip \
    --output-path=/tmp/sampleset
cat /tmp/sampleset
rwsettool --intersect /tmp/sipset /tmp/sampleset \
    --compression=none --invocation-strip
rwsettool --sample --size=3000 /tmp/sampleset \
    --compression=none --invocation-strip
rwsetcat --count /tmp/sampleset
rwsettool --difference /tmp/sipset /tmp/sampleset \
| rwsettool --sample --size=100 - /tmp/sampleset \
| rwsetcat --count

rwsettool --symmetric-difference set1-v4.set set2-v4.set \
| rwsetcat --cldr

rwsettool --intersect set1-v6.set set2-v6.set > \
    /tmp/rwsettool-symmet-diff-s1-s2-v6-intersect \
&& rwsettool --union set1-v6.set set2-v6.set \
| rwsettool --difference - \
    /tmp/rwsettool-symmet-diff-s1-s2-v6-intersect \
| rwsetcat --cldr

rwsettool --intersect set2-v4.set set1-v4.set > \
    /tmp/rwsettool-symmet-diff-s2-s1-v4-intersect \
&& rwsettool --union set2-v4.set set1-v4.set \
| rwsettool --difference - \
    /tmp/rwsettool-symmet-diff-s2-s1-v4-intersect \
| rwsetcat --cldr

rwsettool --symmetric-difference set2-v6.set set1-v6.set \
| rwsetcat --cldr

rwsettool --intersect set3-v4.set set4-v4.set > \
    /tmp/rwsettool-symmet-diff-s3-s4-v4-intersect \
&& rwsettool --union set3-v4.set set4-v4.set \
| rwsettool --difference - \
    /tmp/rwsettool-symmet-diff-s3-s4-v4-intersect \
| rwsetcat --cldr

rwsettool --symmetric-difference set3-v6.set set4-v6.set \
| rwsetcat --cldr

rwsettool --symmetric-difference set4-v4.set set3-v4.set \
| rwsetcat --cldr

rwsettool --intersect set4-v6.set set3-v6.set > \

```

```

        /tmp/rwsettool-symmet-diff-s4-s3-v6-intersect \
&& rwsettool --union set4-v6.set set3-v6.set \
| rwsettool --difference - \
        /tmp/rwsettool-symmet-diff-s4-s3-v6-intersect \
| rwsetcat --cidr \

rwsplit --basename=/tmp/v4 --flow-limit=5000 data.rwf
rwsetbuild /dev/null /tmp/v4.sip
rwsetbuild /dev/null /tmp/v4.dip
rwsetbuild /dev/null /tmp/v4.any
for i in /tmp/v4*.rwf ; do \
    rwset --sip=- $i \
    | rwsettool --output=/tmp/v4.sip.union --union \
        - /tmp/v4.sip ; \
    rwsettool --difference /tmp/v4.sip /tmp/v4.sip.union \
    | rwsetcat --count ; \
    rwsetcat --cidr-blocks=1 /tmp/v4.sip ; \
    rwsettool --intersect /tmp/v4.sip.union /tmp/v4.sip \
    | rwsetcat --cidr-blocks=1 ; \
    rwsettool --intersect /tmp/v4.sip /tmp/v4.sip.union \
    | rwsetcat --cidr-blocks=1 ; \
    mv /tmp/v4.sip.union /tmp/v4.sip ; \
    rwset --dip=- $i \
    | rwsettool --output=/tmp/v4.dip.union --union \
        - /tmp/v4.dip ; \
    rwsettool --difference /tmp/v4.dip /tmp/v4.dip.union \
    | rwsetcat --count ; \
    rwsetcat --cidr-blocks=1 /tmp/v4.dip ; \
    rwsettool --intersect /tmp/v4.dip.union /tmp/v4.dip \
    | rwsetcat --cidr-blocks=1 ; \
    rwsettool --intersect /tmp/v4.dip /tmp/v4.dip.union \
    | rwsetcat --cidr-blocks=1 ; \
    mv /tmp/v4.dip.union /tmp/v4.dip ; \
    rwset --any=- $i \
    | rwsettool --output=/tmp/v4.any.union --union \
        - /tmp/v4.any ; \
    rwsettool --difference /tmp/v4.any /tmp/v4.any.union \
    | rwsetcat --count ; \
    rwsetcat --cidr-blocks=1 /tmp/v4.any ; \
    rwsettool --intersect /tmp/v4.any.union /tmp/v4.any \
    | rwsetcat --cidr-blocks=1 ; \
    rwsettool --intersect /tmp/v4.any /tmp/v4.any.union \
    | rwsetcat --cidr-blocks=1 ; \
    mv /tmp/v4.any.union /tmp/v4.any ; \
done

rwsort --fields=sip,dur,proto,sport,dport \
data.rwf data-v6.rwf \
| rwsplit --basename=/tmp/v4v6 --flow-limit=10000
rwsetbuild /dev/null /tmp/v4v6.sip

```

```

rwsetbuild /dev/null /tmp/v4v6.dip
rwsetbuild /dev/null /tmp/v4v6.any
for i in /tmp/v4v6*.rwf ; do
    rwset --sip=- $i
    | rwsettool --output=/tmp/v4v6.sip.union --union
      - /tmp/v4v6.sip ;
    rwsettool --difference /tmp/v4v6.sip /tmp/v4v6.sip.union
    | rwsetcat --count ;
    rwsetcat --cidr-blocks=1 /tmp/v4v6.sip ;
    rwsettool --intersect /tmp/v4v6.sip.union /tmp/v4v6.sip
    | rwsetcat --cidr-blocks=1 ;
    rwsettool --intersect /tmp/v4v6.sip /tmp/v4v6.sip.union
    | rwsetcat --cidr-blocks=1 ;
    mv /tmp/v4v6.sip.union /tmp/v4v6.sip ;
    rwset --dip=- $i
    | rwsettool --output=/tmp/v4v6.dip.union --union
      - /tmp/v4v6.dip ;
    rwsettool --difference /tmp/v4v6.dip /tmp/v4v6.dip.union
    | rwsetcat --count ;
    rwsetcat --cidr-blocks=1 /tmp/v4v6.dip ;
    rwsettool --intersect /tmp/v4v6.dip.union /tmp/v4v6.dip
    | rwsetcat --cidr-blocks=1 ;
    rwsettool --intersect /tmp/v4v6.dip /tmp/v4v6.dip.union
    | rwsetcat --cidr-blocks=1 ;
    mv /tmp/v4v6.dip.union /tmp/v4v6.dip ;
    rwset --any=- $i
    | rwsettool --output=/tmp/v4v6.any.union --union
      - /tmp/v4v6.any ;
    rwsettool --difference /tmp/v4v6.any /tmp/v4v6.any.union
    | rwsetcat --count ;
    rwsetcat --cidr-blocks=1 /tmp/v4v6.any ;
    rwsettool --intersect /tmp/v4v6.any.union /tmp/v4v6.any
    | rwsetcat --cidr-blocks=1 ;
    rwsettool --intersect /tmp/v4v6.any /tmp/v4v6.any.union
    | rwsetcat --cidr-blocks=1 ;
    mv /tmp/v4v6.any.union /tmp/v4v6.any ;
done

```

```

rwsplit --basename=/tmp/v6 --flow-limit=5000 data-v6.rwf
rwsetbuild /dev/null /tmp/v6.sip
rwsetbuild /dev/null /tmp/v6.dip
rwsetbuild /dev/null /tmp/v6.any
for i in /tmp/v6*.rwf ; do
    rwset --sip=- $i
    | rwsettool --output=/tmp/v6.sip.union --union
      - /tmp/v6.sip ;
    rwsettool --difference /tmp/v6.sip /tmp/v6.sip.union
    | rwsetcat --count ;
    rwsetcat --cidr-blocks=1 /tmp/v6.sip ;
    rwsettool --intersect /tmp/v6.sip.union /tmp/v6.sip

```



```

| rwssetcat --cidr-blocks=1 ; \
rwssettool --intersect /tmp/v6.sip /tmp/v6.sip.union \
| rwssetcat --cidr-blocks=1 ; \
mv /tmp/v6.sip.union /tmp/v6.sip ; \
rwsset --dip=- $i \
| rwssettool --output=/tmp/v6.dip.union --union \
- /tmp/v6.dip ; \
rwssettool --difference /tmp/v6.dip /tmp/v6.dip.union \
| rwssetcat --count ; \
rwssetcat --cidr-blocks=1 /tmp/v6.dip ; \
rwssettool --intersect /tmp/v6.dip.union /tmp/v6.dip \
| rwssetcat --cidr-blocks=1 ; \
rwssettool --intersect /tmp/v6.dip /tmp/v6.dip.union \
| rwssetcat --cidr-blocks=1 ; \
mv /tmp/v6.dip.union /tmp/v6.dip ; \
rwsset --any=- $i \
| rwssettool --output=/tmp/v6.any.union --union \
- /tmp/v6.any ; \
rwssettool --difference /tmp/v6.any /tmp/v6.any.union \
| rwssetcat --count ; \
rwssetcat --cidr-blocks=1 /tmp/v6.any ; \
rwssettool --intersect /tmp/v6.any.union /tmp/v6.any \
| rwssetcat --cidr-blocks=1 ; \
rwssettool --intersect /tmp/v6.any /tmp/v6.any.union \
| rwssetcat --cidr-blocks=1 ; \
mv /tmp/v6.any.union /tmp/v6.any ; \
done

rwssettool --union set1-v4.set set2-v4.set \
| rwssetcat --cidr

rwssettool --union set1-v6.set set2-v6.set \
| rwssetcat --cidr

rwssettool --union set2-v4.set set1-v4.set \
| rwssetcat --cidr

rwssettool --union set2-v6.set set1-v6.set \
| rwssetcat --cidr

rwssettool --union set3-v4.set set4-v4.set \
| rwssetcat --cidr

rwssettool --union set3-v6.set set4-v6.set \
| rwssetcat --cidr

rwssettool --union set4-v4.set set3-v4.set \
| rwssetcat --cidr

```

```

rwsettool --union set4-v6.set set3-v6.set \
| rwsetcat --cidr

mapsid S9 8 S11 10 S7

mapsid --print-classes

rwsiteinfo --fields=class,type,flowtype,id-flowtype,sensor,id-sensor,describe-sensor,group,default-class,default-type,mark-d
--site-config-file tests/rwsiteinfo-site.conf

rwsiteinfo --delimited --fields=class,type,sensor \
--class=@./tests/at-class.txt \
--site-config-file tests/rwsiteinfo-site.conf

rwsiteinfo --delimited --fields=class,type,sensor \
--flowtype=@./tests/at-flowtype.txt \
--site-config-file tests/rwsiteinfo-site.conf

rwsiteinfo --delimited --fields=class,type,sensor \
--sensors=@./tests/at-odd@,n@me.txt \
--site-config-file tests/rwsiteinfo-site.conf

rwsiteinfo --delimited --fields=class,type,sensor \
--sensors=@./tests/at-sensor.txt \
--site-config-file tests/rwsiteinfo-site.conf

rwsiteinfo --delimited --fields=class,type,sensor \
--type=@./tests/at-type.txt \
--site-config-file tests/rwsiteinfo-site.conf

rwsiteinfo --fields=class,default-class \
--site-config-file tests/rwsiteinfo-site.conf

rwsiteinfo --fields=class,default-type \
--site-config-file tests/rwsiteinfo-site.conf

rwsiteinfo --fields=class,sensor \
--site-config-file tests/rwsiteinfo-site.conf

rwsiteinfo --fields=class,type \
--site-config-file tests/rwsiteinfo-site.conf

rwsiteinfo --fields=class \
--site-config-file tests/rwsiteinfo-site.conf

```

```

rwsiteinfo --fields=default-class,type \
    --site-config-file tests/rwsiteinfo-site.conf

rwsiteinfo --fields=default-class \
    --site-config-file tests/rwsiteinfo-site.conf

rwsiteinfo --fields=default-type \
    --site-config-file tests/rwsiteinfo-site.conf

rwsiteinfo --delimited='+' --fields=class,type \
    --site-config-file tests/rwsiteinfo-site.conf

rwsiteinfo --fields=flowtype,sensor \
    --site-config-file tests/rwsiteinfo-site.conf

rwsiteinfo --fields=flowtype \
    --site-config-file tests/rwsiteinfo-site.conf

rwsiteinfo --output-path=stdout --fields=sensor,class \
    --classes=@,bar-class \
    --site-config-file tests/rwsiteinfo-site.conf

rwsiteinfo --fields=flowtype,class \
    --flowtypes=all/type1,bar-class/all,foo-class/type5 \
    --site-config-file tests/rwsiteinfo-site.conf

rwsiteinfo --fields=sensor,class,group --groups=SensorGroup4 \
    --site-config-file tests/rwsiteinfo-site.conf

rwsiteinfo --fields=sensor,class,group --sensors=SensorGroup4 \
    --site-config-file tests/rwsiteinfo-site.conf

rwsiteinfo --fields=sensor,class --sensors=3-5,17,S \
    --site-config-file tests/rwsiteinfo-site.conf

rwsiteinfo --fields=class,type --types=type1,@ \
    --site-config-file tests/rwsiteinfo-site.conf

rwsiteinfo --no-title --no-final-delimiter --no-columns \
    --fields=class,type \
    --site-config-file tests/rwsiteinfo-site.conf

rwsiteinfo --fields=sensor:list,class:list,type:list \
    --site-config-file tests/rwsiteinfo-site.conf

```

```

rwsiteinfo --fields=sensor,class \
    --site-config-file tests/rwsiteinfo-site.conf

rwsiteinfo --fields=sensor,group \
    --site-config-file tests/rwsiteinfo-site.conf

rwsiteinfo --fields=sensor \
    --site-config-file tests/rwsiteinfo-site.conf

rwsiteinfo --column-separator='+' --list-delimiter=';' \
    --fields=class,type:list \
    --site-config-file tests/rwsiteinfo-site.conf

rwsiteinfo --fields=type,default-type \
    --site-config-file tests/rwsiteinfo-site.conf

rwsiteinfo --fields=type \
    --site-config-file tests/rwsiteinfo-site.conf

cat data.rwf \
| rwcombine --buffer-size=1m --max-idle-time=0.002 \
    --output-path=/dev/null --print-statistics=stdout

cat data.rwf \
| rwcombine --buffer-size=1m --max-idle-time=0.002 \
| rwuniq --fields=1-5 --ipv6-policy=ignore \
    --timestamp-format=epoch \
    --values=bytes,packets,records,stime,etime \
    --sort-output --delimited --no-title

rwcombine --buffer-size=2m --max-idle-time=0.002 \
    --output-path=/dev/null --print-statistics=stdout \
    data-v6.rwf

rwcombine --buffer-size=2m --max-idle-time=0.002 \
    data-v6.rwf \
| rwuniq --fields=1-5 --ipv6-policy=force \
    --timestamp-format=epoch \
    --values=bytes,packets,records,stime,etime \
    --sort-output --delimited --no-title

rwcombine data.rwf empty.rwf --max-idle-time=0.002 \
    --output-path=/dev/null --print-statistics=stdout

rwcombine data.rwf --max-idle-time=0.002 \
| rwuniq --fields=1-5 --ipv6-policy=ignore \
    --timestamp-format=epoch \
    --values=bytes,packets,records,stime,etime \
    --sort-output --delimited --no-title

```

```

rwcombine empty.rwf data.rwf --output-path=/dev/null      \
  --print-statistics=stdout                                \

rwcombine data.rwf                                         \
| rwuniq --fields=1-5 --ipv6-policy=ignore                 \
  --timestamp-format=epoch                                 \
  --values=bytes,packets,records,stime,etime              \
  --sort-output --delimited --no-title                    \

rwdedupe --buffer-size=10m data.rwf                       \
| rwuniq --fields=1-5 --ipv6-policy=ignore                 \
  --timestamp-format=epoch                                 \
  --values=bytes,packets,records,stime,etime              \
  --sort-output --delimited --no-title                    \

rwdedupe --ignore-fields=stime data-v6.rwf empty.rwf     \
| rwuniq --fields=1-5 --ipv6-policy=force                 \
  --timestamp-format=epoch                                 \
  --values=bytes,packets,records,stime,etime              \
  --sort-output --delimited --no-title                    \

rwdedupe --ignore-fields=stime data.rwf empty.rwf        \
| rwuniq --fields=1-5 --ipv6-policy=ignore                 \
  --timestamp-format=epoch                                 \
  --values=bytes,packets,records,stime,etime              \
  --sort-output --delimited --no-title                    \

echo '2001:db8::5'
::1
10.0.0.2
2001:db8::6
::ffff:10.0.0.2' > tmp/ips
; rwtuc --fields=sip tmp/ips
| rwdedupe --ignore=sport
| rwcuc --fields=sip --no-title --delimited

echo '2001:db8::5'
::1
10.0.0.2
2001:db8::6
::ffff:10.0.0.2' > tmp/ips
; rwtuc --fields=sip tmp/ips
| rwdedupe
| rwcuc --fields=sip --no-title --delimited

rwdedupe data-v6.rwf                                     \
| rwuniq --fields=1-5 --ipv6-policy=force                 \
  --timestamp-format=epoch                                 \
  --values=bytes,packets,records,stime,etime              \
  --sort-output --delimited --no-title                    \

```

```

rwdedupe empty.rwf data.rwf \
| rwuniq --fields=1-5 --ipv6-policy=ignore \
--timestamp-format=epoch \
--values=bytes,packets,records,stime,etime \
--sort-output --delimited --no-title

rwcatt data-v6.rwf data-v6.rwf \
| rwdedupe \
| rwuniq --fields=1-5 --ipv6-policy=force \
--timestamp-format=epoch \
--values=bytes,packets,records,stime,etime \
--sort-output --delimited --no-title

rwsort --fields=sip,sensor,type,stime data.rwf data.rwf \
| rwdedupe \
| rwuniq --fields=1-5 --ipv6-policy=ignore \
--timestamp-format=epoch \
--values=bytes,packets,records,stime,etime \
--sort-output --delimited --no-title

rwsort --fields=dtype data.rwf \
| rwuniq --fields=dtype --values=dip-distinct --delimited \
--ipv6=ignore --presorted-input

rwsort --fields=stype data.rwf \
| rwuniq --fields=stype --values=sip-distinct --delimited \
--ipv6=ignore --presorted-input

rwsort --fields=bytes data.rwf empty.rwf \
| rwcatt --compression-method=none --byte-order=little \
--ipv4-output

rwsort --fields=class,type,sensor data.rwf \
| rwcatt --compression-method=none --byte-order=little \
--ipv4-output

rwsort --fields=dcc data-v6.rwf \
| rwuniq --fields=dcc --values=distinct:dip --presorted-input

rwsort --fields=dcc data.rwf \
| rwuniq --fields=dcc --values=dip-distinct --ipv6=ignore \
--presorted-input

rwsort --fields=scc data-v6.rwf \
| rwuniq --fields=scc --values=distinct:sip --presorted-input

```

```

rwsort --fields=scc data.rwf \
| rwuniq --fields=scc --values=sip-distinct --ipv6=ignore \
  --presorted-input

rwsort --fields=dip data-v6.rwf \
| rwcat --compression-method=none --byte-order=little

rwsort --fields=dip data.rwf \
| rwcat --compression-method=none --byte-order=little \
  --ipv4-output

rwsort --fields=10 data.rwf \
| rwcat --compression-method=none --byte-order=little \
  --ipv4-output

rwsort --plugin=flowrate.so --fields=bytes/sec data.rwf \
| rwuniq --plugin=flowrate.so --fields=bytes/sec \
  --values=bytes --presorted-input

rwsort --plugin=flowrate.so --fields=payload-bytes data.rwf \
| rwuniq --plugin=flowrate.so --fields=payload-bytes \
  --values=bytes,packets,records --presorted-input

rwsort --plugin=flowrate.so --fields=pckts/sec data.rwf \
| rwuniq --plugin=flowrate.so --fields=pckts/sec \
  --values=packets --presorted-input

cat data.rwf \
| rwsort --field=9,1 --input-pipe=stdin \
| rwcat --compression-method=none --byte-order=little \
  --ipv4-output

/usr/bin/env INCOMING_FLOWTYPES=all/in,all/inweb \
  OUTGOING_FLOWTYPES=all/out,all/outweb \
rwsort --plugin=int-ext-fields.so \
  --fields=ext-ip,ext-port data.rwf \
| /usr/bin/env INCOMING_FLOWTYPES=all/in,all/inweb \
  OUTGOING_FLOWTYPES=all/out,all/outweb \
rwuniq --plugin=int-ext-fields.so --delimited \
  --fields=ext-ip,ext-port --presorted-input

/usr/bin/env INCOMING_FLOWTYPES=all/in,all/inweb \
  OUTGOING_FLOWTYPES=all/out,all/outweb \
rwsort --plugin=int-ext-fields.so \
  --fields=int-ip,int-port data-v6.rwf \
| /usr/bin/env INCOMING_FLOWTYPES=all/in,all/inweb \
  OUTGOING_FLOWTYPES=all/out,all/outweb \
rwuniq --plugin=int-ext-fields.so --delimited \
  --fields=int-ip,int-port --presorted-input

```

```

rwsort --fields=5,1,3,2,4 data.rwf \
| rwuniq --fields=1-5 --ipv6-policy=ignore \
--timestamp-format=epoch \
--values=bytes,packets,records,stime,etime \
--sort-output --delimited --no-title

rwfilter --sport=20000-25000 --pass=- data.rwf \
| rwsplit --basename=/tmp/rwsort-many-presorted-onerec \
--flow-limit=1 \
&& find 'dirname /tmp/rwsort-many-presorted-onerec' -type f \
-name 'basename /tmp/rwsort-many-presorted-onerec'*' \
-print \
| rwsort --fields=sport --presorted-input --xargs=- \
| rwcut --fields=sport

rwsort --field=9,1 data.rwf data.rwf \
| rwcatt --compression-method=none --byte-order=little \
--ipv4-output

rwsort --field=9,1 --output-path=stdout data.rwf \
| rwcatt --compression-method=none --byte-order=little \
--ipv4-output

rwfilter --type=in,inweb --pass=stdout data-v6.rwf \
| rwsort --pmap-file=servhost:ip-map-v6.pmap \
--fields=dst-servhost \
| rwuniq --pmap-file=servhost:ip-map-v6.pmap \
--fields=dst-servhost --presorted-input

rwfilter --type=in,inweb --pass=stdout data.rwf \
| rwsort --pmap-file=servhost:ip-map.pmap \
--fields=dst-servhost \
| rwuniq --pmap-file=servhost:ip-map.pmap \
--fields=dst-servhost --presorted-input

rwfilter --type=in,inweb --pass=stdout data-v6.rwf \
| rwsort --pmap-file=service-port:proto-port-map.pmap \
--pmap-file=ip-map-v6.pmap \
--fields=src-service-host,src-service-port \
| rwuniq --pmap-file=service-port:proto-port-map.pmap \
--pmap-file=ip-map-v6.pmap \
--fields=src-service-host,src-service-port \
--presorted-input

rwfilter --type=in,inweb --pass=stdout data.rwf \
| rwsort --pmap-file=service-port:proto-port-map.pmap \
--pmap-file=ip-map.pmap \
--fields=src-service-host,src-service-port

```



```

| rwuniq --pmap-file=service-port:proto-port-map.pmap \
  --pmap-file=ip-map.pmap \
  --fields=src-service-host,src-service-port \
  --presorted-input

rwfilter --type=in,inweb --pass=stdout data.rwf \
| rwsort --pmap-file=proto-port-map.pmap --fields=sval \
| rwuniq --pmap-file=proto-port-map.pmap --fields=sval \
  --presorted-input

rwfilter --type=in,inweb --pass=stdout data-v6.rwf \
| rwsort --pmap-file=ip-map-v6.pmap --fields=src-service-host \
| rwuniq --pmap-file=ip-map-v6.pmap --fields=src-service-host \
  --presorted-input

rwfilter --type=in,inweb --pass=stdout data.rwf \
| rwsort --pmap-file=ip-map.pmap --fields=src-service-host \
| rwuniq --pmap-file=ip-map.pmap --fields=src-service-host \
  --presorted-input

rwfilter --proto=6 --pass=- \
  --fail=/tmp/rwsort-presorted-data1b data.rwf \
| rwsort --field=9,1 \
  --output-path=/tmp/rwsort-presorted-data1 \
&& rwfilter --proto=17 --pass=- \
  --fail=/tmp/rwsort-presorted-data2b \
  /tmp/rwsort-presorted-data1b \
| rwsort --field=9,1 \
  --output-path=/tmp/rwsort-presorted-data2 \
&& rwsort --field=9,1 \
  --output-path=/tmp/rwsort-presorted-data3 \
  /tmp/rwsort-presorted-data2b \
&& rwsort --field=9,1 --presorted \
  /tmp/rwsort-presorted-data1 empty.rwf \
  /tmp/rwsort-presorted-data2 empty.rwf \
  /tmp/rwsort-presorted-data3 \
| rwcat --compression-method=none --byte-order=little \
  --ipv4-output

rwsort --fields=5,3-4 data-v6.rwf \
| rwcat --compression-method=none --byte-order=little

rwsort --fields=5,3-4 data.rwf \
| rwcat --compression-method=none --byte-order=little \
  --ipv4-output

rwsort --python-file=pysilk-plugin.py \
  --fields=lower_port data.rwf \
| rwuniq --python-file=pysilk-plugin.py --fields=lower_port \
  --values=bytes --presorted-input

```

```

rwsort --python-file=pysilk-plugin.py \
  --fields=proto_name data.rwf \
| rwuniq --python-file=pysilk-plugin.py --fields=proto_name \
  --values=bytes --presorted-input

rwsort --python-file=pysilk-plugin.py \
  --fields=lower_port_simple data.rwf \
| rwuniq --python-file=pysilk-plugin.py \
  --fields=lower_port_simple --values=bytes \
  --presorted-input

rwsort --python-file=pysilk-plugin.py \
  --fields=server_ip data.rwf \
| rwuniq --python-file=pysilk-plugin.py --fields=server_ip \
  --values=bytes --presorted-input

rwsort --python-file=pysilk-plugin.py \
  --fields=server_ipv6 data-v6.rwf \
| rwuniq --python-file=pysilk-plugin.py --fields=server_ipv6 \
  --values=bytes --presorted-input

rwsort --fields=6 --reverse data.rwf \
| rwcat --compression-method=none --byte-order=little \
  --ipv4-output

cat data.rwf \
| rwuniq --fields=1-5 --ipv6-policy=ignore \
  --timestamp-format=epoch \
  --values=bytes,packets,records,stime,etime \
  --sort-output --delimited --no-title

rwsort --fields=1 data-v6.rwf \
| rwcat --compression-method=none --byte-order=little

rwsort --fields=1 data.rwf \
| rwcat --compression-method=none --byte-order=little \
  --ipv4-output

rwsort --plugin=skplugin-test.so --fields=copy-bytes data.rwf \
| rwuniq --plugin=skplugin-test.so --ipv6-policy=ignore \
  --fields=copy-bytes --values=bytes,packets,records \
  --presorted-input

rwsort --field=9,1 --sort-buffer-size=10M data.rwf \
| rwcat --compression-method=none --byte-order=little \
  --ipv4-output

```

```

cat data.rwf \
| rwsort --field=9,1 \
| rwcata --compression-method=none --byte-order=little \
  --ipv4-output

rwsort --fields=9,1 empty.rwf data.rwf \
| rwcata --compression-method=none --byte-order=little \
  --ipv4-output

rwsplit --basename=$temp --byte-limit=10000000 --seed=737292 \
  --file-ratio=800 data.rwf \
&& rwcata --compression-method=none --byte-order=little \
  --ipv4-output $temp*

rwsplit --basename=$temp --byte-limit=10000000 \
  --max-outputs=4 data.rwf \
&& rwcata --compression-method=none --byte-order=little \
  --ipv4-output $temp*

rwsplit --basename=$temp --byte-limit=10000000 --seed=737292 \
  --sample-ratio=1000 data.rwf \
&& rwcata --compression-method=none --byte-order=little \
  --ipv4-output $temp*

rwsplit --basename=$temp --flow-limit=10000 data.rwf \
&& rwcata --compression-method=none --byte-order=little \
  --ipv4-output $temp*

rwsplit --basename=$temp --ip-limit=5000 data.rwf \
&& rwcata --compression-method=none --byte-order=little \
  --ipv4-output $temp*

rwsplit --basename=$temp --packet-limit=10000000 data.rwf \
&& rwcata --compression-method=none --byte-order=little \
  --ipv4-output $temp*

rwsplit --basename=$temp --packet-limit=50000 --seed=737292 \
  --sample-ratio=20 --file-ratio=10 data.rwf \
&& rwcata --compression-method=none --byte-order=little \
  --ipv4-output $temp*

rwstats --fields=dtype --values=dip-distinct --delimited \
  --ipv6-policy=ignore --count=2 data.rwf

rwstats --fields=stype --values=sip-distinct --delimited \
  --ipv6-policy=ignore --count=2 data.rwf

```

```

rwstats --fields=etime --bin-time=3600 --values=bytes \
--count=100 data.rwf

rwstats --fields=stime,etime,dur --bin-time=3600 \
--values=bytes,packets,flows \
--count=500 data.rwf

rwstats --fields=stime,etime --bin-time=3600 \
--values=bytes,packets,flows --count=500 data.rwf

rwstats --fields=stime --bin-time=3600 --values=packets \
--count=100 data.rwf

rwstats --count=10 --fields=dip --column-sep=/ --top \
--ipv6-policy=ignore data.rwf

rwstats --fields=sip --top --count=10 --output-path=/dev/null \
--copy-input=stdout data.rwf
| rwstats --fields=dip --count=10 --ipv6-policy=ignore

rwstats --fields=dcc --values=dip-distinct --count=10 \
data-v6.rwf

rwstats --fields=dcc --values=dip-distinct \
--ipv6-policy=ignore --count=10 data.rwf

rwstats --fields=scc --values=sip-distinct --percentage=1 \
data-v6.rwf

rwstats --fields=scc --values=sip-distinct \
--ipv6-policy=ignore --percentage=1 data.rwf

rwstats --fields=dip --count=10 --delimited=, --top \
--ipv6-policy=ignore data.rwf

rwstats --fields=dip --values=records --percentage=4 \
--ipv6-policy=ignore data.rwf

rwstats --fields=dip --values=packets --threshold=25000 \
--top data-v6.rwf

rwstats --fields=dip --values=packets --threshold=25000 --top \
--ipv6-policy=ignore data.rwf

rwstats --dip=16 --values=bytes --count=10 --bottom \
--ipv6-policy=ignore data.rwf

```

```

rwstats --fields=application --values=distinct:sip --presorted \
--ipv6-policy=ignore --count=0 \
sips-004-008.rw sips-004-008.rw

rwstats --fields=application --values=distinct:sip --count=0 \
--ipv6-policy=ignore sips-004-008.rw sips-004-008.rw

rwfilter --dport=0-66,69-1023,8080 --pass=- data.rwf \
| rwstats --fields=dport --bottom --values=bytes --count=20

rwstats --fields=dport --values=dip-distinct,records \
--ipv6-policy=ignore --threshold=5000 data.rwf

rwfilter --dport=68 --fail=- data.rwf \
| rwstats --fields=proto,dport,iType,iCode --count=16

rwstats --fields=dport --threshold=8000 --top data.rwf

rwstats --plugin=flowrate.so --fields=bytes/sec \
--values=bytes --count=10 data.rwf

rwstats --plugin=flowrate.so --fields=payload-bytes \
--values=bytes,packets,records --count=10 data.rwf

rwstats --plugin=flowrate.so --fields=pckts/sec \
--values=packets --count=10 data.rwf

rwfilter --dport=68 --fail=- data.rwf \
| rwstats --fields=proto,iType,iCode,dport --count=16

rwfilter --proto=1 --pass=- data.rwf \
| rwstats --icmp --byte --percentage=5

/usr/bin/env INCOMING_FLOWTYPES=all/in,all/inweb \
OUTGOING_FLOWTYPES=all/out,all/outweb \
rwstats --plugin=int-ext-fields.so \
--fields=ext-ip,ext-port --values=packets,records \
--count=35 --delimited data.rwf

/usr/bin/env INCOMING_FLOWTYPES=all/in,all/inweb \
OUTGOING_FLOWTYPES=all/out,all/outweb \
rwstats --plugin=int-ext-fields.so \
--fields=int-ip,int-port --values=packets,records \
--count=65 data-v6.rwf

```

```

rwstats --fields=sip,dip --values=bytes --count=8 --top \
    --ip-format=decimal --ipv6-policy=ignore data.rwf

rwfilter --sport=20000-25000 --pass=- data.rwf \
| rwsplit --basename=/tmp/rwstats-many-presorted-onerec \
    --flow-limit=1 \
&& find 'dirname /tmp/rwstats-many-presorted-onerec' -type f \
    -name 'basename /tmp/rwstats-many-presorted-onerec'*' \
    -print \
| rwstats --fields=sport --count=70 --presorted-input \
    --values=packets,distinct:sip,flows \
    --ipv6-policy=ignore --xargs=-

rwfilter --type=in,inweb --pass=stdout data.rwf \
| rwsort --fields=3-5 \
    --output-path=/tmp/rwstats-multi-inputs-3-5-pre-in \
&& rwfilter --type=in,inweb --fail=stdout data.rwf \
| rwsort --fields=3-5 \
    --output-path=/tmp/rwstats-multi-inputs-3-5-pre-out \
&& rwstats --fields=3-5 --values=bytes,packets \
    --threshold=30000000 --presorted-input \
    /tmp/rwstats-multi-inputs-3-5-pre-in \
    /tmp/rwstats-multi-inputs-3-5-pre-out

rwfilter --type=in,inweb \
    --pass=/tmp/rwstats-multi-inputs-3-5-in \
    --fail=/tmp/rwstats-multi-inputs-3-5-out data.rwf \
&& rwstats --fields=3-5 --values=bytes,packets \
    --threshold=30000000 \
    /tmp/rwstats-multi-inputs-3-5-in \
    /tmp/rwstats-multi-inputs-3-5-out

rwstats --fields=dport --values=bytes --count=20 \
    --top empty.rwf data-v6.rwf empty.rwf data.rwf

rwstats --fields=dport --values=bytes --count=20 \
    --top data-v6.rwf data-v6.rwf empty.rwf

rwstats --fields=dport --values=bytes --count=20 \
    --top data.rwf empty.rwf data.rwf

rwstats --fields=dip --count=10 --top --no-column \
    --column-sep=, --ipv6-policy=ignore data.rwf

rwstats --fields=dip --count=10 --top --no-titles \
    --ipv6-policy=ignore data.rwf

rwstats --overall-stats data.rwf

```

```

rwfilter --type=in,inweb --pass=stdout data-v6.rwf \
| rwstats --pmap-file=servhost:ip-map-v6.pmap \
--fields=dst-servhost --count=10

rwfilter --type=in,inweb --pass=stdout data.rwf \
| rwstats --pmap-file=servhost:ip-map.pmap \
--fields=dst-servhost --count=10

rwfilter --type=in,inweb --pass=stdout data-v6.rwf \
| rwstats --pmap-file=service-port:proto-port-map.pmap \
--pmap-file=ip-map-v6.pmap \
--fields=src-service-host,src-service-port --count=10

rwfilter --type=in,inweb --pass=stdout data.rwf \
| rwstats --pmap-file=service-port:proto-port-map.pmap \
--pmap-file=ip-map.pmap \
--fields=src-service-host,src-service-port --count=10

rwfilter --type=in,inweb --pass=stdout data.rwf \
| rwstats --pmap-file=proto-port-map.pmap --fields=sval \
--bottom --count=10

rwfilter --type=in,inweb --pass=stdout data-v6.rwf \
| rwstats --pmap-file=ip-map-v6.pmap \
--fields=src-service-host --count=10

rwfilter --type=in,inweb --pass=stdout data.rwf \
| rwstats --pmap-file=ip-map.pmap --fields=src-service-host \
--count=10

rwstats --fields=protocol --values=packets --count=15 \
--bottom data.rwf

rwstats --fields=proto --values=distinct:sip,distinct:dip \
--count=5 --no-percent data-v6.rwf

rwstats --fields=proto --values=sip-distinct,dip-distinct \
--count=5 --ipv6-policy=ignore data.rwf

rwstats --detail-proto-stats=1 data.rwf

rwstats --fields=protocol --values=packets --count=15 data.rwf

rwstats --python-file=pysilk-plugin.py --fields=lower_port \
--values=max_bytes --count=10 --no-percent data.rwf

```

```

rwstats --python-file=pysilk-plugin.py --fields=lower_port      \
--value=bytes --count=10 --no-percent data.rwf

rwstats --python-file=pysilk-plugin.py                          \
--fields=lower_port_simple                                     \
--values=large_packet_flows,largest_packets,smallest_packets \
--count=5 --no-percent data.rwf

rwstats --python-file=pysilk-plugin.py --fields=sip            \
--values=max_bytes --ipv6-policy=ignore --count=10           \
--no-percent data.rwf

rwstats --fields=sip,dip --values=bytes --count=8              \
--top data-v6.rwf

rwstats --fields=sip,dip --values=bytes --count=8 --top        \
--ipv6-policy=ignore data.rwf

rwfilter --type=in,inweb --pass=stdout data.rwf               \
| rwstats --fields=sport,dport --count=5

rwstats --fields=sip --values=bytes --count=100 --top          \
--ipv6-policy=ignore data.rwf

rwstats --fields=sip --percentage=4 --top data-v6.rwf

rwstats --fields=sip --percentage=4 --top                      \
--ipv6-policy=ignore data.rwf

rwstats --sip=24 --values=packets --percentage=1 --top        \
--ipv6-policy=ignore data.rwf

rwstats --sip=24 --values=packets --percentage=2 --top        \
--ipv6-policy=ignore data.rwf

rwstats --plugin=skplugin-test.so --fields=copy-bytes         \
--values=bytes,packets,records --count=10 data.rwf

rwfilter --sport=0-66,69-1023,8080 --pass=- data.rwf          \
| rwstats --fields=sport --values=records --bottom --count=4

rwstats --fields=sport --values=sip-distinct --threshold=5000 \
--ipv6-policy=ignore data.rwf

rwstats --fields=sport,sip --values=packets,bytes --count=10  \
--ipv6-policy=ignore data.rwf

```



```

rwstats --fields=sport --values=duration,records --percent=50 \
    data.rwf

rwstats --fields=sport --values=duration,records \
    --threshold=86400 data.rwf

rwstats --fields=sport --percentage=5 data.rwf

cat data.rwf \
| rwstats --fields=dip --top --count=10 --ipv6-policy=ignore

rswapbytes --big-endian data-v6.rwf stdout \
| rwcut --fields=1-15,26-29 --timestamp-format=epoch

rswapbytes --big-endian data.rwf stdout \
| rwcut --fields=1-15,26-29 --ip-format=decimal \
    --timestamp-format=epoch --ipv6-policy=ignore

rswapbytes --little-endian data-v6.rwf - \
| rwcut --fields=1-15,26-29 --timestamp-format=epoch

rswapbytes --little-endian data.rwf - \
| rwcut --fields=1-15,26-29 --ip-format=decimal \
    --timestamp-format=epoch --ipv6-policy=ignore

cat data.rwf \
| rswapbytes --big - - \
| rwcut --fields=1-15,26-29 --ip-format=decimal \
    --timestamp-format=epoch --ipv6-policy=ignore

rswapbytes --swap-endian data.rwf stdout \
| rwcut --fields=1-15,26-29 --ip-format=decimal \
    --timestamp-format=epoch --ipv6-policy=ignore

rwttotal --bytes --skip-zero data.rwf

rwttotal --sport --output-path=/dev/null \
    --copy-input=stdout data.rwf \
| rwttotal --sport --skip-zero

rwttotal --sport --delimited --skip-zero data.rwf

rwttotal --dip-first-16 --skip-zero data.rwf

rwttotal --dip-first-24 --skip-zero data.rwf

```

```
rwtotal --dip-first-8 data.rwf

rwtotal --dip-last-16 --skip-zero data.rwf

rwtotal --dip-last-8 data.rwf

rwtotal --dport data.rwf

rwtotal --duration --skip-zero data.rwf

rwfilter --proto=1 --pass=- data.rwf \
| rwtotal --icmp-code

rwtotal --sport \
--skip-zero empty.rwf data.rwf data-v6.rwf empty.rwf

rwtotal --sport --skip-zero data-v6.rwf empty.rwf data-v6.rwf

rwtotal --sport --skip-zero data.rwf empty.rwf data.rwf

rwtotal --sport --no-column --column-sep=, data.rwf

rwtotal --sport --no-titles data.rwf

rwtotal --packets --skip-zero data.rwf

rwtotal --proto data.rwf

rwtotal --sip-first-16 --skip-zero data.rwf

rwtotal --sip-first-24 --skip-zero data.rwf

rwtotal --sip-first-8 data.rwf

rwtotal --sip-last-16 --skip-zero data.rwf

rwtotal --sip-last-8 data.rwf

rwtotal --sport --min-byte=2000 data.rwf

rwtotal --sport --min-packet=20 data.rwf

rwtotal --sport --min-record=10 data.rwf
```

```

rwttotal --sport --max-byte=2000 --skip-zero data.rwf

rwttotal --sport --max-packet=20 --skip-zero data.rwf

rwttotal --sport --max-record=10 --skip-zero data.rwf

cat data.rwf \
| rwttotal --sport --skip-zero

rwttotal --sport --summation --skip-zero data.rwf

rwcuc --fields=sip,dip,sport,dport,proto,packets,bytes,stime,dur,sensor,class,type,in,out,application,initialflags,sessionfl
| rwtuc \
| rwcuc --compression-method=none --byte-order=little

rwcuc --fields=sip,dip,sport,dport,proto,packets,bytes,stime,dur,sensor,class,type,in,out,application,initialflags,sessionfl
| rwtuc \
| rwcuc --compression-method=none --byte-order=little \
--ipv4-output

rwuniq --fields=stype,proto --values=packets \
--sort-output data.rwf

rwuniq --fields=dtype --values=dip-distinct --delimited \
--ipv6-policy=ignore --sort-output data.rwf

rwuniq --fields=stype --values=sip-distinct --delimited \
--ipv6-policy=ignore --sort-output data.rwf

rwuniq --fields=etime --bin-time=3600 --values=bytes \
--sort-output data.rwf

rwuniq --fields=sTime --values=records,sTime-earliest \
--bin-time=0.1 --sort-output data.rwf

rwuniq --fields=sTime --values=records,sTime-earliest \
--bin-time=10 --sort-output data.rwf

rwuniq --fields=stime,dur --bin-time=0.001 \
--values=bytes,packets,flows \
--sort-output data.rwf

rwuniq --fields=stime,dur --bin-time=0.001 \
--values=bytes,packets,flows \
--sort-output data.rwf

```

```

rwuniq --fields=stime,etime,dur --bin-time=3600 \
      --values=bytes,packets,flows \
      --sort-output data.rwf

rwuniq --fields=stime,etime --bin-time=3600 \
      --values=bytes,packets,flows --sort-output data.rwf

rwuniq --fields=stime --bin-time=3600 --sort-output data.rwf

rwuniq --fields=sensor,class,type --sort-output data.rwf

rwuniq --fields=sport --output-path=/dev/null \
      --copy-input=stdout data.rwf \
| rwuniq --fields=sport --sort-output

rwuniq --fields=dcc --values=distinct:scc \
      --sort-output data-v6.rwf

rwuniq --fields=dcc --values=dip-distinct --ipv6-policy=ignore \
      --sort-output data.rwf

rwuniq --fields=scc --values=distinct:dcc \
      --sort-output data-v6.rwf

rwuniq --fields=scc --values=sip-distinct --ipv6-policy=ignore \
      --sort-output data.rwf

rwuniq --fields=sport --delimited --sort-output data.rwf

rwuniq --fields=2 --ipv6-policy=ignore --ip-format=decimal \
      --bytes --sort-output data.rwf

rwuniq --fields=2 --values=packets --ipv6-policy=force \
      --sort-output data-v6.rwf

rwuniq --fields=dip --ipv6-policy=ignore \
      --ip-format=zero-padded --packets \
      --sort-output data.rwf

rwuniq --fields=dport --all-counts --sort-output data.rwf

rwuniq --fields=dport,iType,iCode,proto --sort-output data.rwf

rwuniq --fields=dport --values=duration,flows --bin-time=3600 \
      --threshold=duration=60-120 --timestamp-format=milli \
      --sort-output data.rwf

```

```

rwuniq --fields=protocol --values=duration,flows,etime-latest \
    --bin-time=0.001 --timestamp=nano --sort-output data.rwf

rwuniq --fields=sport,protocol \
    --values=duration,flows,stime-earliest --bin-time=0.001 \
    --sort-output data.rwf

rwuniq --fields=dur --bytes --sort-output data.rwf

rwuniq --fields=etime --timestamp-format=epoch \
    --sort-output data.rwf

rwuniq --plugin=flowrate.so --fields=bytes/sec --values=bytes \
    --sort-output data.rwf

rwuniq --plugin=flowrate.so --fields=payload-bytes \
    --values=bytes,packets,records --sort-output data.rwf

rwuniq --plugin=flowrate.so --fields=pckts/sec \
    --values=packets --sort-output data.rwf

rwuniq --fields=iType,iCode,dport,proto --sort-output data.rwf

rwfilter --proto=1 --pass=- data.rwf \
| rwuniq --fields=icmpTypeCode --sort-output

/usr/bin/env INCOMING_FLOWTYPES=all/in,all/inweb \
    OUTGOING_FLOWTYPES=all/out,all/outweb \
rwuniq --plugin=int-ext-fields.so \
    --fields=ext-ip,ext-port --sort-output \
    data.rwf

/usr/bin/env INCOMING_FLOWTYPES=all/in,all/inweb \
    OUTGOING_FLOWTYPES=all/out,all/outweb \
rwuniq --plugin=int-ext-fields.so \
    --fields=int-ip,int-port --sort-output \
    data-v6.rwf

rwuniq --fields=9,11 --timestamp-format=default \
    --sort-output data.rwf

rwuniq --fields=9,11 --timestamp-format=m/d/y \
    --sort-output data.rwf

rwuniq --fields=application --delimited --presorted \
    --values=distinct:proto,distinct:dip,distinct:sport,distinct:bytes,distinct:dport,distinct:sip,distinct:packet \
    sips-004-008.rw sips-004-008.rw

```

```

rwuniq --fields=application --delimited --sort-output \
--values=distinct:proto,distinct:dip,distinct:sport,distinct:bytes,distinct:dport,distinct:sip,distinct:packet \
sips-004-008.rw sips-004-008.rw

rwfilter --sport=20000-25000 --pass=- data.rwf \
| rwsplit --basename=/tmp/rwuniq-many-presorted-onerec \
--flow-limit=1 \
&& find 'dirname /tmp/rwuniq-many-presorted-onerec' -type f \
-name 'basename /tmp/rwuniq-many-presorted-onerec'*' \
-print \
| rwuniq --fields=sport --values=packets,flows,distinct:sip \
--presorted-input --ipv6-policy=ignore --xargs=-

rwuniq --fields=sport \
--sort-output empty.rwf data.rwf empty.rwf

rwuniq --fields=sport --values=records,sTime-earliest \
--nano-value-times --timestamp-format=nano \
--sort-output data.rwf

rwuniq --fields=sport --no-column --column-sep=, \
--sort-output data.rwf

rwuniq --fields=sport --no-titles --sort-output data.rwf

rwuniq --pmap-file=servhost:ip-map-v6.pmap \
--fields=dst-servhost --sort-output data-v6.rwf

rwuniq --pmap-file=servhost:ip-map.pmap --fields=dst-servhost \
--sort-output data.rwf

rwuniq --pmap-file=service-port:proto-port-map.pmap \
--pmap-file=ip-map-v6.pmap \
--fields=src-service-host,src-service-port \
--sort-output data-v6.rwf

rwuniq --pmap-file=service-port:proto-port-map.pmap \
--pmap-file=ip-map.pmap \
--fields=src-service-host,src-service-port \
--sort-output data.rwf

rwuniq --pmap-file=proto-port-map.pmap --fields=sval \
--sort-output data.rwf

rwuniq --pmap-file=ip-map-v6.pmap --fields=src-service-host \
--sort-output data-v6.rwf

```

```

rwuniq --pmap-file=ip-map.pmap --fields=src-service-host \
    --sort-output data.rwf

rwfilter --type=in,inweb --pass=stdout data.rwf \
| rwsort --fields=3-5 \
    --output-path=/tmp/rwuniq-ports-proto-multi-pre-in \
&& rwfilter --type=in,inweb --fail=stdout data.rwf \
| rwsort --fields=3-5 \
    --output-path=/tmp/rwuniq-ports-proto-multi-pre-out \
&& rwuniq --fields=3-5 --presorted-input --no-title \
    /tmp/rwuniq-ports-proto-multi-pre-in \
    /tmp/rwuniq-ports-proto-multi-pre-out

rwsort --fields=3-5 data.rwf \
| rwuniq --fields=3-5 --presorted-input --no-title

rwuniq --fields=sport,dport,proto --no-title \
    --sort-output data-v6.rwf

rwuniq --fields=sport,dport,proto --no-title \
    --sort-output data.rwf

rwuniq --fields=3-5 --no-title data.rwf \
| sort

rwuniq --fields=proto --sort-output data.rwf

rwuniq --python-file=pysilk-plugin.py --fields=lower_port \
    --values=max_bytes --sort-output data.rwf

rwuniq --python-file=pysilk-plugin.py --fields=lower_port \
    --value=bytes --sort-output data.rwf

rwuniq --python-file=pysilk-plugin.py \
    --fields=lower_port_simple \
    --values=large_packet_flows,largest_packets,smallest_packets \
    --sort-output data.rwf

rwuniq --python-file=pysilk-plugin.py --fields=sip \
    --values=max_bytes --ipv6-policy=ignore --sort-output \
    data.rwf

rwuniq --fields=sip --values=bytes --sort-output data-v6.rwf

rwuniq --fields=sip --bytes --ipv6-policy=ignore \
    --sort-output data.rwf

```

```

rwuniq --plugin=skplugin-test.so --ipv6-policy=ignore \
--no-column --fields=protocol \
--values=bytes,sum-bytes,min-bytes,max-bytes,weird-bytes \
--sort-output data.rwf

rwsort --fields=sport data.rwf \
| rwuniq --fields=sport --sip-distinct --dip-distinct \
--presorted-input --ipv6-policy=ignore

rwuniq --fields=sport --sip-distinct --dip-distinct \
--sort-output data-v6.rwf

rwuniq --fields=sport --sip-distinct --dip-distinct \
--ipv6-policy=ignore --sort-output data.rwf

rwsort --fields=sport data-v6.rwf \
| rwuniq --fields=sport --sip-distinct --presorted-input

rwsort --fields=sport data.rwf \
| rwuniq --fields=sport --sip-distinct --presorted-input \
--ipv6-policy=ignore

rwuniq --fields=sport --sip-distinct --sort-output data-v6.rwf

rwuniq --fields=sport --sip-distinct --sort-output \
--ipv6-policy=ignore data.rwf

rwuniq --fields=sport --values=distinct:sip,distinct:dip \
--sort-output data-v6.rwf

rwuniq --fields=sport --bytes=2000 --sort-output data.rwf

rwuniq --fields=sport --packets=20 --sort-output data.rwf

rwuniq --fields=sport --flows=10 --sort-output data.rwf

rwuniq --fields=sport --bytes=0-2000 --sort-output data.rwf

rwuniq --fields=sport --packets=0-20 --sort-output data.rwf

rwuniq --fields=sport --flows=0-10 --sort-output data.rwf

cat data.rwf \
| rwuniq --fields=sport --sort-output

rwuniq --fields=stime --packets --flows --sort-output data.rwf

rwuniq --fields=stime,proto --bin-time=86400 \
--sort-output data.rwf

```


9.9 Perform a checksum of the output–failure

The following tests perform a variety of checks for error conditions. The output of the command is gathered and compared to a known checksum (MD5). In all cases, the application should exit with a non-zero exit status.

```

rwfilter --proto=0- --max-pass=10000 --pass=- data.rwf      \
| rwcompare data.rwf - 2>&1

rwcompare --quiet empty.rwf data.rwf

rwcut --fields=sport,dport --start-rec-num=300              \
--end-rec-num=100 data.rwf 2>&1

rwcut --fields=sport,dport --start-rec-num=300              \
--tail-recs=100 data.rwf 2>&1

rwcut --fields=sport,dport --end-rec-num=300                 \
--tail-recs=100 data.rwf 2>&1

rwcut --fields=sport,dport --tail-recs=0 data.rwf 2>&1

rwcut --fields=sport,dport --start-rec-num=0 data.rwf 2>&1

rwflowpack ----sensor-conf=sk-teststmp-sensor.conf          \
--verify-sensor 2>&1"

rwpackchecker --value max-tcp-bpp=5000                       \
--allowable-count max-tcp-bpp=1 data.rwf

rwpackchecker --value match-sport=123                         \
--value match-dport=123 data.rwf

echo 172.16-31.x.x                                           \
| rwsetbuild - -                                             \
| rwpackchecker --value match-sip=- data.rwf

rwgroup --id-field=3 --delta-value=10 empty.rwf 2>&1

rwgroup --delta-field=9 empty.rwf 2>&1

rwgroup --id-fields=3 data.rwf empty.rwf 2>&1

rwset --sip=- empty.rwf                                       \
| rwipaimport --catalog=my-cat --description=my-description \
--start-time=2009/02/12:00:00 - 2>&1

```

```

rwset --sip=- empty.rwf \
| rwipainport --catalog=my-cat --description=my-description \
  --end-time=2009/02/14:23:59:59 - 2>&1

rwmatch --relate=1,2 data.rwf 2>&1

rwmatch --relate=1,2 data.rwf data.rwf 2>&1

rwscan empty.rwf 2>&1

rwsiteinfo --delimited --fields=class,type,sensor \
  --sensors=Sensor1,@b@d-esc@pe.txt \
  --site-config-file tests/rwsiteinfo-site.conf

rwsiteinfo --delimited --fields=class,type,sensor \
  --sensors=Sensor1,@at-no-file.txt,5 \
  --site-config-file tests/rwsiteinfo-site.conf

rwsiteinfo --delimited --fields=class,type,sensor \
  --sensors=@./tests/at-no-recurse.txt \
  --site-config-file tests/rwsiteinfo-site.conf

rwsiteinfo --delimited --fields=class,type,sensor \
  --sensors=@./tests/at-sensor.txt,@./tests/at-sensor-bad.txt \
  --site-config-file tests/rwsiteinfo-site.conf

rwsiteinfo --delimited --fields=class,type,sensor \
  --sensors=Sensor1,@trailing@ \
  --site-config-file tests/rwsiteinfo-site.conf

# Uses a long argument to sensors not captured here
rwsiteinfo --delimited='+' \
  --sensors=AbcdefghijklmnopqrstuvwxyzBCDEFG... \
  --fields=class,type \
  --site-config-file tests/rwsiteinfo-site.conf

```

9.10 Comparing checksums

The following tests perform a variety of checks. Multiple commands are run and the output of those commands are gathered. The checksum (MD5) of the outputs are compared to ensure the outputs are identical.

```

rwcat --byte-order=little empty.rwf \
| rwfileinfo --fields=byte-order --no-title -

rwfileinfo --fields=3 --no-title empty.rwf

```

```
rwcat --compression-method=none empty.rwf \
| rwfileinfo --fields=compression --no-title -

rwfileinfo --fields=4 --no-title empty.rwf
```